



WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

)	DOCKET NO. TR-010316
The Burlington Northern and Santa Fe)	
Railway Company)	
_____)	PETITION TO CONSTRUCT OR
Petitioner,)	RECONSTRUCT A HIGHWAY-RAIL
)	GRADE CROSSING AND INSTALL
vs.)	AN INTER-TIE BETWEEN A
City of Renton, Washington)	HIGHWAY SIGNAL AND A
_____)	RAILROAD CROSSING SIGNAL
Respondent)	SYSTEM
)	
)	USDOT CROSSING NO.: 91-724U

Prior to submitting a Petition to Construct a highway-rail grade crossing and install an inter-tie between a Highway Signal and a Railroad Crossing Signal System to the Washington Utilities and Transportation Commission (UTC), State Environmental Protection Act (SEPA) requirements must be met. Washington Administrative Code (WAC) 197-11-865 (2) requires:

All actions of the utilities and transportation commission under statutes administered as of December 12, 1975, are exempted, except the following:

(2) Authorization of the openings or closing of any highway/railroad grade crossing, or the direction of physical connection of the line of one railroad with that of another;


Please attach sufficient documentation to demonstrate that the SEPA requirement has been fulfilled. For additional information on SEPA requirements contact the Department of Ecology.

The Petitioner asks the Washington Utilities and Transportation Commission to approve construction or reconstruction of a highway-rail grade crossing and inter-tie the highway signal with the railroad crossing signal system.

Construction Reconstruction

WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION
STAFF OFFICE
2014 AUG 20 AM 8:48
WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

Section 1 – Petitioner's Information

The Burlington Northern and Santa Fe Railway Company
Petitioner

Signature
2454 Occidental Avenue South, Suite 1-A
Street Address
Seattle WA 98134
City, State and Zip Code
Mailing Address, if different than the street address
Richard W. Wagner
Contact Person Name
206-625- 6152/6356 Richard.Wagner@BNSF.com
Contact Phone Number and E-mail Address

Section 2 – Respondent's Information

City of Renton
Respondent
1055 South Grady Way
Street Address
Renton WA 98057
City, State and Zip Code
Mailing Address, if different than the street address
James P. Wilhoit
Contact Person Name
(425) 430-7319, jwilhoit@rentonwa.gov
Contact Phone Number and E-mail Address

Section 3 – Proposed or Existing Crossing Location

1. Existing highway/roadway Lake Washington Boulevard

2. Existing railroad The Burlington Northern & Santa Fe Ry.

3. Location of proposed crossing:
 Located in the NE 1/4 of the NW1/4 of Sec. 8 , Twp. 23., Range 5 W.M.

4. GPS location, if known 47.5028364, -122.1997135

5. Railroad mile post (nearest tenth) 3.97

6. City Renton County King

Section 4 – Proposed or Existing Crossing Information

1. Railroad company The Burlington Northern & Santa Fe Ry.

2. Type of railroad at crossing Common Carrier Logging Industrial
 Passenger Excursion

3. Type of tracks at crossing Main Line Siding or Spur

4. Number of tracks at crossing 1

5. Average daily train traffic, freight 1
 Authorized freight train speed 10 Operated freight train speed 10

6. Average daily train traffic, passenger 0
 Authorized passenger train speed N/A Operated passenger train speed N/A

7. Will the proposed crossing eliminate the need for one or more existing crossings?
 Yes No X

8. If so, state the distance and direction from the proposed crossing.

9. Does the petitioner propose to close any existing crossings?

Yes No

Section 5 – Temporary Crossing

1. Is the crossing proposed to be temporary? Yes No

2. If so, describe the purpose of the crossing and the estimated time it will be needed

3. Will the petitioner remove the crossing at completion of the activity requiring the temporary crossing? Yes No

Approximate date of removal _____

Section 6 – Current Highway Traffic Information

1. Name of roadway/highway Lake Washington Boulevard

2. Roadway classification public city road

3. Road authority City of Renton

4. Average annual daily traffic (AADT) 18,000

5. Number of lanes 2

6. Roadway speed 25 MPH

7. Is the crossing part of an established truck route? Yes No

8. If so, trucks are what percent of total daily traffic? _____

9. Is the crossing part of an established school bus route? Yes No

10. If so, how many school buses travel over the crossing each day? 16

11. Describe any changes to the information in 1 through 7, above, expected within ten years:

Section 7 – Alternatives to the Proposal

1. Does a safer location for a crossing exist within a reasonable distance of the proposed location?
Yes No

2. If a safer location exists, explain why the crossing should not be located at that site.

3. Are there any hillsides, embankments, buildings, trees, railroad loading platforms or other barriers in the vicinity which may obstruct a motorist's view of the crossing?
Yes No

4. If a barrier exists, describe:

- ◆ Whether petitioner can relocate the crossing to avoid the obstruction and if not, why not.
- ◆ How the barrier can be removed.
- ◆ How the petitioner or another party can mitigate the hazard caused by the barrier.

I-405 freeway overhead, piers can block sight distance

5. Is it feasible to construct an over-crossing or under-crossing at the proposed location as an alternative to an at-grade crossing?
Yes No

6. If an over-crossing or under-crossing is not feasible, explain why.

I-405 freeway overhead is too close to intersection, price of grade separation underpass is

~~very high and beyond current budget and traffic volumes do not warrant grade separation.~~

7. Does the railway line, at any point in the vicinity of the proposed crossing, pass over a fill area or trestle or through a cut where it is feasible to construct an over-crossing or an under-crossing, even though it may be necessary to relocate a portion of the roadway to reach that point?

Yes No

8. If such a location exists, state:

- ◆ The distance and direction from the proposed crossing.
- ◆ The approximate cost of construction.
- ◆ Any reasons that exist to prevent locating the crossing at this site.

9. Is there an existing public or private crossing in the vicinity of the proposed crossing?

Yes No

10. If a crossing exists, state:

- ◆ The distance and direction from the proposed crossing.
- ◆ Whether it is feasible to divert traffic from the proposed to the existing crossing.

◆ 0.02 mile south- Park Drive overhead bridge- Public

0.08 mile north - Gene Coulon Park -Public crossing

◆ Not feasible to divert traffic from the proposed to the existing crossing

Section 8 – Sight Distance

1. Complete the following table, describing the sight distance for motorists when approaching the tracks from either direction.

a. Approaching the crossing from South, the current approach provides an unobstructed view as follows: (North, South, East, West)

Direction of sight (left or right)	Number of feet from proposed crossing	Provides an unobstructed view for how many feet
Right	300	View obstructed
Right	200	View obstructed
Right	100	130
Right	50	60
Right	25	30
Left	300	650
Left	200	780
Left	100	890
Left	50	950
Left	25	850

b. Approaching the crossing from North, the current approach provides an unobstructed view as follows: (Opposite direction-North, South, East, West)

Direction of sight (left or right)	Number of feet from proposed crossing	Provides an unobstructed view for how many feet
Right	300	View obstructed
Right	200	200
Right	100	100
Right	50	50
Right	25	30
Left	300	330
Left	200	400
Left	100	500
Left	50	620
Left	25	850

2. Will the new crossing provide a level approach measuring 25 feet from the center of the railway on both approaches to the crossing?

Yes X No

3. If not, state in feet the length of level grade from the center of the railway on both approaches to the crossing. _____

4. Will the new crossing provide an approach grade of not more than five percent prior to the level grade?

Yes X No

5. If not, state the percentage of grade prior to the level grade and explain why the grade exceeds five percent.

Section 9 – Illustration of Proposed Crossing Configuration

Attach a detailed diagram, drawing, map or other illustration showing the following:

- ◆ The vicinity of the proposed crossing.
- ◆ Layout of the railway and highway 500 feet adjacent to the crossing in all directions.
- ◆ Percent of grade.
- ◆ Obstructions of view as described in Section 7 or identified in Section 8.
- ◆ Traffic control layout showing the location of the existing and proposed signage.

Section 10 – Sidewalks

1. Provide the following information:

- a. Provide a description of the type of sidewalks proposed.
 - b. Describe who will maintain the sidewalks.
 - c. Attach a proposed diagram or design of the crossing including the sidewalks.
- a. & c. See attached exhibit

b. City of Renton and Southport development will maintain the sidewalks.

Section 11 – Proposed Warning Signals or Devices

1. Explain in detail the number and type of automatic signals or other warning devices planned at the proposed crossing, including a cost estimate for each. If requesting pre-emption include the type of train detection circuitry, sequencing and advanced preemption time, justification for the changes and its effects on current warning devices and warning times for drivers.

Install automatic flashing light traffic control devices (1 cantilever and 1 shoulder mounted type) with gates and constant warning time devices. Total cost \$128,808

2. Provide an estimate for maintaining the signals for 12 months. _____

3. Is the petitioner prepared to pay to the respondent railroad company its share of installing the warning devices as provided by law?
 Yes _____ No _____ City of Renton is funding project per agreement

Section 12 – Traffic Signal Preemption

Complete the attached Guide for Determining Time Requirements for Traffic Signal Preemption at Highway-Rail Grade Crossings.

1. Specify simultaneous or advance preemption requested.

If advance preemption, what is the preemption time.

Section 13 – Additional Information

Provide any additional information supporting the proposal, including information such as the public benefits that would be derived from constructing a new crossing as proposed or modifying an existing crossing. Provide project specific information.

Section 14 – Waiver of Hearing by Respondent

Waiver of Hearing

The undersigned represents the Respondent in the petition to construct or reconstruct a highway-railroad grade crossing and inter-tie the highway signal with the railroad crossing signal system.

USDOT Crossing No.: 91-724U

We have investigated the conditions at the proposed or existing crossing site. We are satisfied the conditions are the same as described by the Petitioner in this docket. We agree that a crossing be installed or reconstructed and the highway signals inter-tied with the railroad crossing signal system and consent to a decision by the commission without a hearing.

Dated at Renton, Washington, on the 15th day of
August, 2014.

Gregg Zimmerman

Printed name of Respondent

Gregg Zimmerman

Signature of Respondent's Representative

Public Works Administrator

Title

City of Renton

Name of Company

425-430-7311 gzimmerman@rentonwa.gov

Phone number and e-mail address

City Hall, 5th Floor,


1055 South Grady Way
Renton WA 98057

Mailing address

GUIDE FOR DETERMINING TIME REQUIREMENTS FOR TRAFFIC SIGNAL PREEMPTION AT HIGHWAY-RAIL GRADE CROSSINGS

City Renton, WA
 County King
 District King County

Date 06/20/14
 Completed by CTC Inc.
 District Approval _____



Parallel Street Name
Southport Boulevard
 Crossing Street Name
Lake Washington Boulevard

Railroad BNSF
 Crossing DOT# 091724U

Railroad Contact Rick Wagner
 Phone (206) 625-6152

SECTION 1: RIGHT-OF-WAY TRANSFER TIME CALCULATION

Preempt verification and response time

Item	Description	Value	Remarks
1.	Preempt delay time (seconds)	0.0	Prop. Firmware 4.53a
2.	Controller response time to preempt (seconds)	1.0	Controller type <u>Eagle M50</u>
3.	Preempt verification and response time (seconds): add lines 1 and 2	1.0	

Worst-case conflicting vehicle time

Item	Description	Value	Remarks
4.	Worst-case conflicting vehicle phase number		
5.	Minimum green time during right-of-way transfer (seconds)	5.00	
6.	Other green time during right-of-way transfer (seconds)	0.00	
7.	Yellow change time (seconds)	3.50	
8.	Red clearance time (seconds)	2.00	
9.	Worst-case conflicting vehicle time (seconds): add lines 5 through 8	10.5	

Worst-case conflicting pedestrian time


Item	Description	Value	Remarks
10.	Worst-case conflicting pedestrian phase number		
11.	Minimum walk time during right-of-way transfer (seconds)	0.0	
12.	Pedestrian clearance time during right-of-way transfer (seconds)	20.0	
13.	Vehicle yellow change time, if not included on line 12 (seconds)	3.5	
14.	Vehicle red clearance time, if not included on line 12 (seconds)	2.0	
15.	Worst-case conflicting pedestrian time (seconds): add lines 11 through 14	25.5	

Worst-case conflicting vehicle or pedestrian time

16.	Worst-case conflicting vehicle or pedestrian time (seconds): maximum of lines 9 and 15	25.5
17.	Right-of-way transfer time (seconds): add lines 3 and 16	26.5

SECTION 2: QUEUE CLEARANCE TIME CALCULATION

Form 2364
(6/3/99)
Page 2 of 3



CSD = Clear storage distance
 MTCD = Minimum track clearance distance
 DVL = Design vehicle length
 L = Queue start-up distance, also stop-line distance
 DVCD = Design vehicle clearance distance

		Remarks
18. Clear storage distance (CSD, feet)	18.	57
19. Minimum track clearance distance (MTCD, feet)	19.	116
20. Design vehicle length (DVL, feet)	20.	75
		Design vehicle type <u>Tractor-Trailer</u>
21. Queue start-up distance, L (feet) add lines 18 and 19	21.	173
		Remarks
22. Time required for design vehicle to start moving (seconds): calculate as $2+(L \div 20)$	22.	10.7
23. Design vehicle clearance distance, DVCD (feet): add lines 19 and 20	23.	191
24. Time for design vehicle to accelerate through the DVCD (seconds)	24.	19.1
		Read from Figure 2 in Instructions
25. Queue clearance time (seconds): add lines 22 and 24	25.	29.8

SECTION 3: MAXIMUM PREEMPTION TIME CALCULATION

		Remarks
26. Right-of-way transfer time (seconds) line 17	26.	26.5
27. Queue clearance time (seconds) line 25	27.	29.8
28. Desired minimum separation time (seconds)	28.	4.0
29. Maximum preemption time (seconds): add lines 26 through 28	29.	60.3

SECTION 4: SUFFICIENT WARNING TIME CHECK

		Remarks
30. Required minimum time, MT (seconds): per regulations	30.	20.0
31. Clearance time, CT (seconds) get from railroad	31.	12.0
		Existing BNSF design
32. Minimum warning time, MWT (seconds) add lines	32.	32.0
		Excludes buffer time (BT)
33. Advance preemption time, APT, if provided (seconds) get from railroad	33.	0.0
34. Warning time provided by the railroad (seconds) add lines 32 and 33	34.	32.0
35. Additional warning time required from railroad (seconds): subtract line 34 from line 29, round up to nearest full second, enter 0 if less than 0	35.	29

If the additional warning time required (line 35) is greater than zero, additional warning time has to be requested from the railroad. Alternatively, the maximum preemption time (line 29) may be decreased after performing an engineering study to investigate the possibility of reducing the values on lines 1, 5, 6, 7, 8, 11, 12, 13 and 14.

Remarks: _____

SECTION 5: TRACK CLEARANCE GREEN TIME CALCULATION (OPTIONAL)

Form 210
Rev. 11/11

Preempt Trap Check

36. Advance preemption time (APT) provided (seconds)	36.	29.0	Line 33 only valid if line 35 is zero
37. Multiplier for maximum APT due to train handling	37.	1.00	See Instructions for details
38. Maximum APT (seconds): multiply line 36 and 37	38.	29.0	Remarks
39. Minimum duration for the track clearance green interval (seconds)	39.	15.0	For zero advance preemption time
40. Gates down after start of preemption (seconds) add lines 38 and 39	40.	44.0	
41. Preempt verification and response time (seconds) line 3	41.	1.0	Remarks
42. Best-case conflicting vehicle or pedestrian time (seconds) usually 0	42.	0.0	
43. Minimum right-of-way transfer time (seconds) add lines 41 and 42	43.	1.0	
44. Minimum track clearance green time (seconds) subtract line 43 from line 40	44.	43.0	
Clearing of Clear Storage Distance			
45. Time required for design vehicle to start moving (seconds) line 22	45.	10.7	
46. Design vehicle clearance distance (DVCD, feet) line 23	46.	191	Remarks
47. Portion of CSD to clear during track clearance phase (feet)	47.	57	CSD* in Figure 3 in Instructions
48. Design vehicle relocation distance (DVRD, feet) add lines 46 and 47	48.	248	
49. Time required for design vehicle to accelerate through DVRD (seconds)	49.	21.9	Read from Figure 2 in Instructions
50. Time to clear portion of clear storage distance (seconds) add lines 45 and 49	50.	32.6	
51. Track clearance green interval (seconds): maximum of lines 44 and 50, round up to nearest full second	51.	43	

SECTION 6: VEHICLE-GATE INTERACTION CHECK (OPTIONAL)

52. Right-of-way transfer time (seconds) line 17	52.	28.5	
53. Time required for design vehicle to start moving (seconds) line 22	53.	10.7	
54. Time required for design vehicle to accelerate through DVL (on line 20 seconds)	54.		Read from Table 3 in Instructions
55. Time required for design vehicle to clear descending gate (seconds) add lines 52 through 54	55.	37.2	Remarks
56. Duration of flashing lights before gate descent start (seconds) get from railroad	56.		Remarks
57. Full gate descent time (seconds) get from railroad	57.		
58. Proportion of non-interaction gate descent time	58.		Read from Figure 5 in Instructions
59. Non-Interaction gate descent time (seconds) multiply lines 57 and 58	59.	0.0	
60. Time available for design vehicle to clear descending gate (seconds) add lines 56 and 59	60.	0.0	
61. Advance preemption time (APT) required to avoid design vehicle-gate interaction (seconds): subtract line 60 from line 55, round up to nearest full second, enter 0 if less than 0	61.	38	



INSTRUCTIONS

GUIDE FOR DETERMINING TIME REQUIREMENTS FOR TRAFFIC SIGNAL PREEMPTION AT HIGHWAY-RAIL GRADE CROSSINGS

USING THESE INSTRUCTIONS: *These instructions are designed to assist applicants in completing the Guide For Determining Time Requirements For Traffic Signal Preemption At Highway-Rail Grade Crossings. This assists in determining if additional time (advance preemption) is required for the traffic signal to move stationary vehicles out of the crossing before the arrival of the train. If you have any questions about completing the form, please contact Kathy Hunter, commission staff at (360)664-1257 or by e-mail at khunter@utc.wa.gov.*

SITE DESCRIPTIVE INFORMATION:

Enter the location for the highway-rail grade crossing including the (nearest) **City** and the **County** in which the crossing is located. Next, enter the **Date** the analysis was performed, your (the analyst's) name next to **Completed by**.

To complete the reference schematic for this site, place a **North Arrow** in the provided circle to correctly orient the crossing and roadway. Record the name of the **Parallel Street** and the **Crossing Street** in the spaces provided and remember to include any street sign or local name for the streets as well as any state or interstate highway designation. You may wish to note other details on the intersection and crossing diagram as well, including the number of lanes or turn bays on the intersection approach crossing the tracks and any adjacent land use.

Enter the **Railroad** name, **Railroad Contact** person's name and **Phone** number for the responsible railroad company and its equipment maintenance and operations contractor (if any). Finally, record the unique 7-character **Crossing USDOT#** (6 numeric plus one alphanumeric characters) for the crossing.

Note that this guide for determining warning time requirements for traffic signal preemption requires you to input many controller unit timing and phasing values. To preserve the accuracy of these values, record all values to the next highest tenth of a second (i.e., record 5.42 seconds as 5.5 seconds).

SECTION 1: RIGHT-OF-WAY TRANSFER TIME CALCULATION

Preempt Verification and Response Time

Line 1. The **preempt delay time** is the amount of time, in seconds, that the traffic signal controller is programmed to wait from the initial receipt of a preempt call until the call is "verified" and considered a viable request for transfer into preemption mode. Preempt delay time is a value entered into the controller unit for purposes of preempt call validation, and may not be available on all manufacturer's controllers.

Line 2. Unlike preempt delay time (Line 1) which is a value entered into the controller, **controller response time to preempt** is the time that elapses while the controller unit electronically registers the preempt call (i.e., it is the controller's equipment response time for the preempt call). The controller manufacturer should be consulted to find the correct value (in seconds) for use here. For future reference, you may wish to record the controller type in the **Remarks** section to the right of the controller response time to preempt value. However, note that the manufacturer's given response time may be unique for a controller unit's model and software generation; other models and/or software generations may have different response times.

Line 3. The sum of Line 1 and Line 2 is the **preempt verification and response time**, in seconds. It represents the number of seconds between the receipt at the controller unit of a preempt call issued by the railroad's grade crossing warning equipment and the time the controller software actually begins to respond to the preempt call (i.e., by transitioning into preemption mode).

Worst-Case Conflicting Vehicle Time

Line 4. **Worst-case conflicting vehicle phase number** is the number of the controller unit phase which

conflicts with the phase(s) used to clear the tracks—the track clearance phase(s)—that has the longest sum of minimum green (if provided), other (additional) green time (if provided), yellow change interval, and red clearance interval durations that may need to be serviced during the transition into preemption. Note that all of these time elements are for vehicular phases only; pedestrian phase times will be assessed in the next part of the analysis. The worst-case vehicle phase can be any phase that conflicts with the track clearance phase(s); it is not restricted to only the phases serving traffic parallel to the tracks.

Line 5. Minimum green time during right-of-way transfer is the number of seconds that the worst-case vehicle phase (see Line 4 discussion) must display a green indication before the controller unit will terminate the phase through its yellow change and red clearance intervals and transition to the track clearance green interval. The minimum green time during right-of-way transfer may be set to zero to allow as rapid a transition as possible to the track clearance green interval. However, local policies will govern the amount of minimum green time provided during the transition into preemption.

Line 6. If any additional green time is preserved beyond the preempt minimum green time for the worst-case vehicle phase (line 4), it should be entered here as **Other green time during right-of-way transfer**. Given the time-critical nature of the transition to the track clearance green interval during preempted operation, this value is usually zero except in unusual circumstances. One situation where other green time may be present is when a trailing green overlap is used on the worst-case vehicle phase, and the controller unit is set up to time out the trailing green overlap on entry into preemption.

Line 7. Yellow change time is the required yellow change interval time for the worst-case vehicle phase (line 4) given prevailing operating conditions. Yellow change time for the phase under preemption is usually the same value, in seconds, programmed for the phase under normal operating circumstances.

Line 8. Red clearance time is the required red clearance interval for the worst-case vehicle phase (line 4) given prevailing operating conditions. Red clearance time for the phase under preemption is usually the same value, in seconds, programmed for the phase under normal operating circumstances.

Line 9. Worst-case conflicting vehicle time is the sum of lines 5 through 8. It will be compared with the worst-case conflicting pedestrian time to determine whether vehicle or pedestrian phase times are the most critical in their impact on warning time requirements during the transition to the track clearance green interval.

Worst-case Conflicting Pedestrian Time

Line 10. Worst-case pedestrian phase number is the pedestrian phase number (referenced as the vehicle phase number that the pedestrian phase is associated with) that has the longest sum of walk time, pedestrian clearance (i.e., flashing don't walk) times, and associated vehicle clearance times that have to be provided during the transition into preemption. The worst-case pedestrian phase is not restricted to pedestrian phases running concurrently with vehicle phases that serve traffic parallel to the tracks. The vehicle phase associated with the worst-case pedestrian phase may even be one of the track clearance phases if the pedestrian phase is not serviced concurrently with the associated track clearance phase.

Line 11. Minimum walk time during right-of-way transfer (seconds) is the minimum pedestrian walk time for the worst-case pedestrian phase (line 10).

Line 12. Pedestrian clearance time during right-of-way transfer (seconds) is the clearance (i.e., flashing don't walk) time for the worst-case pedestrian phase.

Line 13. Enter a **Yellow change time** if the pedestrian clearance interval does not time simultaneously with the yellow change interval of the vehicular phase associated with your worst-case pedestrian phase; enter zero if does. Local policies will determine if this is allowed. Simultaneous timing of the pedestrian clearance interval and the yellow change interval (i.e. a zero value on line 13) allows for the most rapid transition to the track clearance green interval. If a non-zero value is entered, make sure to enter the yellow change time of the vehicular phase associated with your worst-case pedestrian phase. This value

may not be the same value you enter on Line 7, since the worst-case pedestrian phase may not be the same as the worst-case vehicular phase.

Line 14. Enter a **Red clearance time** if the pedestrian clearance interval does not time simultaneously with the red clearance interval of the vehicular phase associated with your worst-case pedestrian phase; enter zero if it does. Local policies will determine if this is allowed. Also, note that not all traffic signal controllers allow simultaneous timing of the pedestrian clearance interval and the red clearance interval. Simultaneous timing of the pedestrian clearance interval and the red clearance interval (i.e. a zero value on line 14) allows for the most rapid transition to the track clearance green interval. If a non-zero value is entered, make sure to enter the red clearance time of the vehicular phase associated with your worst-case pedestrian phase. This value may not be the same value you enter on Line 8, since the worst-case pedestrian phase may not be the same as the worst-case vehicular phase.

Line 15. Add lines 11 through 14 to calculate the **Worst -case conflicting pedestrian time**. This value will be compared to the worst-case conflicting vehicle time to determine whether vehicle or pedestrian phase times are the most critical in their impact on warning time requirements during the transition to the track clearance green interval.

Worst-case Conflicting Vehicle or Pedestrian Time

Line 16. Record the **Worst-case conflicting vehicle or pedestrian time** (in seconds) by comparing lines 9 and 15 and writing the larger of the two as the entry for line 16.

Line 17. Calculate the **Right-of-way transfer time** by adding lines 3 and 16. The right-of-way transfer time is the maximum amount of time needed for the worst case condition, prior to display of the track clearance green interval.




Figure 1 Queue clearance distances.

SECTION 2: QUEUE CLEARANCE TIME CALCULATION

Line 18. Record the **Clear storage distance (CSD in Figure 1)**, in feet, as the shortest distance along the crossing street between the edge of the grade crossing nearest the signalized intersection—identified by a line parallel to the rail 6 feet (2 m) from the rail nearest to the intersection—and the edge of the street or shoulder of street that parallels the tracks. If the normal stopping point on the crossing street is significant different from the edge or shoulder of parallel street, measure the distance to the normal stopping point. For angled (i.e., non-perpendicular) railroad crossings, always measure the distance along the inside (centerline) edge of the leftmost lane or the distance along the outside (shoulder) edge of the rightmost lane, as appropriate, to determine the shortest clear storage distance and record that value.

Line 19. **Minimum track clearance distance (MTCD in Figure 1)**, in feet, is the length along the highway

at one or more railroad tracks, measured from the railroad crossing stop line, warning device, or 12 feet (4 m) perpendicular to the track centerline—whichever is further away from the tracks, to 6 feet (2 m) beyond the tracks measured perpendicular to the far rail. For angled (i.e., non-perpendicular) railroad crossings, always measure the distance along the inside (centerline) edge of the leftmost lane or the distance along the outside (shoulder) edge of the rightmost lane, as appropriate, to determine the longest minimum track clearance distance and record that value.

Line 20. Design vehicle length (DVL in Figure 1), in feet, is the length of the design vehicle, the longest vehicle permitted by road authority statute on the subject roadway. In the **Remarks** section to the right of the data entry box for Line 20, note the design vehicle type for ease of reference. Some design vehicles from the *AASHTO Green Book (A Policy on Geometric Design of Highways and Streets)* are given in Table 1.

Table 1. AASHTO Design vehicle lengths and heights.

Design Vehicle Type	Symbol	Length (ft)
Passenger Car	P	19
Single Unit Truck	SU	30
Large School Bus	S-BUS 40	40
Intermediate Semi-Trailer	WB-50	55

Line 21. Queue start-up distance (L in Figure 1), in feet, is the maximum length over which a queue of vehicles stopped for a red signal indication at an intersection downstream of the crossing must get in motion so that the design vehicle can move out of the railroad crossing prior to the train's arrival. Queue start-up distance is the sum of the clear storage distance (Line 18) and minimum track clearance distance (Line 19).

Line 22. Time required for the design vehicle to start moving (seconds) is the time elapsed between the start of the track clearance green interval and the time the design vehicle, which is located at the edge of the railroad crossing on the opposite side from the signalized intersection, begins to move. This elapsed time is based on a "shock wave" speed of 20 feet per second and a 2 second start-up time (the additional time for the first driver to recognize the signal is green and move his/her foot from the brake to the accelerator). The time required for the design vehicle to start moving is calculated, in seconds, as 2 plus the queue start-up distance, L (Line 21) divided by the wave speed of 20 feet per second. The time required for the design vehicle to start moving is a conservative value taking into account the worst-case vehicle mix in the queue in front of the design vehicle as well as a limited level of driver inattentiveness. This value may be overridden by local observation, but care must be taken to identify the worst-case (longest) time required for the design vehicle to start moving.

Line 23. Design vehicle clearance distance (DVCD in Figure 1) is the length, in feet, which the design vehicle must travel in order to enter and completely pass through the railroad crossing's minimum track clearance distance (MTCDD). It is the sum of the minimum track clearance distance (Line 19) and the design vehicle's length (Line 20).

Line 24. The Time for design vehicle to accelerate through the design vehicle clearance distance (DVCD) is the amount of time required for the design vehicle to accelerate from a stop and travel the complete design vehicle clearance distance. This time value, in seconds, can be found through local observation or by using Figure 2. If local observation is used, take care to identify the worst-case (longest) time required for the design vehicle to accelerate through the DVCD. If Figure 2 is used to estimate the time for the design vehicle to accelerate through the DVCD, locate the DVCD from Line 23 on the horizontal axis of Figure 2 and then draw a line straight up until that line intersects the acceleration time performance curve for your design vehicle. Then, draw a horizontal line from this point to the left until it intersects the vertical axis, and record the appropriate acceleration time. Round up to the next higher tenth of a second. For example, with a DVCD of 80 feet and a WB-50 semi-trailer design vehicle on a level surface, the time required for the design vehicle to accelerate through the DVCD will be 12.2 seconds.

If your design vehicle is a WB-50 semi-trailer, large school bus (S-BUS 40), or single unit (SU) vehicle, you may need to apply a correction factor to estimate the effect of grade on the acceleration of the vehicle. Determine the average grade over a distance equal to the design vehicle clearance distance

(DVCD), centered around the minimum track clearance distance (MTCD). If the grade is 1% uphill (+1%) or greater, multiply the acceleration time obtained from Figure 2 with the factor obtained from Table 2 and round up to the next higher tenth of a second to get an estimate of the acceleration time on the grade. For example, with a DVCD of 80 feet and a WB-50 semi-trailer design vehicle on a 4% uphill, the (interpolated) factor from Table 2 is 1.30. Therefore, the estimated time required for the design vehicle to accelerate through the DVCD will be $12.2 \times 1.30 = 15.86$ seconds, or 15.9 seconds rounded up to the next higher tenth of a second.

If you selected a design vehicle different from those listed in Figure 2 and Table 2, you may still be able to use Figure 2 and Table 2 if you can match your design vehicle to the weight, weight-to-power ratio, and power application characteristics of the design vehicles in Figure 2 and Table 2. The WB-50 curve and grade factors are based on an 80,000 lb vehicle with a weight-to-power ratio of 400 lb/hp accelerating at 85% of its maximum power on level grades and at 100% of its maximum power on uphill grades, and may therefore be representative of any heavy tractor-trailer combination with the same characteristics. The school bus curve and grade factors are based on a 27,000 lb vehicle with a weight-to-power ratio of 180 lb/hp accelerating at 70% of its maximum power on level grades and at 85% of its maximum power on uphill grades. The SU curve and grade factors are based on a 34,000 lb vehicle with a weight-to-power ratio of 200 lb/hp accelerating at 75% of its maximum power on level grades and at 90% of its maximum power on uphill grades.

Table 2. Factors to account for slower acceleration on uphill grades. Multiply the appropriate factor (depending on the design vehicle, grade, and acceleration distance) with the acceleration time in Figure 2 to obtain the estimated acceleration time on the grade.

Acceleration Distance (ft)	Design Vehicle and Percentage Uphill Grade														
	Single Unit Truck (SU)				Large School Bus (S-BUS 40)					Intermediate Tractor-Trailer (WB-50)					
	0-2%	4%	6%	8%	0-1%	2%	4%	6%	8%	0%	2%	4%	6%	8%	
25	1.00	1.06	1.13	1.19	1.00	1.01	1.10	1.19	1.28	1.00	1.09	1.27	1.42	1.55	
50	1.00	1.09	1.17	1.25	1.00	1.01	1.12	1.21	1.30	1.00	1.10	1.28	1.44	1.58	
75	1.00	1.10	1.19	1.29	1.00	1.02	1.13	1.23	1.33	1.00	1.11	1.30	1.47	1.61	
100	1.00	1.11	1.21	1.32	1.00	1.02	1.14	1.25	1.35	1.00	1.11	1.31	1.48	1.64	
125	1.00	1.12	1.23	1.34	1.00	1.03	1.15	1.26	1.37	1.00	1.12	1.32	1.50	1.66	
150	1.00	1.12	1.24	1.37	1.00	1.03	1.16	1.28	1.40	1.00	1.12	1.33	1.52	1.68	
175	1.00	1.13	1.25	1.38	1.00	1.03	1.17	1.29	1.42	1.00	1.12	1.34	1.53	1.70	
200	1.00	1.13	1.26	1.40	1.00	1.04	1.17	1.30	1.43	1.00	1.13	1.35	1.54	1.72	
225	1.00	1.14	1.27	1.42	1.00	1.04	1.18	1.32	1.45	1.00	1.13	1.35	1.56	1.74	
250	1.00	1.14	1.28	1.43	1.00	1.04	1.19	1.33	1.47	1.00	1.13	1.36	1.57	1.76	
275	1.00	1.14	1.29	1.44	1.00	1.05	1.20	1.34	1.49	1.00	1.14	1.37	1.58	1.77	
300	1.00	1.14	1.30	1.46	1.00	1.05	1.20	1.35	1.50	1.00	1.14	1.37	1.59	1.79	
325	1.00	1.15	1.30	1.47	1.00	1.05	1.21	1.36	1.52	1.00	1.14	1.38	1.60	1.81	
350	1.00	1.15	1.31	1.48	1.00	1.05	1.22	1.37	1.54	1.00	1.15	1.39	1.61	1.82	
375	1.00	1.15	1.31	1.49	1.00	1.06	1.22	1.38	1.55	1.00	1.15	1.39	1.62	1.84	
400	1.00	1.15	1.32	1.50	1.00	1.06	1.23	1.40	1.57	1.00	1.15	1.40	1.63	1.85	

For design vehicle clearance distances greater than 400 feet, use Equation 1 to estimate the time for the design vehicle to accelerate through the design vehicle clearance distance or any other distance:

$$T = e^{\left[a - b \sqrt{c + \frac{2}{b} \ln \left(\frac{d}{X} \right)} \right]} \quad (1)$$

where

- T = time to accelerate through distance X , in seconds;
- X = distance over which acceleration takes place, in feet;
- \ln = natural logarithm function;
- e = 2.71828, the base of natural logarithms; and
- a , b , c , and d = calibration parameters from Table 3.

Note: To interpolate between grades, do not interpolate the parameters in Table 3. The correct way to interpolate is to calculate the acceleration time T using Equation 1 for the two nearest grades and then interpolate between the two acceleration times.

Line 25. Queue clearance time is the total amount of time required (after the signal has turned green for the approach crossing the tracks) to begin moving a queue of vehicles through the queue start-up distance (L, Line 21) and then move the design vehicle from a stopped position at the far side of the crossing completely through the minimum track clearance distance (MTCD, Line 19). This value is the sum of the time required for design vehicle to start moving (Line 22) and the time for design vehicle to accelerate through the design vehicle clearance distance (Line 24).

Table 3. Parameters to estimate vehicle acceleration times over distances greater than 400 feet using Equation 1.

Design Vehicle	Grade	a	b	c	d
Through Passenger Car	Level	7.75	3.252	5.679	2.153
Left Turning Passenger Car	Level	10.29	5.832	3.114	5.090
Single Unit Truck (SU)	Level to 2%	8.16	3.624	5.070	2.018
	4%	10.39	4.865	4.560	1.739
	6%	9.52	4.542	4.393	1.700
	8%	9.38	4.597	4.165	1.668
Large School Bus (S-BUS 40)	Level to 1%	10.02	4.108	5.95	0.885
	2%	11.51	5.254	4.801	1.300
	4%	10.79	5.042	4.577	1.266
	6%	10.61	5.101	4.329	1.253
Intermediate Semi-Trailer (WB-50)	Level	17.75	7.984	4.940	0.481
	2%	10.26	4.028	6.500	0.249
	4%	9.39	3.635	6.670	0.193
	6%	9.38	3.732	6.310	0.188
	8%	10.31	4.515	5.219	0.265

SECTION 3: MAXIMUM PREEMPTION TIME CALCULATION

Line 26. Right-of-way transfer time, in seconds, recorded on Line 17. The right-of-way transfer time is the maximum amount of time needed for the worst case condition, prior to display of the track clearance green interval.

Line 27. Queue clearance time, in seconds, recorded on Line 25. Queue clearance time starts simultaneously with the track clearance green interval (i.e. after right-of-way transfer), and is the time required for the design vehicle stopped just inside the minimum track clearance distance to start up and move completely out of the minimum track clearance distance.

Line 28. Desired minimum separation time is a time "buffer" between the departure of the last vehicle (the design vehicle) from the railroad crossing (as defined by the minimum track clearance distance) and the arrival of the train. Separation time is added for safety reasons and to avoid driver discomfort. If no separation time is provided, a vehicle could potentially leave the crossing at exactly the same time the train arrives, which would certainly lead to severe driver discomfort and potential unsafe behavior. The recommended value of four (4) seconds is based on the minimum recommended value found in the Institute of Transportation Engineer's *ITE Journal* (in an article by Marshall and Berg in February 1997).

Line 29. Maximum preemption time is the total amount of time required after the preempt is initiated by the railroad warning equipment to complete right-of-way transfer to the track clearance green interval, initiate the track clearance phase(s), move the design vehicle out of the crossing's minimum track

clearance distance, and provide a separation time "buffer" before the train arrives at the crossing. It is the sum of the right-of-way transfer time (Line 26), the queue clearance time (Line 27), and the desired minimum separation time (Line 28).

SECTION 4: SUFFICIENT WARNING TIME CHECK

Line 30. Minimum time (seconds) is the least amount of time active warning devices shall operate prior to the arrival of a train at a highway-rail grade crossing.

Line 31. Clearance time (seconds), typically known as CT, is the additional time that may be provided by the railroad to account for longer crossing time at wide (i.e., multi-track crossings) or skewed-angle crossings. You must obtain the clearance time from the railroad responsible for the railroad crossing. In cases where the minimum track clearance distance (Line 19) exceeds 35 feet, the railroads' *AREMA Manual* requires clearance time of one second be provided for each additional 10 feet, or portions thereof, over 35 feet. Additional clearance time may also be provided to account for site-specific needs. Examples of extra clearance time include cases where additional time is provided for simultaneous preemption (where the preemption notification is sent to the signal controller unit simultaneously with the activation of the railroad crossing's active warning devices), instead of providing advance preemption time.

Line 32. Minimum warning time (seconds) is the sum of the minimum time (Line 30) and the clearance time (Line 31). This value is the actual minimum time that active warning devices can be expected to operate at the crossing prior to the arrival of the train under normal, through-train conditions. The term "through-train" refers to the case where trains do not stop or start moving while near or at the crossing. Note that the minimum warning time, does not include buffer time (BT). Buffer time is added by the railroad to ensure that the minimum warning time is always provided despite inherent variations in warning times; however, it is not consistently provided and cannot be relied upon by the traffic engineer for signal preemption and/or warning time calculations.

Line 33. Advance preemption time (seconds), if provided, is the period of time that the notification of an approaching train is forwarded to the highway traffic signal controller unit or assembly prior to activating the railroad active warning devices. Only enter advance preemption time if you can verify from the railroad that advance preemption time is already being provided for your site. If you are determining whether or not you need advance preemption time, enter zero for the advance preemption time in Line 33.

Line 34. Warning time provided by the railroad is the sum of the minimum warning time (Line 32) and the advance preemption time (Line 33), in seconds. This value should be verified with the railroad, and should not include buffer time (BT).

Line 35. Additional warning time required from railroad is the additional time needed (if any), in seconds, that is required to provide safe preemption in the worst case (the maximum preemption time on Line 29), given the warning time provided by the railroad (Line 34). The additional warning time required is calculated by subtracting the warning time provided by the railroad (Line 34) from the maximum preemption time (Line 29). If the result of the subtraction is equal to or less than zero, it means that sufficient warning time is available, and you should enter zero (0) on Line 35. However, keep in mind that highly negative (-10 or less) subtraction results may indicate the potential for operational problems due to insufficient track clearance green time. Section 5 of the worksheet contains a methodology for calculating sufficient track clearance green time.

If the additional warning time is greater than zero (0), it means that the warning time provided by the railroad is insufficient, and additional warning time has to be requested from the railroad to ensure safe operation. The railroad can provide additional warning time either by providing additional clearance time (CT) (Line 30), or by providing or increasing advance preemption time (Line 33).

As an alternative, it may be possible to reduce the maximum preemption time (Line 29). To reduce the maximum preemption time, you can reduce either the preempt delay time (Line 1), if this is possible; reduce preempt minimum green time (Line 5) or other green time (Line 6), as long as you do not violate

local policies for signal timing; or, reduce yellow change time (Line 7) or red clearance time (Line 8) as long as adequate and appropriate yellow change and red clearance intervals are provided.

If pedestrian rather than vehicular phasing controls warning time requirements for preemption, it may be possible to reduce the minimum walk time (Line 11) and/or pedestrian clearance time (Line 12) as long as you do not violate local policies for signal timing. You can also let the pedestrian clearance time (flashing don't walk) time simultaneous with vehicular yellow change and red clearance and so reduce the values on Line 13 (yellow change time) and Line 14 (red clearance time) to zero (0). If local policies do not currently allow simultaneous clearance for pedestrian and vehicular phasing, you may want to consider allowing this type of operation to reduce your worst-case conflicting pedestrian time. Once you have made all of the possible adjustments to the warning time, recompute the totals in Lines 3, 9, 15, 16, 17, 26, 29, and 35. If Line 35 remains greater than zero, then you will have to request additional warning time from the railroad, as described above, to ensure safe preemption of the adjacent signalized intersection.

SECTION 5: TRACK CLEARANCE GREEN TIME CALCULATION (OPTIONAL)

Note: This section is optional and is used to calculate the duration of the track clearance green interval. If this worksheet is only used to determine if additional warning time has to be requested from the railroad, this section need not be completed. The objective of the section is to calculate the duration of the track clearance green interval to ensure safe and efficient operations at the crossing and adjacent traffic signal.

The Preempt Trap Check section (lines 36 to 44) focuses on safety by calculating the minimum duration of the track clearance green interval to ensure that the track clearance green does not terminate before the gates block access to the crossing. If the gates do not block access to the crossing before the expiration of the track clearance green, it is possible that vehicles can continue to cross the tracks and possibly stop on the tracks. However, the track clearance green interval has already expired and there will be no further opportunity to clear. This potentially hazardous condition is called the "preempt trap".

The Clearing of Clear Storage Distance section (lines 45 to 50) focuses on efficiency by calculating duration of the track clearance green interval that is needed to clear the clear storage distance (CSD in Figure 1), or a specific portion thereof.

Preempt Trap Check

Line 36. Advance preemption time provided is the duration (in seconds) the preempt sequence is active in the highway traffic signal controller before the activation of the railroad active warning devices. If Line 35 is zero (i.e. no additional warning time is required from the railroad), the value on Line 33 can be used. In other cases, use the actual value of the advance preemption time (APT) provided by the railroad. If no APT is provided, enter zero on Line 36.

Line 37. Multiplier for maximum APT due to train handling is a value that relates the maximum duration of the advance preemption time (APT) to the minimum value guaranteed by the railroad. Although the railroad guarantees a minimum duration for the APT, it is probable that in most cases the actual duration of the APT will be longer than the guaranteed duration. This variability in APT occurs due to "train handling", which a term that describes the acceleration and deceleration of trains on their approach to the crossing. If a train accelerates or decelerates while approaching to the crossing, the railroad warning system cannot estimate the arrival time of the train at the crossing accurately, resulting in variation in the actual duration of APT provided. This variation needs to be taken into account to ensure safe operation.

To make sure that the preempt trap does not occur we need to determine the maximum value of the APT so that a sufficiently long track clearance green interval can be provided to ensure that the gates block access to the crossing before the track clearance green ends. The maximum APT can be estimated by multiplying the advance preemption time provided (and guaranteed) by the railroad (Line 36) with the multiplier for maximum APT due to train handling. This value is only significant if the value for APT on Line 36 is non-zero. If APT is zero, continue to line 38.

In the case where APT is provided, the difference between the minimum and maximum values of APT is termed excess APT. Excess APT usually occurs when the train decelerates on the approach to the crossing, or where train handling affects the accuracy of the estimated time of train arrival at the crossing so that the preempt sequence is activated earlier than expected. The amount of excess APT is increased by the following conditions:

- Increased variation in train speeds, since more trains will be speeding up and slowing down;
- Lower train speeds, since a fixed deceleration rate has a greater effect on travel time at low speeds than at higher speeds; and
- Longer warning times, because more time is available for the train to decelerate on the approach to the crossing.

The multiplier for maximum APT can be determined from field measurements as the largest advance preemption time observed (or the 95th percentile, if enough observations are available) divided by the value on Line 36. If no field observations are available, the multiplier for maximum APT can be estimated as 1.60 if warning time variability is high or 1.25 if warning time variability is low. High warning time variability can typically be expected in the vicinity of switching yards, branch lines, or anywhere low-speed switching maneuvers takes place. According to Section 16.30.10 of the *AREMA Signal Manual* the railroad can provide a "timer for constant time between APT and CWT." The effect of such a "not to exceed" timer is to eliminate excess APT, and if provided, the multiplier on Line 37 can be set to 1.0.

Line 38. Maximum APT is largest value (in seconds) of the advance preemption time that can typically be expected, which corresponds to the earliest possible time the preemption sequence in the traffic signal controller will be activated before the activation of the railroad grade crossing warning system (flashing lights and gates). It is calculated by multiplying the APT provided by the railroad (Line 36) with the multiplier for maximum APT due to train handling (Line 37).

Line 39. Minimum duration for the track clearance green is the minimum duration (in seconds) of the track clearance green interval to ensure that the gates block access to the crossing before the track clearance green expires in the case where no advance preemption time is provided. It is necessary to block access to the crossing before the track clearance green expires to ensure that vehicles do not enter the crossing after the expiration of the track clearance green and so be subject to the preempt trap (described in the introduction to Section 5). The 15 seconds minimum duration for the track clearance green interval is calculated from federal regulations and requirements.

Line 40. Gates down after start of preemption is the maximum duration (in seconds) from when the preempt is activated in the highway traffic signal controller until the gates reach a horizontal position. Calculate this value by adding the maximum advance preemption time on Line 38 to the minimum duration for the track clearance green interval on Line 39.

Line 41. Preempt verification and response time, recorded on Line 3, is the number of seconds between the receipt at the controller unit of a preempt call issued by the railroad's grade crossing warning equipment and the time the controller software actually begins to respond to the preempt call.

Line 42. Best-case conflicting vehicle or pedestrian time (in seconds) is the minimum time from when the preempt starts to time in the controller (i.e. after verification and response) until the track clearance green interval can start timing. In most cases, this value is zero, since the controller may already be in the track clearance phase(s) when the preempt starts timing, and therefore the track clearance green interval can start timing immediately. The best-case conflicting vehicle or pedestrian time may be greater than zero if the track clearance green interval contains phases that are not in normal operation (and conflicts with the normal phases), or where another phase or interval always has to terminate before the track clearance green interval can start timing.

Line 43. Minimum right-of-way transfer time is the minimum amount of time needed for the best case condition, prior to display of the track clearance green interval. Calculate the minimum right-of-way transfer time by adding lines 41 and 42.

Line 44. Calculate the **Minimum track clearance green time** by subtracting Line 43 from Line 40. This yields the minimum time that the track clearance green interval has to be active to avoid the preempt trap.

Clearing of Clear Storage Distance




Figure 3 Relocation distances during the track clearance green interval.

Line 45. Time required for design vehicle to start moving, recorded on Line 22, is the number of seconds that elapses between the start of the track clearance green interval and the time the design vehicle, which is located at the edge of the railroad crossing on the opposite side from the signalized intersection, begins to move.

Line 46. Design vehicle clearance distance (DVCD in Figure 3) is the length, in feet, which the design vehicle must travel in order to enter and completely pass through the railroad crossing's minimum track clearance distance (MTCD). This is the same value as recorded on Line 23.

Line 47. Portion of CSD to clear during track clearance, (CSD* in Figure 3) is the portion of the clear storage distance (CSD), in feet, that must be cleared of vehicles before the track clearance green interval ends. For intersections with a CSD greater than approximately 150 feet it is desirable—but not necessary—to clear the full CSD during the track clearance green interval. In other words, it is desirable to set Line 47 to the full value of CSD (Line 18). If the full CSD is not cleared, however, vehicles will be stopped in the CSD during the preempt dwell period, and if not serviced during the preempt dwell period, will be subject to unnecessary delays which may result in unsafe behavior. For CSD values less than 150 feet the full CSD is typically cleared to avoid the driver task of crossing the tracks followed immediately by the decision to stop or go when presented by a yellow signal as the track clearance green interval terminates.

Line 48. Design vehicle relocation distance (DVRD in Figure 3) is the distance, in feet, that the design vehicle must accelerate through during the track clearance green interval. It is the sum of the design vehicle clearance distance (Line 46) and the portion of CSD to clear during the track clearance green interval (Line 47).

Line 49. The Time required for design vehicle to accelerate through DVRD is the amount of time required for the design vehicle to accelerate from a stop and travel the complete design vehicle relocation distance (DVRD). This time value, in seconds, can be found by locating your design vehicle relocation distance from Line 48 on the horizontal axis of Figure 2 and then drawing a line straight up until that line intersects the acceleration time performance curve for your design vehicle. For a WB-50 semi-trailer, large school bus (S -BUS 40), or single unit (SU) vehicle, multiply the acceleration time with a correction factor obtained from Table 2 to estimate the effect of grade on the acceleration of the vehicle. Use the average grade over the design vehicle relocation distance. For design vehicle relocation distances greater than 400 feet, use Equation 1 with the appropriate parameters listed in Table 3.

Line 50. Time to clear portion of clear storage distance, in seconds, is the total amount of time

required (after the signal has turned green for the approach crossing the tracks) to begin moving a queue of vehicles through the queue start-up distance (L in Figure 3) and then move the design vehicle from a stopped position at the far side of the crossing completely through the portion of clear storage distance that must be cleared (CSD* in Figure 3). This value is the sum of the time required for design vehicle to start moving (Line 45) and the time for the design vehicle to accelerate through the design vehicle relocation distance, DVRD (Line 49).

Line 51. The Track clearance green interval is the time required, in seconds, for the track clearance green interval to avoid the occurrence of the preempt trap and to provide enough time for the design vehicle to clear the portion of the clear storage distance specified on Line 47. The track clearance green interval time is the maximum of the minimum track clearance green time (Line 44) and the time required to clear a portion of clear storage distance (Line 50).

SECTION 6: VEHICLE-GATE INTERACTION CHECK (OPTIONAL)

Note: This section is optional and is used to calculate the required advance preemption time to avoid the automatic gates descending on a stationary or slow moving design vehicle as it moves through the minimum track clearance distance (MT CD). If this worksheet is only used to determine if additional warning time has to be requested from the railroad to ensure that vehicles have enough time to clear the crossing before the arrival of the train, this section need not be completed.

Line 52. Right-of-way transfer time, in seconds, recorded on Line 17, is the maximum amount of time needed for the worst case condition, prior to display of the track clearance green interval.

Line 53. Time required for design vehicle to start moving, recorded on Line 22, is the time (in seconds) elapsed between the start of the track clearance green interval and the time the design vehicle, which is located at the edge of the railroad crossing on the opposite side from the signalized intersection, begins to move.

Line 54. Time required for design vehicle to accelerate through the design vehicle length, DVL, is the time required for the design vehicle to accelerate through its own length. The design vehicle length is recorded on Line 20. This time value, in seconds, can be read from Figure 2 and Table 2 or looked up in Table 4 for standard design vehicles. For a WB-50 semi-trailer, large school bus, or single unit (SU) truck use the average grade over the design vehicle length at the far side of the crossing.

Line 55. Time required for design vehicle to clear the descending gates, in seconds, is the sum of the right-of-way transfer time on Line 52, the time required for design vehicle to start moving on Line 53, and the time required for design vehicle to accelerate through the design vehicle length on Line 54.

Line 56. Duration of flashing lights before gate descent start, in seconds, is the time the railroad warning lights flash before the gates start to descend. This value typically ranges from 3 to 5 seconds and must be obtained from the railroad. The value obtained from the railroad may be verified using field observation.

Table 4. Time required for the design vehicle to accelerate through the design vehicle length.

Design Vehicle	Design Vehicle Length (feet)	Grade	Acceleration Time (seconds)
Through Passenger Car	19	Level	2.6
Left Turning Passenger Car	19	Level	2.7
Single Unit Truck (SU)	30	Level to 2%	3.8
		4%	4.0
		6%	4.3
		8%	4.6
Large School Bus (S-BUS 40)	40	Level to 1%	5.5
		2%	5.5
		4%	6.1
		6%	6.6
Intermediate Semi-Trailer (WB-50)	55	Level	10.0
		2%	11.0
		4%	12.8
		6%	14.4
		8%	15.8

Line 55. Time required for design vehicle to clear the descending gates, in seconds, is the sum of the right -of-way transfer time on Line 52, the time required for design vehicle to start moving on Line 53, and the time required for design vehicle to accelerate through the design vehicle length on Line 54.

Line 56. Duration of flashing lights before gate descent start, in seconds, is the time the railroad warning lights flash before the gates start to descend. This value typically ranges from 3 to 5 seconds and must be obtained from the railroad. The value obtained from the railroad may be verified using field observation.

Line 57. Full gate descent time, in seconds, is the time it takes for the gates to descend to a horizontal position after they start their descent. This value must be obtained from the railroad and may be verified using field observation. In the case where multiple gates descend at different speeds, use the descent time of the gate that reaches the horizontal position first.

Line 58. The Proportion of non-interaction gate descent time is the decimal proportion of the full gate descent time on Line 57 during which the gate will not interact with (i.e. not hit) the design vehicle if it is located under the gate. This value depends on the design vehicle height, h , and the distance from the center of the gate mechanism to the nearest side of the design vehicle, d , as shown in Figure 4. Figure 5 can be used to determine the proportion of non-interaction gate descent time. Select the distance from the center of the gate mechanism to the nearest side of the design vehicle, d , on the vertical axis of Figure 5, draw a horizontal line until you reach the curve that represents the design vehicle, and then draw a vertical line down to the horizontal axis and read off the value of the proportion of non-interaction gate descent time.

Line 59. Non-interaction gate descent time is time (in seconds) during gate descent that the gate will not interact with (i.e. not hit) the design vehicle if it is located under the gate. In other words, it is the time that expires after the gate starts to descend until it hits the design vehicle if it is located under the gate. This value is calculated by multiplying the full gate descent time on Line 57 with the proportion of non-interaction gate descent time on Line 58.




Figure 4 Gate interaction with the design vehicle.




Figure 5 Proportion of gate descent time available as a function of the design vehicle height and the distance from the center of the gate mechanism to the nearest side of the design vehicle.

Line 60. Time available for design vehicle to clear descending gate, in seconds, is the time, after the railroad warning lights start to flash, that is available for the design vehicle to clear the descending gate before the gate hits the vehicle. It is the sum of the duration of the flashing lights before gate descent start (Line 56) and the non-interaction gate descent time (Line 59).

Line 61. Advance preemption time required to avoid design vehicle-gate interaction, in seconds, is calculated by subtracting the time available for the design vehicle to clear descending gate (Line 60) from the time required for the design vehicle to clear descending gate (Line 55). The result is the amount of advance preemption time that is required to avoid the gates descending on a stationary or slow-moving design vehicle. If the result of the subtraction is equal to or less than zero, it means that sufficient time is available, and you should enter zero (0) on Line 61. If the result is greater than the amount of advance preemption time provided by the railroad, as given on Line 36, there is a possibility that the gates could descend on a stationary or slow-moving design vehicle. To avoid this situation, additional advance preemption time should be requested from the railroad.

It should be kept in mind that on its own, gates descending on a vehicle is not a critical safety failure, because enough time still exists to clear the crossing before the arrival of the train, if the advance preemption time on Line 36 is provided. Therefore, local policies may vary on whether additional advance preemption time (over and above that on Line 36) should be requested solely for the purpose of prohibiting gates descending on vehicles.

If additional advance preemption time is provided to avoid design vehicle-gate interaction, Line 33 of this Worksheet has to be updated, and Lines 34 and 35 recomputed. Section 5 also needs to be recomputed to calculate the track clearance green time.

NO.	REVISION
1	FOR CITY OF RENTON REVIEW
2	REVISED FOR PHASING PLAN

DATE	BY	CHKD	APPD
11/19/02

CITY OF RENTON
 Planning/Building/Police/Finance/Development
 400 1st Avenue, Renton, WA 98057

COVER SHEET
LAKE WASH. BLVD. IMPROVEMENTS
SOUTHPORT DEVELOPMENT

DEVELOPER:
 SECO DEVELOPMENT, INC.
 10843 NE 5TH STREET, SUITE 200
 BELLEVUE, WA 98004
 CONTACT: RICK ALLEN
 PHONE: 425-888-3065


TRANSPORTATION ENGINEER:
 THE TRANSPRO GROUP, INC.
 11720 118TH AVENUE NE, SUITE 500
 KIRKLAND, WA 98034
 CONTACT: CHRIS JOCKET, PE
 PHONE: 425-821-3685

1. EXISTING UTILITIES AND UNDERGROUND STRUCTURES SHOWN ON THE PLAN ARE BASED UPON THE RECORD DRAWINGS AND FIELD SURVEY DATA. CITY RECORD DRAWING NO. 2118 - 3 1/2" SCALE (SEE STAFFED CITY OF RENTON RECORD DRAWING NO. 2118 - 3 1/2" SCALE) SHOWS THE LOCATION OF POWER TOWER, TOWER LOCATED NORTH OF THE ENTRANCE ROAD TO PROJECT. POWER TRANSMISSION TOWER SHALL BE SHOWN ON SHEET C1. ELEVATION = 2409 FEET (GNSS 1988).
2. EXISTING UTILITIES AND UNDERGROUND STRUCTURES SHOWN ON THE PLAN ARE BASED UPON THE RECORD DRAWINGS AND FIELD SURVEY DATA. CITY RECORD DRAWING NO. 2118 - 3 1/2" SCALE (SEE STAFFED CITY OF RENTON RECORD DRAWING NO. 2118 - 3 1/2" SCALE) SHOWS THE LOCATION OF POWER TOWER, TOWER LOCATED NORTH OF THE ENTRANCE ROAD TO PROJECT. POWER TRANSMISSION TOWER SHALL BE SHOWN ON SHEET C1. ELEVATION = 2409 FEET (GNSS 1988).
3. THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF RENTON AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (SDOT) PRIOR TO THE START OF CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF RENTON AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (SDOT) PRIOR TO THE START OF CONSTRUCTION.
4. THE CONTRACTOR SHALL MAINTAIN ACCESS TO ALL EXISTING UTILITIES AND UNDERGROUND STRUCTURES AT ALL TIMES AND SHALL BE RESPONSIBLE FOR PROTECTING ALL UTILITIES AND UNDERGROUND STRUCTURES FROM DAMAGE DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF RENTON AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (SDOT) PRIOR TO THE START OF CONSTRUCTION.
5. THE CONTRACTOR SHALL MAINTAIN ACCESS TO ALL EXISTING UTILITIES AND UNDERGROUND STRUCTURES AT ALL TIMES AND SHALL BE RESPONSIBLE FOR PROTECTING ALL UTILITIES AND UNDERGROUND STRUCTURES FROM DAMAGE DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF RENTON AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (SDOT) PRIOR TO THE START OF CONSTRUCTION.
6. THE CONTRACTOR SHALL MAINTAIN ACCESS TO ALL EXISTING UTILITIES AND UNDERGROUND STRUCTURES AT ALL TIMES AND SHALL BE RESPONSIBLE FOR PROTECTING ALL UTILITIES AND UNDERGROUND STRUCTURES FROM DAMAGE DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF RENTON AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (SDOT) PRIOR TO THE START OF CONSTRUCTION.
7. THE CONTRACTOR SHALL MAINTAIN ACCESS TO ALL EXISTING UTILITIES AND UNDERGROUND STRUCTURES AT ALL TIMES AND SHALL BE RESPONSIBLE FOR PROTECTING ALL UTILITIES AND UNDERGROUND STRUCTURES FROM DAMAGE DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE CITY OF RENTON AND THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (SDOT) PRIOR TO THE START OF CONSTRUCTION.


LEGEND

PROPOSED DISTING

CONCRETE PAVEMENT
 SPOT ELEVATION
 CONTOUR
 INDEX LINE
 SANITARY SEWER
 WATER PIPE
 STORM PIPE
 STORM CATCHER
 STORM MANHOLE
 REPAIR
 CONC. RETAIN. WALL
 FINISH GRADE AT BOTTOM OF HALL
 FINISH GRADE AT TOP OF WALL
 ROOFTOP
 WATER VALVE
 FIRE HYDRANT
 WATER METER
 UTILITY POLE
 UTILITY BOX
 STREET MANHOLE
 TRAFFIC SIGN
 FILTER FABRIC FENCE
 ROCK CHECK DAM
 STRAW BALES
 BARBED WIRE FENCE
 CHAIN LINK FENCE



PERMIT PLAN MARKUPS INCLUDED WITHIN THE ACCOMPANYING CIVIL PLANS WERE PREPARED BY GUYHILL IN PORTER LUNDEEN IN COORDINATION WITH TENW (TRAFFIC CONSULTANT), SECO DEVELOPMENT, INC. (OWNER), AND THE CITY OF RENTON FOR SITE WORK TO BE CONSTRUCTED IN PHASE 1.



THESE PLANS ARE REPLACED BY TENW SHEETS 1-4 DATED SEPTEMBER 2012

T-349301

DRAMAING INDEX:

COVER SHEET (CONC.)	SHT C1
PLAN & PROFILE STA 8+98 TO STA 14+60	SHT C2
PLAN & PROFILE STA 14+60 TO STA 20+00	SHT C3
PLAN & PROFILE STA 20+00 TO STA 23+00	SHT C4
PLAN & PROFILE COLLON PARK ENTRANCE	SHT C5
ROAD GEOMETRY STA 8+98 TO STA 14+60	SHT C6
ROAD GEOMETRY STA 14+60 TO STA 20+00	SHT C7
ROAD GEOMETRY STA 20+00 TO STA 23+00	SHT C8
ROAD GEOMETRY STA COLLON PARK ENTRANCE	SHT C9
EROSION CONTROL STA 8+98 TO STA 14+60	SHT C10
EROSION CONTROL STA 14+60 TO STA 20+00	SHT C11
EROSION CONTROL STA 20+00 TO STA 23+00	SHT C12
EROSION CONTROL COLLON PARK ENTRANCE	SHT C13
UTILITY COORDINATION PLAN	SHT C14
NOT USED	SHT C15
DRIVEWAY ACCESS EASEMENT	SHT C16
ROAD SECTIONS	SHT C17
ROAD SECTIONS	SHT C18
DETAILS	SHT C19
DETAILS	SHT C20
NOTES & SPECIFICATIONS	SHT C21
LAKE WASH BLVD/PARK AVE H CHANNLEIZATION PLAN	SHT C01
LAKE WASH BLVD STA 13+25 TO 16+85 CHANNLEIZATION PLAN	SHT C02
LAKE WASH BLVD/SITE ACCESS CHANNLEIZATION PLAN	SHT C03
LAKE WASH BLVD/PARK AVE H TRAFFIC SIGNAL PLAN	SHT T01
LAKE WASH BLVD STA 13+00 TO 16+00 TRAFFIC SIGNAL PLAN	SHT T02
LAKE WASH BLVD/SITE ACCESS TRAFFIC SIGNAL PLAN	SHT T03
LAKE WASH BLVD/SITE ACCESS SIGNAL WIRING DIAGRAM	SHT T04
LAKE WASH BLVD/SITE ACCESS SIGNAL STANDARD DETAILS	SHT T05

93923.02
 SEAL
 ORDERED FOR COMPLIANCE WITH THE CITY STANDARDS

RENTON
 CITY OF RENTON
 VIGNY MAP
 NOT TO SCALE

LAYERSET 001-V2
 PLOT# 11/18/02 12:13

NO.	REVISION	BY	DATE	APP'D.
1	FOR CITY OF SOUTHPORT REVIEW	LDJ/SL	11/18/02	
2	FOR CITY OF SOUTHPORT REVIEW	LDJ/SL	11/18/02	


1	DATE	BY	APP'D.	NO.
1	11/18/02	LDJ/SL		1
2	11/18/02	LDJ/SL		2

CITY OF RENTON
 Planning/Building/Public Works Dept.
 Project Management P.E. Administrator

Scale: 1"=50'

PLAN & PROFILE STA 8+00 TO STA 14+00
LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT

1. MATCH EXISTING PLAN
2. MATCH EXISTING PROFILE
3. MATCH EXISTING ELEVATIONS
4. MATCH EXISTING CURBS AND GUTTERS
5. MATCH EXISTING SIDEWALKS
6. MATCH EXISTING DRIVEWAYS
7. MATCH EXISTING UTILITIES
8. MATCH EXISTING TRENCHES
9. MATCH EXISTING WALLS
10. MATCH EXISTING FENCES
11. MATCH EXISTING LIGHTS
12. MATCH EXISTING SIGNAGE
13. MATCH EXISTING LANDSCAPE
14. MATCH EXISTING TREES
15. MATCH EXISTING BUILDINGS
16. MATCH EXISTING PAVEMENT
17. MATCH EXISTING GRADES
18. MATCH EXISTING SLOPES
19. MATCH EXISTING EROSION CONTROL
20. MATCH EXISTING DRAINAGE
21. MATCH EXISTING UTILITIES
22. MATCH EXISTING TRENCHES
23. MATCH EXISTING WALLS
24. MATCH EXISTING FENCES
25. MATCH EXISTING LIGHTS
26. MATCH EXISTING SIGNAGE
27. MATCH EXISTING LANDSCAPE
28. MATCH EXISTING TREES
29. MATCH EXISTING BUILDINGS
30. MATCH EXISTING PAVEMENT
31. MATCH EXISTING GRADES
32. MATCH EXISTING SLOPES
33. MATCH EXISTING EROSION CONTROL
34. MATCH EXISTING DRAINAGE
35. MATCH EXISTING UTILITIES
36. MATCH EXISTING TRENCHES
37. MATCH EXISTING WALLS
38. MATCH EXISTING FENCES
39. MATCH EXISTING LIGHTS
40. MATCH EXISTING SIGNAGE
41. MATCH EXISTING LANDSCAPE
42. MATCH EXISTING TREES
43. MATCH EXISTING BUILDINGS
44. MATCH EXISTING PAVEMENT
45. MATCH EXISTING GRADES
46. MATCH EXISTING SLOPES
47. MATCH EXISTING EROSION CONTROL
48. MATCH EXISTING DRAINAGE
49. MATCH EXISTING UTILITIES
50. MATCH EXISTING TRENCHES
51. MATCH EXISTING WALLS
52. MATCH EXISTING FENCES
53. MATCH EXISTING LIGHTS
54. MATCH EXISTING SIGNAGE
55. MATCH EXISTING LANDSCAPE
56. MATCH EXISTING TREES
57. MATCH EXISTING BUILDINGS
58. MATCH EXISTING PAVEMENT
59. MATCH EXISTING GRADES
60. MATCH EXISTING SLOPES
61. MATCH EXISTING EROSION CONTROL
62. MATCH EXISTING DRAINAGE
63. MATCH EXISTING UTILITIES
64. MATCH EXISTING TRENCHES
65. MATCH EXISTING WALLS
66. MATCH EXISTING FENCES
67. MATCH EXISTING LIGHTS
68. MATCH EXISTING SIGNAGE
69. MATCH EXISTING LANDSCAPE
70. MATCH EXISTING TREES
71. MATCH EXISTING BUILDINGS
72. MATCH EXISTING PAVEMENT
73. MATCH EXISTING GRADES
74. MATCH EXISTING SLOPES
75. MATCH EXISTING EROSION CONTROL
76. MATCH EXISTING DRAINAGE
77. MATCH EXISTING UTILITIES
78. MATCH EXISTING TRENCHES
79. MATCH EXISTING WALLS
80. MATCH EXISTING FENCES
81. MATCH EXISTING LIGHTS
82. MATCH EXISTING SIGNAGE
83. MATCH EXISTING LANDSCAPE
84. MATCH EXISTING TREES
85. MATCH EXISTING BUILDINGS
86. MATCH EXISTING PAVEMENT
87. MATCH EXISTING GRADES
88. MATCH EXISTING SLOPES
89. MATCH EXISTING EROSION CONTROL
90. MATCH EXISTING DRAINAGE
91. MATCH EXISTING UTILITIES
92. MATCH EXISTING TRENCHES
93. MATCH EXISTING WALLS
94. MATCH EXISTING FENCES
95. MATCH EXISTING LIGHTS
96. MATCH EXISTING SIGNAGE
97. MATCH EXISTING LANDSCAPE
98. MATCH EXISTING TREES
99. MATCH EXISTING BUILDINGS
100. MATCH EXISTING PAVEMENT



DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

PROF. T-349302

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL

DATE: 11/18/02
 DRAWN: LDJ/SL
 CHECKED: LDJ/SL
 APPROVED: LDJ/SL



DATE	14-19-02
DRAWN BY	...
CHECKED BY	...
SCALE	AS SHOWN

- CONSTRUCTION NOTES:**
1. CONCRETE CURB AND GUTTER
 2. SAND/GRIT LANE (SEE ROAD SECTIONS SHIT C17)
 3. SAND/GRIT LANE (SEE ROAD SECTIONS SHIT C-25)
 4. EX. UTILITY POLE/GUY WIRE TO BE RELOCATED BY OTHERS (REFER TO UTILITY COORDINATION PLAN)
 5. EX. UTILITY POLE/GUY WIRE TO BE RELOCATED BY OTHERS (REFER TO SHEET 153)
 6. NOT USED

7. CONCRETE CURB AND GUTTER
8. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
9. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
10. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
11. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
12. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
13. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
14. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
15. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
16. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
17. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
18. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
19. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
20. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
21. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
22. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
23. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
24. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
25. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
26. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
27. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
28. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
29. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
30. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
31. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
32. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
33. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
34. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
35. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
36. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
37. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
38. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
39. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
40. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
41. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
42. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
43. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
44. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
45. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
46. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
47. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
48. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
49. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
50. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
51. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
52. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
53. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
54. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
55. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
56. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
57. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
58. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
59. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
60. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
61. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
62. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
63. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
64. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
65. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
66. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
67. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
68. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
69. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
70. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
71. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
72. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
73. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
74. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
75. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
76. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
77. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
78. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
79. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
80. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
81. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
82. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
83. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
84. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
85. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
86. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
87. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
88. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
89. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
90. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
91. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
92. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
93. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
94. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
95. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
96. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
97. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
98. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
99. CONCRETE SHOULD BE PER D.O. ON SHIT C-18
100. CONCRETE SHOULD BE PER D.O. ON SHIT C-18

1. EX. R.I. SIGNAL TO BE REMOVED BY OTHERS (SEE SHEET 153)
2. NEW MATERIAL BY ON-SITE DEVELOPER
3. DESIGN BY ON-SITE DEVELOPER (BY OTHERS)
4. CONCRETE RAMP PER DETAIL ON SHIT C-18
5. REMOVE EXISTING MATERIALS BY OTHERS (SEE SHEET 153)

6. ST LIGHT EQUIPMENT (PER CITY OF RENTON STANDARD)
7. ASPHALT FINISH TO BE PER CITY OF RENTON STANDARD
8. NEW CURB ALUMINUM FINISH TO BE PER CITY OF RENTON STANDARD
9. R.I. COMPONENT TO BE INSTALLED BY OTHERS (SEE SHEET 153)
10. EXIST STREET LIGHT TO BE REMOVED BY OTHERS (SEE SHEET 153)


11. E-23.84 (EX. 153)
12. E-23.87 (EX. 153)
13. E-23.84 (EX. 153)
14. E-23.84 (EX. 153)
15. E-23.84 (EX. 153)
16. E-23.84 (EX. 153)
17. E-23.84 (EX. 153)
18. E-23.84 (EX. 153)
19. E-23.84 (EX. 153)
20. E-23.84 (EX. 153)
21. E-23.84 (EX. 153)
22. E-23.84 (EX. 153)
23. E-23.84 (EX. 153)
24. E-23.84 (EX. 153)
25. E-23.84 (EX. 153)
26. E-23.84 (EX. 153)
27. E-23.84 (EX. 153)
28. E-23.84 (EX. 153)
29. E-23.84 (EX. 153)
30. E-23.84 (EX. 153)
31. E-23.84 (EX. 153)
32. E-23.84 (EX. 153)
33. E-23.84 (EX. 153)
34. E-23.84 (EX. 153)
35. E-23.84 (EX. 153)
36. E-23.84 (EX. 153)
37. E-23.84 (EX. 153)
38. E-23.84 (EX. 153)
39. E-23.84 (EX. 153)
40. E-23.84 (EX. 153)
41. E-23.84 (EX. 153)
42. E-23.84 (EX. 153)
43. E-23.84 (EX. 153)
44. E-23.84 (EX. 153)
45. E-23.84 (EX. 153)
46. E-23.84 (EX. 153)
47. E-23.84 (EX. 153)
48. E-23.84 (EX. 153)
49. E-23.84 (EX. 153)
50. E-23.84 (EX. 153)
51. E-23.84 (EX. 153)
52. E-23.84 (EX. 153)
53. E-23.84 (EX. 153)
54. E-23.84 (EX. 153)
55. E-23.84 (EX. 153)
56. E-23.84 (EX. 153)
57. E-23.84 (EX. 153)
58. E-23.84 (EX. 153)
59. E-23.84 (EX. 153)
60. E-23.84 (EX. 153)
61. E-23.84 (EX. 153)
62. E-23.84 (EX. 153)
63. E-23.84 (EX. 153)
64. E-23.84 (EX. 153)
65. E-23.84 (EX. 153)
66. E-23.84 (EX. 153)
67. E-23.84 (EX. 153)
68. E-23.84 (EX. 153)
69. E-23.84 (EX. 153)
70. E-23.84 (EX. 153)
71. E-23.84 (EX. 153)
72. E-23.84 (EX. 153)
73. E-23.84 (EX. 153)
74. E-23.84 (EX. 153)
75. E-23.84 (EX. 153)
76. E-23.84 (EX. 153)
77. E-23.84 (EX. 153)
78. E-23.84 (EX. 153)
79. E-23.84 (EX. 153)
80. E-23.84 (EX. 153)
81. E-23.84 (EX. 153)
82. E-23.84 (EX. 153)
83. E-23.84 (EX. 153)
84. E-23.84 (EX. 153)
85. E-23.84 (EX. 153)
86. E-23.84 (EX. 153)
87. E-23.84 (EX. 153)
88. E-23.84 (EX. 153)
89. E-23.84 (EX. 153)
90. E-23.84 (EX. 153)
91. E-23.84 (EX. 153)
92. E-23.84 (EX. 153)
93. E-23.84 (EX. 153)
94. E-23.84 (EX. 153)
95. E-23.84 (EX. 153)
96. E-23.84 (EX. 153)
97. E-23.84 (EX. 153)
98. E-23.84 (EX. 153)
99. E-23.84 (EX. 153)
100. E-23.84 (EX. 153)

- PROFILE**
- DATE: 14-19-02
- 99.23.02
- DESIGNED BY: ...
- CHECKED BY: ...

DESIGNED BY: ...



CHECKED FOR COMPLIANCE TO CITY STANDARDS: ...

DATE: ...



T-349303



LAYER: 1001-14 Revised: 11/17/05 13-11		Scale: 1"=20' H 1"=4' V				 CITY OF RENTON Planning/Building/Public Works Dept. Gary Zimmerman, P.E., Administrator		PLAN & PROFILE STA 20+00 TO STA 23+00 LAKE WASH. BLVD. IMPROVEMENTS SOUTHPORT DEVELOPMENT		SHEET NO. 01 TOTAL SHEETS 02	
NO.	REVISION	DATE	BY	CHKD.	APP'D.						
1	FOR CITY OF RENTON REVIEW	11/17/05									
2	FOR OFF OF NORTH AVENUE										



PROFILE
Scale: 1"=4' V

SEC 8, TWP 23N, RGE 5E, W1M.

T-349304

BUSH, REED & MITCHELL, INC.
 ONE ONE ONE 1ST AVE
 SEASIDE, WA 98148
 206.875.1234
 98323.02

CHECKED FOR COMPLIANCE
 TO CITY STANDARDS
 Date: 11/17/05
 By: [Signature]

CLUT 3/1/2004



LAYSECT-002-VS
 Plotter: 11/18/02 13:13

NO.	REVISION	BY	DATE	APP'D.
1	PER CITY OF RENTON REVIEW		1/17/01	
2	PER CITY OF RENTON REVIEW		4/23/01	
3	REVISION			

1"=200' 1"=50'

CITY OF RENTON
 Planning/Building/Public Works Dept.
 Gregg Zimmerman, P.E., Administrator


**PLAN & PROFILE COULON PARK ENTRANCE
 LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT**



CITY REGULATOR NOTICE
 IN THE S.E. COR. OF CONC. BASE OF TRANSMISSION TOWER
 ELEVATION = 24.00 (NAVD 1985)

SEE EXHIBIT PLANS SHEETS C-1011 (A)
 FOR UTILITY (ELEVATIONS) OF SANITARY LINE

NIC = NOT IN CONTRACT



T-349305

CONSTRUCTION NOTES:

- 1 CONCRETE CURB AND CUTTER
- 2 SANICUT LANE
- 3 SIDEWALK (24" V. MAX.)
- 4 NOT USED
- 5 NOT USED
- 6 NOT USED
- 7 CONCRETE SIDEWALK PER DTL ON SHT. C18
- 8 CONCRETE CURB RAMP PER DTL ON SHT. C18
- 9 SIGNAL POLE (REFER TO SHEET T33)
- 10 BRIDGE-GRASSHOPPER-FOR-THE-SIDEWALK-RAMP- NIC
- 11 NOT USED
- 12 CONCRETE R.A. (CONSTRUCTION BY OTHERS)
- 13 REMOVE EX. CONC. CURB AND/OR SIDEWALK
- 14 EX. INTERMEDIATE-SIGNAL-CONCRETE-TO BE REMOVED/REMOVED BY OTHERS (REFER TO SHEET T33)
- 15 REMOVE EXISTING PAVEMENT
- 16 PROVIDE 4" CONC. WALL WITH 2" REBAR PER DETAIL SHT C17
- 17 PROVIDE 4" CONC. CURB WITH 2" REBAR PER DETAIL SHT C17
- 18 EX. R.A. SHALL TO BE REMOVED BY OTHERS (REFER TO SHEET T33)
- 19 NEW VARIATION BY ON-SITE DEVELOPMENT (DESIGN BY ON-SITE CIVIL ENGINEER)
- 20 NOT USED
- 21 CONCRETE RAMP PER DETAIL SHT C18
- 22 R.A. EQUIPMENT TO BE INSTALLED BY OTHERS (REFER TO SHEET T33)

99323.02

SEAL

DESIGNED BY: [Signature]

CHECKED FOR COMPLIANCE TO CITY STANDARDS

DATE: [Date]

BY: [Signature]


LAYERSET: 003-10
 Plotted: 11/15/02 13:00

NO.	REVISION	BY	DATE	APPR
1	FOR CITY OF RENTON REVIEW			
2	FOR CITY OF RENTON REVIEW			

CITY OF RENTON
 Planning/Building/Public Works Dept.
 Group Administration P.E. Administrator

ROAD GEOMETRY STA 9+96 TO STA 14+80
LAKE WASH. BLVD. IMPROVEMENTS
SOUTHPORT DEVELOPMENT

DATE	03-01-00
SCALE	
PROJECT	
NO.	



SEC 8, TWP 23N, RGE SE, W.M.

BUSH, ROED & MITCHELLS, INC.
 CIVIL ENGINEERS & LAND SURVEYORS
 93323.02

Professional Engineer Seal
 Professional Surveyor Seal

CHECKED FOR COMPLIANCE TO CITY STANDARDS
 Date: _____
 Name: _____
 Title: _____

T-349306

LAYOUT: GED-VI
 Plotfile: 11/19/02 16.14


NO	REVISION	BY	DATE	APPR
1	FOR CITY OF RENTON REVIEW		11/17/02	
2	FOR CITY OF RENTON REVIEW		12/23/02	

DATE	BY	DESCRIPTION
11/17/02		FOR CITY OF RENTON REVIEW
12/23/02		FOR CITY OF RENTON REVIEW

CITY OF RENTON
 Planning/Building/Public Works Dept.
 Greg Zimmerman, P.E., Administrator

**ROAD GEOMETRY STA 14+50 TO STA 20+00
 LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT**

DATE	03-01-00
PROJECT	
NO.	
DATE	
NO.	07




SEAL
99323.02
BUSSA, GREGG & WITCHAMERS, INC.
 CIVIL ENGINEERS & LAND SURVEYORS
 1500 1st Avenue, Suite 200
 Renton, WA 98057
 Phone: (206) 881-1111
 Fax: (206) 881-1112
 Email: gregg@bussaw.com

**CHICKEN FOR COMPLIANCE
 TO CITY STANDARDS**

SEC 8, TWP 23N, RGE SE, W.M.

LAYERSET 000-14 Revised: 11/16/02 12:04		DATE: 11/16/02		DRAWN BY: [Blank]		CHECKED BY: [Blank]		CITY OF RENTON Public Works Dept. Engineering		ROAD GEOMETRY STA 20+00 - STA 23+00 LAKE WASH. BLVD. IMPROVEMENTS SOUTHPORT DEVELOPMENT		SHEET NO. 01	
NO.	DESCRIPTION	BY	DATE	APPROV.	DATE	APPROV.	DATE	APPROV.	DATE	APPROV.	DATE	APPROV.	DATE



SEC 8, TWP 23N, RGE SE, W1M.

T-349308

99323.02

BUSH, REED & WITCHINGS, INC.
 10000 1st Ave. S.W.
 Burien, WA 98148
 (206) 835-3333
 FAX (206) 835-3334
 WWW.BRWINC.COM

Checked for compliance
 to city standards
 [Signature]
 Date: [Blank]


LAYERSET 000-10
 Plotfile: 11/16/02 13:03

NO.	REVISION	BY	DATE	APPR.
1	FOR CITY OF RENTON REVIEW		11/22/02	
2	FOR CITY OF RENTON REVIEW		11/22/02	



**ROAD GEOMETRY COULON PARK ENTRANCE
 LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT**

DATE	11/16/02
PROJECT NO.	T-349309
DRAWN BY	
CHECKED BY	
SCALE	



SEC 8, TWP 23N, RGE 5E, W1M

T-349309

BURNS, ROED & HITCHCOCK, INC.
 98333102
 1400 10th Avenue, Suite 100
 Renton, WA 98057
 (206) 881-1111

CHIEFED FOR COMPLIANCE
 TO CITY STANDARDS
 Date: _____
 Name: _____


LAYERSET: D30-V2
Plotted: 11/19/22 13:02

NO	REVISION	BY	DATE	APPR
1	FOR CITY OF RENTON REVIEW		12/22/22	

CITY OF RENTON
Planning/Building/Public Works Dept.
Gregg Zimmerman P.E., Administrator

EROSION CONTROL STA 94+00 TO STA 144+00
LAKE WASH. BLVD. IMPROVEMENTS
SOUTHPORT DEVELOPMENT

3/1/22



- EROSION CONTROL NOTES:**
1. LIMITS OF CLEARING & GRADING
 2. DITCHED
 3. TEMPORARY DITCH (21" WIDE x 18" DEEP)
 4. ROCK CHECK DAM PER PLAN ON SHEET D30
 5. TEMPORARY CONSTRUCTION ENTRANCE PER STATE OR LET ODS
 6. STAKE-DRIVEN STAKE AND EMBANKMENT PER STATE OR LET ODS
 7. 12" TEMPORARY SD @ 1' INT. MIN.
 8. TEMPORARY CB (TYPE II)
- INC - NOT IN CONTRACT**

R-349301

BASH, ROED & HITCHINGS, INC.
CIVIL ENGINEERS & LAND SURVEYORS
93323.02

CHECKED FOR COMPLIANCE

DATE	
BY	
DATE	
BY	

GP, L-349301

LAYERS: 000-00-03
 Printed: 11/14/02 12:58


NO.	REVISION	BY	DATE	APPR.	DATE	APPR.
1	FOR CITY OF RENTON REVIEW		8/21/02			



CITY OF RENTON
 Planning/Building/Public Works Dept.
 Engineering P.E. Administrator

EROSION CONTROL STA 14+80 TO STA 20+00
LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT

3/1/00
 151



- EROSION CONTROL NOTES:**
- ① LIMITS OF SETBACKS & DRIVWAYS
 - ② FILTER FABRIC FENCE PER DETAIL ON SHEET C20
 - ③ TEMPORARY DITCH (2:1 SLOPES)
 - ④ ROCK CHECK DAM PER DETAIL ON SHEET C20
 - ⑤ CG & STORM DRAIN PER SHEET C3
 - ⑥ SILT LOAN RUNOFF SHALL NOT BE DISCHARGED TO DRAINAGE

R-349302

BUSH, ROED & HITCHCOCK, INC.
 ENGINEERS & ARCHITECTS
 9822102
 1000 1st Avenue, Suite 100
 Renton, WA 98057
 Phone: (206) 881-1111
 Fax: (206) 881-1112
 www.bushroed.com

DESIGNED FOR COMPLIANCE
 WITH CITY STANDARDS

SEC 8, TWP 23N, RGE 5E, W.M.


LAYERSET:ERO-V4
 DATE: 11/16/02 12:57

NO.	DESCRIPTION	DATE	BY	APP'D.
1	FOR CITY OF RENTON REVIEW			
2	REVISION			



CITY OF RENTON
 Planning/Building/Public Works Dept.
 Greg Zimmerman, P.E., Administrator

EROSION CONTROL STA 20+00 TO STA 23+00
LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT



- EROSION CONTROL NOTES.**
- ① LIMITS OF CLEARING & GRADING
 - ② TEMPORARY DITCH (21' SPACING)
 - ③ ROCK CHECK DAM PER DETAIL ON SHEET C80

SEC 8, TWP 23N, RGE 5E, W.M.

R-349303

BUSH, ROED & HITCHINGS, INC.
 CIVIL ENGINEERS & LAND SURVEYORS
 98323.02
 1000 1st Avenue, Suite 200
 Renton, WA 98057
 Phone: (206) 875-1234
 Fax: (206) 875-1234


CHECKED FOR COMPLIANCE
 TO CITY STANDARDS

DATE: _____
 BY: _____

LAVERSET, 98323ACD
 Printed: 11/18/02 11:56



NO.	REVISION	BY	DATE	APP.
1	FOR CITY OF RENTON REVIEW		02/23/02	

AS NOTED



**DRIVEWAY ACCESS EASEMENT
 LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT**

63/09/00



SEC. 8, TWP. 23N, RGE. SE, W.M.

DL R-349306

BLISS, ROSS & HITCHCOCK, INC.
 CIVIL ENGINEERS & LAND SURVEYORS
 1000 1st Avenue, Suite 200
 Renton, WA 98057
 98323.02



CHIEF OF PERMITS
 TO CITY ENGINEERS

R-349306

- LEGEND:**
- PRIORITY LINE
 - EXIST. EASEMENT LINE
 - NEW EASEMENT LINE

- NOTES:**
- 1) R/W PROPOSED SOUTHPORT DEVELOPMENT TO BE COORD. WITH BLISS & THE THAMISO GROUP, INC.
 - 2) CONCRETE & IRON TRUCK CROSSING APPROX (DESIGN CONFORM WITH BNSF)
 - 3) EXIST. ACCESS EASEMENT FROM B.N.S.F. R.O.W. AREA = 16.73' ±
 - 4) PROPOSED ACCESS EASEMENT FROM B.N.S.F. R.O.W. AREA = 14.73' ±

DEVELOPER:
 SOUTHPORT DEVELOPMENT, INC.
 10844 NE 5TH STREET, STE. 200
 RENTON, WA 98057
 PHONE: (425) 888-3088

TRANSPORTATION ENGINEER:
 THE THAMISO GROUP, INC.
 11720 14TH AVENUE NE, STE. 600
 RENTON, WA 98057
 PHONE: (425) 821-3843




LAYERSET 04/11/2021
 Plotfile: 10/10/2021 11:38

NO.	REVISION	BY	DATE	APPROVED
1	FOR CITY OF SOUTH BEACH	DA/VA	4/23/21	
2	FOR CITY OF SOUTH BEACH	DA/VA	4/23/21	

CITY OF RENTON
 Planning/Building/Public Works Dept.
 Gregg Zimmerman P.E., Administrator

**ROAD SECTIONS
 LAKE WASH. BLVD. IMPROVEMENTS
 SOUTHPORT DEVELOPMENT**

DATE	3/1/20
SCALE	AS SHOWN
DWG. NO.	017




- 1 2" COMP. 1.00TH CLASS B ASPH/CONC PAVEMENT
- 2 6" COMP. 1.00TH ASPHALT TREATED BASE
- 3 6" COMP. 1.00TH CRUSHED SURFACING BASE COURSE
- 4 SUBGRADE OR GRAVEL BANNER COMPACTED TO 95%
- 5 TYPE A CURB ON SHEET C18
- 6 4" THICK CONCRETE SIDEWALK PER DETAIL ON SHEET C18
- 7 1"-1/2" DEPTH CLASS B ASPH/CONC RELAY
- 8 DIMENSION TO SANGU VARIES PER GEOMETRIC PLANS DIMENSION TO SANGU VARIES PER GEOMETRIC PLANS IS NOT LOCATED AT REED TRAFFIC LINE.

T-349310

**GEGRID REINFORCED
 BLOCK WALL**
 NO SCALE

NOT RECONTRACT
 (FUTURE PHASE 2 WORK)



DAVIS, BOND & HITCHCOCK, INC.
 CIVIL ENGINEERS & LAND SURVEYORS
 99323.02
 CHECKED FOR COMPLIANCE TO CITY STANDARDS
 DATE 5/11/21
 SEAL

SEC. 8, TWP. 23N, RGE. 5E, W.M.

NO.	REVISION	DATE	BY
1	FOR CITY OF RENTON REVIEW	02/11/02	ASB






CITY OF RENTON
 Planning/Building/Public Works Dept.
 Greg Zimmerman, P.E., Administrator



EROSION CONTROL DETAILS
LAKE WASH. BLVD. IMPROVEMENTS
SOUTHPORT DEVELOPMENT

3/1/00
DATE
SCALE
PROJECT NO.
DATE
BY


- NOTES:**
1. EXTEND THE FILTER FABRIC/ROCK MESH BEYOND THE SLOPE TO PROTECT THE EXPOSED SOIL SURFACE.
 2. AT LEAST 1" OF SAND SHOULD BE PLACED OVER THE FILTER FABRIC/ROCK MESH. THE DEPTH OF SAND SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE.
 3. SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE. THE SAND MUST BE PLACED AWAY FROM THE MESH AND CLEANED OR REPLACED PERIODICALLY.
 4. AFTER LAST RAINFALL AND AT LEAST DAILY DURING PROLONGED PERIODS, ANY REMAINS SHOULD BE WASH AWAY.






- NOTES:**
1. FILTER FABRIC SHOULD BE INSTALLED PERPENDICULAR TO FLOW.
 2. MAXIMUM SPACING BETWEEN PERPENDICULARS TO FLOW SHALL BE 12" FT.
 3. MAXIMUM SPACING BETWEEN PERPENDICULARS TO FLOW SHALL BE 12" FT.
 4. 6" DIA. OR LARGER OF THE STAKE SHOULD BE USED. STAKES SHOULD BE PLACED TO BE AT LEAST 12" FROM THE EDGE OF THE ROADWAY.
 5. STAKES SHOULD BE SPACED WITH 3/4" DIA. DIALECTOR WASHED GRAVEL.
 6. FILTER FABRIC SHOULD BE WASHED WITH HIGH PRESSURE WATER TO REMOVE DEBRIS.
 7. AFTER LAST RAINFALL AND AT LEAST DAILY DURING PROLONGED PERIODS, ANY REMAINS SHOULD BE WASH AWAY.





- NOTES:**
1. USE 12" OR 18" DIA. STAKES OR EQUIVALENT FOR BRUSH BARRIERS.
 2. BRUSH SHOULD BE PLACED OVER THE FILTER FABRIC/ROCK MESH. THE DEPTH OF SAND SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE.
 3. SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE. THE SAND MUST BE PLACED AWAY FROM THE MESH AND CLEANED OR REPLACED PERIODICALLY.
 4. AFTER LAST RAINFALL AND AT LEAST DAILY DURING PROLONGED PERIODS, ANY REMAINS SHOULD BE WASH AWAY.



- NOTES:**
1. USE 12" OR 18" DIA. STAKES OR EQUIVALENT FOR BRUSH BARRIERS.
 2. BRUSH SHOULD BE PLACED OVER THE FILTER FABRIC/ROCK MESH. THE DEPTH OF SAND SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE.
 3. SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE. THE SAND MUST BE PLACED AWAY FROM THE MESH AND CLEANED OR REPLACED PERIODICALLY.
 4. AFTER LAST RAINFALL AND AT LEAST DAILY DURING PROLONGED PERIODS, ANY REMAINS SHOULD BE WASH AWAY.



- NOTES:**
1. USE 12" OR 18" DIA. STAKES OR EQUIVALENT FOR BRUSH BARRIERS.
 2. BRUSH SHOULD BE PLACED OVER THE FILTER FABRIC/ROCK MESH. THE DEPTH OF SAND SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE.
 3. SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE. THE SAND MUST BE PLACED AWAY FROM THE MESH AND CLEANED OR REPLACED PERIODICALLY.
 4. AFTER LAST RAINFALL AND AT LEAST DAILY DURING PROLONGED PERIODS, ANY REMAINS SHOULD BE WASH AWAY.



- NOTES:**
1. USE 12" OR 18" DIA. STAKES OR EQUIVALENT FOR BRUSH BARRIERS.
 2. BRUSH SHOULD BE PLACED OVER THE FILTER FABRIC/ROCK MESH. THE DEPTH OF SAND SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE.
 3. SHOULD BE AT LEAST 1" OVER THE ENTIRE SLOPE. THE SAND MUST BE PLACED AWAY FROM THE MESH AND CLEANED OR REPLACED PERIODICALLY.
 4. AFTER LAST RAINFALL AND AT LEAST DAILY DURING PROLONGED PERIODS, ANY REMAINS SHOULD BE WASH AWAY.



BUSH, BORD & HATHORN, INC.
 98323.02
 CHECKED FOR COMPLIANCE TO CITY STANDARDS

R-349308

**CONSTRUCTION NOTES
LAKE WASH. BLVD. IMPROVEMENTS
SOUTHPORT DEVELOPMENT**



LAKE WASH. BLVD. IMPROVEMENTS
Printed: 11/16/02 11:48

NO.	DATE	REVISION
1		FOR CITY OF RENTON REVIEW

SHARPE WATER DRAINAGE NOTES & SPECIFICATIONS

1. REVIEW AND DEVELOPMENT OF DEVELOPMENT ACTIVITY GROUPS, A PRELIMINARY DRAINAGE MAPS BE HELD WITH THE CITY OF RENTON.
2. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CITY OF RENTON SPECIFICATIONS FOR WATER, SEWER AND SANITATION WORKS ASSOCIATION (S&SWA) AS ADOPTED BY THE CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
3. THE SERVICE WATER DRAINAGE SYSTEM SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE CITY OF RENTON SPECIFICATIONS FOR WATER, SEWER AND SANITATION WORKS ASSOCIATION (S&SWA) AS ADOPTED BY THE CITY OF RENTON DEPARTMENT OF PUBLIC WORKS. ANY DEVIATIONS FROM THE APPROVED SPECIFICATIONS SHALL BE APPROVED BY THE CITY OF RENTON DEPARTMENT OF PUBLIC WORKS OR SHARPE WATER UTILITY.
4. A COPY OF THESE APPROVED PLANS MUST BE ON THE JOB SITE THROUGHOUT CONSTRUCTION IS IN PROGRESS.
5. DRAIN SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS. PROTECTIVE COVERINGS AND ALL RESTRICTIONS/RESTRICTIONS MUST BE IN PLACE AND NOT LIFTED UNTIL THE PROJECT IS COMPLETE. ANY RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
6. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
7. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
8. GRADES SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
9. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
10. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
11. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
12. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
13. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
14. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
15. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
16. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
17. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
18. ALL RESTRICTIONS/RESTRICTIONS MUST BE MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.

EROSION CONTROL NOTES

1. EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
2. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
3. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
4. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
5. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
6. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
7. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
8. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
9. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
10. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
11. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
12. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
13. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
14. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
15. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
16. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
17. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
18. ALL EROSION CONTROL MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.

BASELAW DRAINAGE NOTES



1. BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
2. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
3. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
4. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
5. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
6. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
7. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
8. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
9. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
10. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
11. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
12. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
13. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
14. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
15. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
16. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
17. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.
18. ALL BASELAW DRAINAGE MEASURES SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION BY CITY OF RENTON DEPARTMENT OF PUBLIC WORKS.

R-349309

BUSH ROAD & HITCHINGS, INC.
1100 1st Ave. SE
Renton, WA 98057
Tel: 206-881-1100
Fax: 206-881-1101

98323.02

Checked for compliance to City Standards



SEC 8, TWP 23N, RGE 5E, W.M.

GENERAL NOTES
FROM GENERAL NOTES, SEE SHEET CH1

CHANNELIZATION NOTES

- 1) DISTAL END SIGN WITH WHITE BACK, FOR CITY OF RENTON
- 2) DISTAL END SIGN WITH RED BACK, FOR CITY OF RENTON
- 3) DISTAL END SIGN WITH GREEN BACK, FOR CITY OF RENTON
- 4) DISTAL END SIGN WITH BLUE BACK, FOR CITY OF RENTON
- 5) DISTAL END SIGN WITH YELLOW BACK, FOR CITY OF RENTON
- 6) DISTAL END SIGN WITH PINK BACK, FOR CITY OF RENTON
- 7) DISTAL END SIGN WITH PURPLE BACK, FOR CITY OF RENTON
- 8) DISTAL END SIGN WITH BROWN BACK, FOR CITY OF RENTON
- 9) DISTAL END SIGN WITH BLACK BACK, FOR CITY OF RENTON
- 10) DISTAL END SIGN WITH WHITE BACK, FOR CITY OF RENTON
- 11) DISTAL END SIGN WITH GREY BACK, FOR CITY OF RENTON
- 12) DISTAL END SIGN WITH LIGHT BLUE BACK, FOR CITY OF RENTON
- 13) DISTAL END SIGN WITH LIGHT GREEN BACK, FOR CITY OF RENTON
- 14) DISTAL END SIGN WITH LIGHT YELLOW BACK, FOR CITY OF RENTON
- 15) DISTAL END SIGN WITH LIGHT PINK BACK, FOR CITY OF RENTON
- 16) DISTAL END SIGN WITH LIGHT PURPLE BACK, FOR CITY OF RENTON
- 17) DISTAL END SIGN WITH LIGHT BROWN BACK, FOR CITY OF RENTON
- 18) DISTAL END SIGN WITH LIGHT BLACK BACK, FOR CITY OF RENTON
- 19) DISTAL END SIGN WITH LIGHT WHITE BACK, FOR CITY OF RENTON
- 20) DISTAL END SIGN WITH LIGHT GREY BACK, FOR CITY OF RENTON

CONSTRUCTION NOTES (SEE SHEET CH1)

- 1) CONCRETE CURB WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 2) GRASS WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 3) 18" DIA. BOLLARD WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 4) BOLLARD MOUNTED SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 5) STOP SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 6) TRAFFIC CONTROL SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 7) 18" DIA. BOLLARD WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 8) BOLLARD MOUNTED SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 9) STOP SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 10) TRAFFIC CONTROL SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 11) 18" DIA. BOLLARD WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 12) BOLLARD MOUNTED SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 13) STOP SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 14) TRAFFIC CONTROL SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 15) 18" DIA. BOLLARD WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 16) BOLLARD MOUNTED SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 17) STOP SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 18) TRAFFIC CONTROL SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 19) 18" DIA. BOLLARD WITH 2" REINFORCING BARS AT 18" ON CENTER.
- 20) BOLLARD MOUNTED SIGN WITH 2" REINFORCING BARS AT 18" ON CENTER.




CHECK FOR COMPLIANCE TO
CITY STANDARDS

DATE	
BY	
CHKD	
APPD	



PROJECT	LAKE WASHINGTON BOULEVARD/ SITE ACCESS
CLIENT	CITY OF RENTON
DATE	APR 2014
BY	CH2M HILL
REVISION	

SEC 8, TWP 23N, RGE 5E, W.M.



- GENERAL NOTES**
FOR GENERAL NOTES, SEE SHEET CH1
- CHANNELIZATION NOTES**
1. CHANNELIZATION MARKERS SHALL BE PAINTED WHITE UAC, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 2. INSTALL TYPE 'A' REFLECTORIZED PAVEMENT MARKING PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 3. INSTALL 4" RADIUS WHITE PAINTED EDGE STIPES, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 4. INSTALL 4" RADIUS WHITE PAINTED CORNER UAC, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 5. INSTALL 4" RADIUS WHITE PAINTED DOTTED EXTENSION LINE PER DETAIL A, SHEET CH1.
 6. INSTALL WHITE REFLECTIVE PLASTIC MOUNTING STUDS, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 7. INSTALL 1/2" X 1/2" REFLECTIVE PLASTIC MOUNTING STUDS, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 8. INSTALL TYPE 'C' BLACK PREGRADE TRAFFIC CURBS, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 9. INSTALL 80% APPROACH UAC, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 10. INSTALL HIGHWAY STIPES PER DETAIL B, SHEET CH1.

- CONSTRUCTION NOTES (THIS SHEET ONLY)**
1. REGULAR EXISTING TRAFFIC MARKINGS SHALL BE REMOVED PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 2. INSTALL 4" RADIUS WHITE PAINTED CORNER UAC, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 3. INSTALL 4" RADIUS WHITE PAINTED DOTTED EXTENSION LINE PER DETAIL A, SHEET CH1.
 4. INSTALL WHITE REFLECTIVE PLASTIC MOUNTING STUDS, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.
 5. INSTALL TYPE 'C' BLACK PREGRADE TRAFFIC CURBS, PER CITY OF RENTON STANDARD PLANS, PAGE 1007.




SEC 8, TWP 23N, RGE 5E, W.M.

MATCH LINE - THIS SHEET BELOW (RIGHT)


CONSTRUCTION NOTES

1. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
2. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
3. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
4. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
5. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
6. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
7. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
8. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
9. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
10. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
11. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
12. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
13. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
14. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.
15. CONTRACTOR TO VERIFY ALL DIMENSIONS AND LOCATIONS OF EXISTING UTILITIES AND (UT) MARKERS WITH THE UTILITY LOCATOR PRIOR TO CONSTRUCTION.



LAKE WASHINGTON BOULEVARD / RENTON CITY OF TENWA TRAFFIC SIGNAL PLAN DATE: 12/13/11

16. PER TO REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
17. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
18. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
19. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
20. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
21. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
22. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
23. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
24. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
25. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
26. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
27. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
28. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
29. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
30. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
31. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
32. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
33. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
34. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
35. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
36. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
37. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
38. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
39. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
40. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
41. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
42. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
43. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
44. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
45. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
46. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
47. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
48. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
49. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
50. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
51. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
52. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
53. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
54. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
55. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
56. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
57. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
58. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
59. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
60. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
61. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
62. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
63. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
64. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
65. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
66. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
67. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
68. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
69. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
70. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
71. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
72. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
73. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
74. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
75. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
76. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
77. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
78. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
79. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
80. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
81. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
82. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
83. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
84. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
85. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
86. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
87. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
88. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
89. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
90. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
91. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
92. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
93. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
94. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
95. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
96. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
97. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
98. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
99. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE
100. REPLACE EXISTING WPS LAMPAKE WITH LED LAMPAKE



LAKE WASHINGTON BOULEVARD / RENTON CITY OF TENWA TRAFFIC SIGNAL PLAN DATE: 12/13/11

CHECK FOR COMPLIANCE WITH CITY STANDARDS

DATE: _____

DRAWN BY: _____

DATE: _____

LAKE WASHINGTON BOULEVARD / RENTON CITY OF TENWA TRAFFIC SIGNAL PLAN DATE: 12/13/11

LAKE WASHINGTON BOULEVARD / RENTON CITY OF TENWA TRAFFIC SIGNAL PLAN DATE: 12/13/11

LAKE WASHINGTON BOULEVARD / RENTON CITY OF TENWA TRAFFIC SIGNAL PLAN DATE: 12/13/11

SEC. B, TWP. 23N, RGE. 5E, W.M.

SIGNAL & ILLUMINATION GENERAL NOTES



- THE LOCATION OF ALL SIGNAL, JUNCTION BOXES, AND CABLES SHOWN ON THIS PLAN ARE APPROXIMATE ONLY. FINAL LOCATIONS SHALL BE DETERMINED BY THE CONTRACTOR AND CONFIRMED IN THE FIELD BY THE ENGINEER.
- ALL WORK SHALL BE IN ACCORDANCE WITH THESE PLANS, THE PROJECT SPECIAL PROVISIONS, CITY OF MILWAUKEE STANDARDS AND MOST RECENT STANDARDS AND SPECIFICATIONS.
- THE LOCATIONS OF FOUNDING SHEETS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR AS NECESSARY.
- THE CONTRACTOR SHALL SUBMIT A REQUEST TO THE CITY OF MILWAUKEE FOR WORKMAN APPROVAL, AT THE EARLIEST POSSIBLE DATE.
- ALL WORK SHALL BE COMPLETED WITH UTILITY AGENCY REQUIREMENTS. THE CONTRACTOR SHALL CONTACT ALL PERTINENT UTILITY AGENCIES 48 HOURS BEFORE COMMENSAL WORK, AND SHALL COORDINATE WITH AFFECTED UTILITY AGENCIES THROUGHOUT THE PROJECT.
- ALL WORK SHALL BE IN ACCORDANCE WITH THE CITY OF MILWAUKEE STANDARD SPECIFICATIONS FOR THE PROJECT.
- POLE FOUNDATIONS SHALL NOT BE RECOVERED AND POLES BETWEEN SIGNAL LOCATIONS ARE APPROVED BY THE ENGINEER.
- THE CONTRACTOR SHALL VERIFY THAT 10 FEET WORKMAN CLEARANCE IS MAINTAINED BETWEEN LAMPHIRE POLES AND OVERHEAD POWER LINES. IF A CONFLICT IS DISCOVERED, THE CONTRACTOR SHALL NOTIFY THE ENGINEER PRIOR TO FOUNDATION INSTALLATION.
- FOR SIGNAL SYSTEM COORDINATION WITH THE CITY OF MILWAUKEE, CONTRACTOR SHALL CONTACT TRANSPORTATION MAINTENANCE DIVISION AT (414) 436-7423.

SERVICE #1145 BURNER SCHEDULE

ITEM	DESCRIPTION	QUANTITY
1	1" - 100'	1
2	1" - 150'	1
3	1" - 200'	1
4	1" - 250'	1
5	1" - 300'	1
6	1" - 350'	1
7	1" - 400'	1
8	1" - 450'	1
9	1" - 500'	1
10	1" - 550'	1
11	1" - 600'	1
12	1" - 650'	1
13	1" - 700'	1
14	1" - 750'	1
15	1" - 800'	1
16	1" - 850'	1
17	1" - 900'	1
18	1" - 950'	1
19	1" - 1000'	1

LAMPHIRE POLE SCHEDULE

LAMPHIRE POLE NO.	MANUFACTURER	HEIGHT	ARM LENGTH	ARM SPACING	POLE TYPE	POLE TYPE	POLE TYPE
1	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
2	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
3	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
4	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
5	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
6	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
7	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
8	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
9	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
10	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE
11	BOURNS BROS	15.5H	12.5'	12.5'	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE	NEW HANSON SIGNAL POLE



WIRING SCHEDULE

ITEM	DESCRIPTION	QUANTITY	DATE	BY	CHECKED	DATE	BY
1	1" - 100'	1					
2	1" - 150'	1					
3	1" - 200'	1					
4	1" - 250'	1					
5	1" - 300'	1					
6	1" - 350'	1					
7	1" - 400'	1					
8	1" - 450'	1					
9	1" - 500'	1					
10	1" - 550'	1					
11	1" - 600'	1					
12	1" - 650'	1					
13	1" - 700'	1					
14	1" - 750'	1					
15	1" - 800'	1					
16	1" - 850'	1					
17	1" - 900'	1					
18	1" - 950'	1					
19	1" - 1000'	1					

REVISIONS 1-56 # 1 TO FOR FUTURE PER PER FOR 30-11-17 BY TRANSPORTATION MAINTENANCE DIVISION

WORKING NOTES

- ALL CONCRETE CONTAINING CORNER REINFORCEMENT SHALL INCLUDE CORNER WIRE STRAP WITH SIZE SHALL MATCH THE LARGEST CORNER (USE #4 OR #5 NOTED OTHERWISE IN THE WORK NOTES). CORNERS SHALL BE LABELED WITH "CORNER" AND SHALL CONTAIN DETACHABLE PULL TABS.
- ALL CONCRETE SHALL BE TWO TIER 40, EXCEPT UNDER ROADWAY USE PVC SCHEDULE 80 CONDUIT

CHECK FOR COMPLIANCE WITH CITY STANDARDS

DATE: _____

BY: _____

SCALE: _____

LAKE WASHINGTON BOULEVARD/ TRAFFIC SIGNAL PLAN


CITY OF MILWAUKEE

PROJECT: LAKE WASHINGTON BOULEVARD/ TRAFFIC SIGNAL PLAN









DATE: _____

BY: _____


SCALE: _____







12/27/13	LAKE WASHINGTON BOULEVARD/ SITE ACCESS	SIGNAL WIRING DIAGRAM	1
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			



NO.	DESCRIPTION	DATE	BY	CHKD.	APP'D.









STANDARD PLAN 100-2
 ADOPTED
 STANDARD PLANS
 LAST DATE: 03/08
 BY PAGE: 10002.2

ADDITIONAL NOTES:
 1. The symbol shall be white on a blue background.
 2. The symbol shall be 18" high by 18" wide.
 3. The symbol shall be placed in the center of the lane.
 4. The symbol shall be placed on a 1/2" thick concrete base.



ADOPTED
 CITY OF RENTON
 LAST DATE: 11/09
 BY PAGE: 10006

PERMANENT MARKING SYMBOLS

STOP LINE

EDGE OF ROAD LINE

TURN MARKINGS

ISLAND W/ CROSSWALKING

LANE LINES

RAILROAD CROSSING WARNING

ADDITIONAL NOTES:
 1. The Road Marking shall be white on a dark background.
 2. The Road Marking shall be 1/2" thick.
 3. The Road Marking shall be placed on a 1/2" thick concrete base.

ADDITIONAL NOTES:
 1. The Road Marking shall be white on a dark background.
 2. The Road Marking shall be 1/2" thick.
 3. The Road Marking shall be placed on a 1/2" thick concrete base.

CHECK FOR COMPLIANCE TO CITY STANDARDS

DATE: _____
 DATE: _____
 DATE: _____

14 18 88

July 13, 2014

Kathy Hunter, Deputy Assistant Director, Transportation Safety
Washington Utilities and Transportation Commission
1300 S. Evergreen Park Dr. SW
PO Box 47250
Olympia, WA 98504-7250

Subject: Lake Washington Boulevard/Houser Way/Southport – Interim Conditions
DOT#091724U, M.P. 3.97
DOT#091725B, M.P. 4.05
BNSF Railway, Woodinville Subdivision, LS 0405

Dear Ms. Hunter,

The following is a narrative describing the proposed two-phase construction of improvements to the Lake Washington Boulevard/Houser Way/Southport Site Access intersection, associated with the Southport Hotel development. The Southport development is required to mitigate its traffic impacts by widening, realigning, and signalizing the existing intersection. The purpose of this narrative is to demonstrate that a safe, effective Interim (Phase 1) traffic control plan can be operated in conjunction with existing BNSF Mainline and Spur Railroad crossings until full vehicular traffic signal and associated Railroad Signal improvements are made functional in 2015 (Phase2).

The City of Renton and Southport desire to complete all physical/hardscape improvements to the intersection now (summer/fall of 2014), consistent with the Ultimate Conditions described below. New vehicular traffic signals would operate in flashing-red "All Way Stop" mode until such time that BNSF can complete and make-functional new railroad gates per the Ultimate conditions (anticipated summer 2015). At that time, the vehicular traffic signal would be converted to fully-functional Red-Yellow-Green operations.

Existing Conditions at Railroad Crossings:

The existing Mainline track crosses Lake Washington Boulevards immediately north of Houser Way/Southport Boulevard at an approximate 45-degree angle. Lake Washington Boulevard consists of single northbound and southbound vehicular lanes at the crossing, with adjacent bike lanes. The existing intersection operates as an all-way stop. The existing Spur track crosses Southport Boulevard immediately west of Lake Washington Boulevard at an approximate 90-degree angle. Southport Boulevard consists of single eastbound and westbound vehicular lanes at the crossing.

Flashing-light railroad signals with gates are provided at all approaches to the mainline and spur crossings. An overhead cantilever structure is provided for the southbound approach to the mainline crossing of Lake Washington Boulevard.

Ultimate Conditions at Railroad Crossings:

Lake Washington Boulevard would consist of single northbound and dual-southbound vehicular lanes at the crossing, with adjacent bike lanes. Southport Boulevard would consist of dual eastbound and westbound vehicular lanes at the Spur crossing, with adjacent sidewalks.

Proposed Interim Conditions at Railroad Crossings

Proposed interim conditions would include construction of all ultimate improvements, with minor modifications as reflected in 7-13-14 Interim Traffic Plan. The intersection would operate as an all-way stop consistent with existing conditions, with vehicular traffic signal heads functioning in flashing-red mode, and associated stop signs for all approaches. Existing railroad gates would remain functional. Protective barrier would be provided to protect existing gates, and to channelize vehicles through interim striping. Roadway illumination via new stand-alone luminaire poles and traffic signal pole-mounted luminaires would be provided, which would significantly improve nighttime safety.

Summary

In summary, the following justifications support the proposed two-phase approach to construction of improvements:

- Public safety would be maintained. The proposed Interim (Phase 1) plan would provide for safe and efficient movement of vehicles, pedestrians, and bikes at the railroad crossings. Signage, pavement markings, and protective barriers would be implemented to protect railroad gates and channelize vehicles at railroad crossings consistent with existing operations/alignments.
- New pedestrian facilities (ADA-compliant sidewalks, ramps) as well as roadway illumination would result in immediate accessibility and safety improvements over existing conditions.
- Gene Coulon Park Seasonal restrictions do not allow for construction for the majority of summer (approximately June through August). Because this is a significant roadway improvement project with along construction duration, there is substantial benefit in constructing improvements in two phases.
- The duration of Phase 1 is expected to be relatively short (approximately one year).
- The City of Renton supports the proposed 2-phase construction approach.
- BNSF anticipates availability of construction crews and materials no sooner than summer 2015.

We appreciate your review of the attached materials. Please feel free to call me with any questions at (425) 250-5002

Sincerely,
Transportation Engineering NorthWest



Chis Bicket, PE, Design Manager
bicket@tenw.com