UT-043007 Smith Direct Eschelon Telecom, Inc. July 23, 2004 Exhibit No. ______ (RJ-S-51)



Service Performance Indicator Definitions (PID)

14-State 271 PID Version 7.1

PO-2 - Electronic Flow-through

Purpose:

Monitors the extent Qwest's processing of CLEC Local Service Requests (LSRs) is completely electronic, focusing on the degree that electronically-transmitted LSRs flow directly to the service order processor without human intervention or without manual retyping.

Description:

PO-2A - Measures the percentage of all electronic LSRs that flow from the specified electronic gateway interface to the Service Order Processor (SOP) without any human intervention.

Includes all LSRs that are submitted electronically through the specified interface during the
reporting period, subject to exclusions specified below.

PO-2B – Measures the percentage of all flow-through-eligible LSRs NCTE ¹ that flow from the specified electronic gateway interface to the SOP without any human intervention.

 Includes all flow-through-eligible LSRs that are submitted electronically through the specified interface during the reporting period, subject to exclusions specified below.

Reporting Period: One month	Unit of Measure: Percent
Reporting Comparisons: CLEC aggregate, individual CLEC	Disaggregation Reporting: Statewide level (per multi- state system serving the state). Results for PO-2A and PO-2B will be reported according to the gateway interface* used to submit the LSR: 1 LSRs received via IMA-GUI 2 LSRs received via IMA-EDI **CO also reports an aggregate of IMA-GUI and IMA-EDI results.
I .	. ————————————————————————————————————

Formula:

- PO-2A = [(Number of Electronic LSRs that pass from the Cateway Interface to the SOP without human intervention) + (Total Number of Electronic LSRs that pass through the Cateway Interface)] x 100
- PO-2B = [(Number of flow-through-eligible Electronic LSRs that actually pass from the Cateway Interface to the SOP without human intervention) + (Number of flow-through-eligible Electronic LSRs received, through the Gateway Interface)] × 100

Exclusions:

- Rejected LSRs and LSRs containing CLEC-caused non-fatal errors.
- Non-electronic LSRs (e.g., via fax or courier).
- Records with invalid product codes.
- Records missing data essential to the calculation of the measurement per the PID.
- Duplicate LSR numbers. (Exclusion to be eliminated upon implementation of IMA capability to disallow duplicate LSR #'s.)
- Invalid start/stop dates/times.

PO-2 - Electronic Flow-through (continued)

Standards: Product Reporting: PO-2A: Resale CO: CO PO-2B benchmarks minus 10 percent NOTE 2 Unbundled Loops (with or All Other States: Diagnostic without Local Number Portability) PO-2B: NOTE 2 Local Number Portability UNE-P (POTS) and UNE-P 95% Resale: (Centrex 21). 85% Unbundled Loops: Line Sharing 95% LNP: 95% UNE-P (POTS & Centrex 21): Diagnostic Lìne Sharing: Notes: Availability: The list of LSR types classified as eligible for flow through is contained in Available (except as the "LSRs Eligible for Flow Through" matrix. This matrix also includes foliows): availability for enhancements to flow through. Matrix will be distributed through the CMP process. Combined reporting 2. In Colorado the standard for PO-2 is considered met if the standard for of JNE-P (POTS). either PO-2A or PO-2B is met. For both FO-2A and PO-2B, the and UNE-P (Centrex) benchmark percentages shown apply to the aggregations of PO-2A-1 and 21) - beginning with PO-2A-2 (i.e., the combined PC-2A result) and of PO-2B-1 and PO-2B-2 Jul 04 data on the (i.e., the combined PO-2B result). Aug 04 report. The standard and future disaggregated reporting of the Line Sharing product is TBD, pending resolution of TRO issues. Line Shanng beginning with Jul C4 data on the Aug 04 report