

Sondra,

This meets our needs and should satisfy the builder community. Thank you for taking the time to work with us to address the conduit issue.

Jim Hogan
Manager
Standards & Compliance Dept.
Puget Sound Energy
425-462-3957

-----Original Message-----

From: Sondra Walsh [mailto:swalsh@wutc.wa.gov]
Sent: Wednesday, April 20, 2005 8:04 AM
To: Hogan, Jim; Daugherty, Kaaren
Cc: Ann Rendahl
Subject: Gas rules

Here is the rule language change the Commission is making to WAC 480-93-178.

At this time the Commission is moving forward with adoption of the rules.

If you have any questions please let me know.

I will be forwarding the language to the Building Industry Association of Washington (Trent Matson of BIAW)

Thanks

(4) When installing plastic pipelines parallel to other underground utilities, operators must ensure there is a minimum of twelve inches of separation from the other utilities. Where a minimum twelve inches of separation is not possible, operators must take adequate precautions, such as inserting the plastic pipeline in conduit, to minimize any potential hazards resulting from the close proximity to the other utilities.

Sondra Walsh
Senior Policy Strategist
Washington Utilities and Transportation Commission
1300 S Evergreen Park Dr. S.W.
Olympia, WA 98504
TEL (360) 664-1286
FAX (360) 586-1172
E-mail swalsh@wutc.wa.gov