


WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

)	DOCKET NO. TR- 152114-P
)	
<u>Washington State Dept. of Transportation</u>)	PETITION TO INSTALL OR
Petitioner,)	MODIFY AN INTER-TIE BETWEEN
)	A HIGHWAY SIGNAL AND A
vs.)	RAILROAD CROSSING SIGNAL
)	SYSTEM
)	
<u>Tri City Railroad</u>)	
Respondent)	
)	USDOT No.: 310402M
)	

The Petitioner asks the Washington Utilities and Transportation Commission to approve installation of an inter-tie between a highway signal and a railroad crossing signal system.

Section 1 – Petitioner’s Information

Washington State Department of Transportation	
Petitioner	
 11/6/15	
Signature	
310 Maple Park Avenue SE, Suite 2B	
Street Address	
Olympia, WA 98504	
City, State and Zip Code	
PO Box 47329 Olympia, WA 98504-7329	
Mailing Address, if different than the street address	
Ahmer Nizam	
Contact Person Name	
360-705-7271 nizama@wsdot.wa.gov	
Contact Phone Number and E-mail Address	

RECEIVED
 RECORDS MANAGEMENT
 2015 NOV -6 AM 9:58
 STATE OF WASH.
 UTIL AND TRANSP.
 COMMISSION

Section 2 – Respondent's Information

<u>Tri City Railroad</u>
Respondent
<u>PO Box 1700</u>
Street Address
<u>Richland, WA 99352</u>
City, State and Zip Code
<u></u>
Mailing Address, if different than the street address
<u>Rhett Peterson</u>
Contact Person Name
<u>509-371-8313 or 509-727-8824 rhettwater@me.com</u>
Contact Phone Number and E-mail Address

Section 3 – Crossing Location

1. Existing highway/roadway <u>SR 240 (signal) at Airport Way</u>
2. Existing railroad <u>Tri City Railroad</u>
3. USDOT Crossing No. <u>310402M</u>
4. Located in the <u>NE</u> 1/4 of the <u>NW</u> 1/4 of <u>Sec.3</u> , Twp. <u>T9N</u> , Range <u>R28E</u> W.M.
5. GPS location, if known <u></u>
7. Railroad mile post (nearest tenth) <u>39.5</u>
8. City <u>Richland</u> County <u>Benton</u>

Section 4 – Vehicle Traffic

1. Type of public road at the crossing State County City
 Port State Park Other _____

2. Name of public road SR 240 and Airport Way

3. Road authority WSDOT

4. Average daily vehicle traffic over the crossing 784 on Airport Way in 1996 (27,000 on SR 240 in 2014)
Vehicle speed limit 25 MPH on Airport Way

5. Number of lanes Airport Way is a city street with two lanes approaching the intersection and a single lane leaving the intersection. SR 240 is a six lane state highway plus a turn lane in each direction.

6. Trucks (commercial vehicles) are what percent of average daily traffic 8%

7. Number of school buses over the crossing each day N/A

Section 5 – Railroad Traffic

1. Name of railroad(s) operating at crossing
Tri City Railroad

2. Type of railroad at crossing Common Carrier Logging Industrial
 Passenger Excursion

3. Type of tracks at crossing Main Line Siding or Spur

4. Number of tracks at crossing 1

5. Average daily train traffic, freight: 4 (increasing to 6 by 2016)
Authorized freight train speed 20 Operated freight train speed 10

6. Average daily train traffic, passenger 0
Authorized passenger train speed N/A Operated passenger train speed N/A

Section 6 – Current Warning Devices

1. Provide a complete description of the warning devices currently located at the crossing, including signs, gates, lights, train detection circuitry and any other warning devices.

Shoulder mounted flashing lights with gates

Section 7 – Description of Proposed Changes

1. Describe in detail the proposed changes, including train detection circuitry, sequencing and advanced preemption time, justification for the changes and its effects on current warning devices and warning times for drivers.


Install new eight wire preemption which will improve the communication between the train detection system and the WSDOT traffic signal, upgrade signals to LED. Upgrade track circuitry to support 8 wire system and additional preemption time needed.

WSDOT to improve right turn radius from SB 240 to Airport. Install R8-10 or R8-10a “Stop Here” signs and repaint road markings as appropriate.

All improvements funded under Section 130.

Section 8 – Illustration of Current and Proposed Layout

Attach a detailed diagram, drawing, map or other illustration showing the current and proposed layout of the road, crossing surface and railway in the vicinity of the crossing, including shoulders, sidewalks, lanes of travel, bike lanes, warning devices and any other applicable crossing conditions.



Section 9 – Traffic Signal Preemption

Complete the attached Guide for Determining Time Requirements for Traffic Signal Preemption at Highway-Rail Grade Crossings.

1. Specify simultaneous or advance preemption requested.

Advance preemption

If advance preemption, what is the preemption time.

43 seconds

Section 10 - Waiver of Hearing by Respondent

Waiver of Hearing

The undersigned represents the Respondent in the petition to install or modify an inter-tie between the highway signal and the railroad crossing signal system at the following crossing.

USDOT Crossing No. 310402M

We have investigated the conditions at the crossing. We are satisfied the conditions are the same as described by the Petitioner in this docket. We agree the inter-tie should be installed and consent to a decision by the commission without a hearing.

Dated at 10:40 AM, Washington, on the 3rd day of NOVEMBER, 2015.

JOHN J. MILLER

Printed name of Respondent

John J. Miller

Signature of Respondent's Representative

VICE PRESIDENT + CHIEF OPERATIONS OFFICER

Title

509-578-8557

MILLER@TCRY.COM

Phone number and e-mail address

TRI CITY RAILROAD

PO BOX 1700

RICHLAND, WA 99352


Mailing address



**Minnesota Department of Transportation
GUIDE FOR DETERMINING TIME REQUIREMENTS FOR
TRAFFIC SIGNAL PREEMPTION AT HIGHWAY-RAIL GRADE CROSSINGS**

City Richland, WA
 County _____
 District _____

Date 10/07/14
 Completed by Joe DeGroat
 District Approval _____



Parallel Street Name
SR240
 Crossing Street Name
Airport Way

Railroad Tri-City RR
 Crossing DOT# 310402M

Railroad Contact Rhett Peterson
 Phone (509) 371-0901

SECTION 1: RIGHT-OF-WAY TRANSFER TIME CALCULATION

Preempt verification and response time

- 1. Preempt delay time (seconds) 1.
- 2. Controller response time to preempt (seconds) 2.
- 3. Preempt verification and response time (seconds): add lines 1 and 2 3.

Remarks _____
 Controller type: _____

Worst-case conflicting vehicle time

- 4. Worst-case conflicting vehicle phase number 4.
- 5. Minimum green time during right-of-way transfer (seconds) 5.
- 6. Other green time during right-of-way transfer (seconds) 6.
- 7. Yellow change time (seconds) 7.
- 8. Red clearance time (seconds) 8.
- 9. Worst-case conflicting vehicle time (seconds): add lines 5 through 8 9.

Remarks _____

Worst-case conflicting pedestrian time


- 10. Worst-case conflicting pedestrian phase number 10.
- 11. Minimum walk time during right-of-way transfer (seconds) 11.
- 12. Pedestrian clearance time during right-of-way transfer (seconds) 12.
- 13. Vehicle yellow change time, if not included on line 12 (seconds) 13.
- 14. Vehicle red clearance time, if not included on line 12 (seconds) 14.
- 15. Worst-case conflicting pedestrian time (seconds): add lines 11 through 14 15.

Remarks _____

Worst-case conflicting vehicle or pedestrian time

- 16. Worst-case conflicting vehicle or pedestrian time (seconds): maximum of lines 9 and 15 16.
- 17. Right-of-way transfer time (seconds): add lines 3 and 16 17.

SECTION 2: QUEUE CLEARANCE TIME CALCULATION



		Remarks	
18. Clear storage distance (CSD, feet)	18. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">35</td></tr></table>	35	_____
35			
19. Minimum track clearance distance (MTCD, feet)	19. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">29</td></tr></table>	29	_____
29			
20. Design vehicle length (DVL, feet)	20. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">75</td></tr></table>	75	Design vehicle type: _____
75			
21. Queue start-up distance, L (feet): add lines 18 and 19	21. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">64</td></tr></table>	64	
64			
22. Time required for design vehicle to start moving (seconds): calculate as 2+(L+20)	22. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">5.2</td></tr></table>	5.2	Remarks
5.2			
23. Design vehicle clearance distance, DVCD (feet): add lines 19 and 20	23. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">104</td></tr></table>	104	
104			
24. Time for design vehicle to accelerate through the DVCD (seconds)	24. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">13.5</td></tr></table>	13.5	Read from Figure 2 in Instructions.
13.5			
25. Queue clearance time (seconds): add lines 22 and 24	25. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">18.7</td></tr></table>	18.7	
18.7			

SECTION 3: MAXIMUM PREEMPTION TIME CALCULATION

		Remarks	
26. Right-of-way transfer time (seconds): line 17	26. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">32.5</td></tr></table>	32.5	_____
32.5			
27. Queue clearance time (seconds): line 25	27. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">18.7</td></tr></table>	18.7	_____
18.7			
28. Desired minimum separation time (seconds)	28. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">4.0</td></tr></table>	4.0	_____
4.0			
29. Maximum preemption time (seconds): add lines 26 through 28	29. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">55.2</td></tr></table>	55.2	
55.2			

SECTION 4: SUFFICIENT WARNING TIME CHECK

		Remarks	
30. Required minimum time, MT (seconds): per regulations	30. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">20.0</td></tr></table>	20.0	_____
20.0			
31. Clearance time, CT (seconds): get from railroad	31. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">1.0</td></tr></table>	1.0	_____
1.0			
32. Minimum warning time, MWT (seconds): add lines 30 and 31	32. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">21.0</td></tr></table>	21.0	Excludes buffer time (BT)
21.0			
33. Advance preemption time, APT, if provided (seconds): get from railroad	33. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">0.0</td></tr></table>	0.0	_____
0.0			
34. Warning time provided by the railroad (seconds): add lines 32 and 33	34. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">21.0</td></tr></table>	21.0	
21.0			
35. Additional warning time required from railroad (seconds): subtract line 34 from line 29, round up to nearest full second, enter 0 if less than 0	35. <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td style="width: 40px; height: 20px; text-align: center;">35</td></tr></table>	35	
35			

If the additional warning time required (line 35) is greater than zero, additional warning time has to be requested from the railroad. Alternatively, the maximum preemption time (line 29) may be decreased after performing an engineering study to investigate the possibility of reducing the values on lines 1, 5, 6, 7, 8, 11, 12, 13 and 14.

Remarks: _____

SECTION 5: TRACK CLEARANCE GREEN TIME CALCULATION (OPTIONAL)**Preempt Trap Check**

36. Advance preemption time (APT) provided (seconds):	36.	43.0	Line 33 only valid if line 35 is zero.
37. Multiplier for maximum APT due to train handling	37.	1.25	See Instructions for details.
38. Maximum APT (seconds): multiply line 36 and 37	38.	53.8	Remarks
39. Minimum duration for the track clearance green interval (seconds)	39.	15.0	For zero advance preemption time
40. Gates down after start of preemption (seconds): add lines 38 and 39	40.	68.8	
41. Preempt verification and response time (seconds): line 3	41.	0.0	Remarks
42. Best-case conflicting vehicle or pedestrian time (seconds): usually 0	42.	0.0	
43. Minimum right-of-way transfer time (seconds): add lines 41 and 42	43.	0.0	
44. Minimum track clearance green time (seconds): subtract line 43 from line 40	44.	68.8	

Clearing of Clear Storage Distance

45. Time required for design vehicle to start moving (seconds), line 22	45.	5.2	
46. Design vehicle clearance distance (DVCD, feet), line 23	46.	104	Remarks
47. Portion of CSD to clear during track clearance phase (feet)	47.	35	CSD* in Figure 3 in Instructions.
48. Design vehicle relocation distance (DVRD, feet): add lines 46 and 47	48.	139	
49. Time required for design vehicle to accelerate through DVRD (seconds)	49.	16.0	Read from Figure 2 in Instructions.
50. Time to clear portion of clear storage distance (seconds): add lines 45 and 49	50.	21.2	
51. Track clearance green interval (seconds): maximum of lines 44 and 50, round up to nearest full second	51.	69	

SECTION 6: VEHICLE-GATE INTERACTION CHECK (OPTIONAL)

52. Right-of-way transfer time (seconds): line 17	52.	32.5	
53. Time required for design vehicle to start moving (seconds), line 22	53.	5.2	
54. Time required for design vehicle to accelerate through DVL (on line 20, seconds)	54.	11.7	Read from Table 3 in Instructions.
55. Time required for design vehicle to clear descending gate (seconds): add lines 52 through 54	55.	49.4	Remarks
56. Duration of flashing lights before gate descent start (seconds): get from railroad	56.	3.0	Remarks
57. Full gate descent time (seconds): get from railroad	57.	12.0	
58. Proportion of non-interaction gate descent time	58.	0.30	Read from Figure 5 in Instructions.
59. Non-interaction gate descent time (seconds): multiply lines 57 and 58	59.	3.6	
60. Time available for design vehicle to clear descending gate (seconds): add lines 56 and 59	60.	6.6	
61. Advance preemption time (APT) required to avoid design vehicle-gate interaction (seconds): subtract line 60 from line 55, round up to nearest full second, enter 0 if less than 0	61.	43	