



WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

Clark County Public Works,

Petitioner,

vs.

Portland Vancouver Junction Railroad

Respondent

DOCKET NO. TR-

PETITION TO MODIFY WARNING DEVICES AT A HIGHWAY-RAILROAD GRADE CROSSING

USDOT: 852-436D

The Petitioner asks the Washington Utilities and Transportation Commission to approve modification of warning devices at a highway-rail grade crossing.

Section 1 – Petitioner’s Information

Clark County – Public Works Department

Petitioner

*Robin A Washington*

Signature

1300 Franklin Street

Street Address

Vancouver, WA 98666

City, State and Zip Code

PO Box 9810 – Vancouver, WA 98666-9810

Mailing Address, if different than the street address

Robin Washington

Contact Person Name & Signature

564.397.4572 Robin.Washington@clark.wa.gov

Contact Phone Number and Email Address

***Section 2 – Respondent’s Information***

<u>Portland Vancouver Junction Railroad</u> Respondent
<u>1300 Franklin Street</u> Street Address
<u>Vancouver, WA 98666</u> City, State and Zip Code
<u>PO Box 9810, Vancouver, WA</u> Mailing Address, if different than the street address
<u>Greg Shafer</u> Contact Person Name
<u>564.397.4064 - <a href="mailto:Greg.Shafer@clark.wa.gov">Greg.Shafer@clark.wa.gov</a></u> Contact Phone Number and Email Address

***Section 3 – Crossing Location***

1. Existing highway/roadway <u>NE 119<sup>th</sup> Street</u>
2. Existing railroad <u>Portland Vancouver Junction Railroad</u>
3. USDOT Crossing No. <u>852-436D</u>
4. GPS location <u>Latitude 45.707811; Longitude -122.570418</u>
5. Railroad mile post (nearest tenth) <u>7.60</u>
6. City <u>Vancouver</u> County <u>Clark County Washington</u>

*Section 4 – Vehicle Traffic*

1. Name of highway NE 119<sup>th</sup> Street

2. Road authority Clark County

3. Average annual daily traffic (AADT) 12,809 (2017)

4. Number of lanes two

5. Roadway speed 45 MPH Posted

6. Is the crossing part of an established truck route? Yes X No \_\_\_\_\_

7. If so, trucks are what percent of total daily traffic? 10%

8. Is the crossing part of an established school bus route? Yes X No \_\_\_\_\_

9. If so, how many school buses travel over the crossing each day? 70 buses

10. Describe any changes to the information in 1 through 7, above, expected within ten years:

This roadway section is a Clark County Public Works, Capital project. Construction is starting this summer (2018).

This roadway will be widening from two lanes to four travel-lanes, center turn-lane, sidewalks and bike-lanes.

*Section 5 – Current Crossing Information*

1. Railroad company Portland Vancouver Junction Railroad

2. Type of railroad at crossing     Common Carrier         Logging         Industrial  
 Passenger                     Excursion

3. Type of tracks at crossing     Main Line         Siding or Spur

4. Number of tracks at crossing    one

5. Average daily train traffic, freight twice weekly

Authorized freight train speed 10mph    Operated freight train speed 10mph

6. Average daily train traffic, passenger -0-

Authorized passenger train speed N/A    Operated passenger train speed N/A

7. Describe any changes to the information in 1 through 4, above, expected within ten years:

None

8. What is the available sight distance from the stop bar (or 25 feet from the tracks if no stop bar) on both approaches to the crossing?

The roadway is being widened. Sightlines for the widened crossing are not known

9. If the sight distance is less than 400 feet, describe the structures, roadway or track curvature, visual obstacles or other characteristics that limit sight distance.

Vegetation, dips in roadway and rail line curve limit sightlines



## *Section 6 – Current Warning Devices*

Provide a complete description of the warning devices currently located at the crossing (vehicle and pedestrian), including signs, gates, lights, train detection circuitry and any other warning devices.

Style-C track circuits, flasher signals with gates arms, bells and crossbucks.

## *Section 7 – Description of Proposed Changes*

Describe in detail the number and type of proposed automatic signals (vehicle and pedestrian), gates or other warning devices, including proposed circuitry. If sidewalks are being installed, please provide information on who will maintain them.

**Two each Flasher/Gate/Cantilever combo with flashing lights and bells, the gate arms 35' – 0", Cantilevers mast 30' – 0"** (Sheet RR15 (136 of 167))

**New crossing surface:** width will be 121'-10.5". The crossing will be extended (5) panels in each direction. Sheet RRCD (120 of 167)

**Center Island Medians:** Two medians will be installed, 95' long (west side) and 150' long (east side) by 10' wide and 6' high with RPMS. See TYP 2 (74 of 232), SSD13 (78 of 167) and M1 (99 of 232)

Guardrail will be installed to protect the signals.

**Bungalow:** The existing rail bungalow is being relocated and retrofitted. Connections to the County ITS system are being provided. Sheets RRS1 to RRS15 (122 of 167 to 136 of 167) for detailed information on the wiring.

**Pedestrian walkway/sidewalks** – Four Flashers only (no gates) and detectable warning surface will be installed. No stop bars for pedestrians nor cyclist. See RR1 (96 of 232, 97 of 232). The sidewalks will be maintained by Clark County.

**Pavement markings and warning signs,** Bicycles use caution, crossing marking, Sheet SSIN5 (92 of 167) There is not a "slow speed sign" listed.

## *Section 8 – Illustration of Proposed Warning Devices*

Attach a detailed design diagram, drawing, map or other illustration showing all proposed modifications, including signals, signage, pavement markings, sidewalks, etc.

See Attached "Railroad Signaling" Sheet 1 of 15 also "HDR CCCP Diagnostic Report".

Section 9 – Waiver of Hearing by Respondent

**Waiver of Hearing**

The undersigned represents the Respondent in the petition to modify highway-rail grade crossing warning signals at the following crossing.

USDOT Crossing No. 852-436D

We have investigated the conditions at the crossing. We are satisfied the conditions are the same as described by the Petitioner in this docket. We agree the warning signals should be modified and consent to a decision by the commission without a hearing.

Dated at Vancouver, Washington, on the 12<sup>TH</sup> day of July, 2018.

Gregory A. Staker

Printed name of Respondent

Gregory A. Staker for Jerry Barnett  
Signature of Respondent's Representative

Development Engineering Manager for  
Title RR Coordinator


(360) 397-6118 (x-4000) greg.staker@clackwa.wa.gov  
Phone number and e-mail address

1300 Franklin St.

Vancouver, WA 98666  
Mailing address

**GENERAL NOTES:**


1. ALL SURFACING AND PAVING DEPTHS SHOWN ARE COMPACTED DEPTHS. SEE SPECIFICATIONS FOR MAXIMUM LIFT DEPTHS.
2. SEE ROADWAY PLAN AND PROFILE SHEETS FOR VARIABLE WIDTHS.
3. SEE SHEET TYP4 FOR CSBC EXTENSION AND TYPICAL SLOPE GRADING DETAILS.



\* SEE BIORETENTION CELL PLANS FOR LOCATIONS OF BIORETENTION CELLS.  
 \*\*\* SEE ROADWAY PLANS FOR LOCATIONS.  
 # SEE PP6 AND PP7 FOR EOP PROFILES.

NE 119TH STREET  
 STA 219+00.00 TO 223+60.00 LT  
 STA 220+00.00 TO 222+00.00 RT

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 1 CRP #342422  
 TYPICAL SECTIONS  
 SHEET 2 OF 4


DATE 04/12/18  
 TYP2  
 74 OF 232

DELINEATION FOR MEDIAN CURB AND CENTER MEDIAN ISLAND


NOTES:

1. ALL MEDIAN CURB SHALL BE PAINTED AS SPECIFIED IN SECTION B-07.3(2) OF THE WSDOT STANDARD SPECIFICATIONS.


2YY RPM'S NEXT TO MEDIAN CURB





TUBULAR MARKER AND 2YY ARRAY AT END OF CONCRETE MEDIAN DETAIL



TUBULAR MARKER AND 2W ARRAY AT END OF CONCRETE MEDIAN DETAIL



CENTER MEDIAN ISLAND WITH 2YY RPM'S AND STRIPING DETAIL



TUBULAR MARKER SHALL MEET THE REQUIREMENTS OF WSDOT STANDARD SPECIFICATIONS 1-10.3(3)H AND 9-35.10.

DETAIL 1

REV. NO.	DATE	BY	APPR
1	05/16/17	MG	HH

DWG:



Department of Public Works  
**CLARK COUNTY**  
 WASHINGTON  
 proud past. promising future

DELINEATION FOR MEDIAN CURB AND CENTER MEDIAN ISLAND

APPROVED

09/20/16  
 DATE

COUNTY ENGINEER

STANDARD  
**T12.0**  
 DETAIL  
 DESIGNED  
 DRAWN  
 DATE

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



TRANSPORTATION PROGRAM

PUBLIC WORKS  
 ENGINEERING & CONSTRUCTION DIVISION

ENGINEERING AND DESIGN SECTION




NE 119TH STREET EAST - VOLUME 2 CRP #342422

SIGNING AND STRIPING DETAILS  
 SHEET 13 OF 13


DATE 04/12/18

SSD13

78 OF 167



- CONSTRUCTION NOTES**
- ② GRADING LIMITS
  - ③ CONSTRUCT ROADWAY. SEE TYPICAL SECTIONS ON SHEETS TYP(x)
  - ⑥ CONSTRUCT CEMENT CONCRETE TRAFFIC CURB AND GUTTER PER DETAIL ON SHEETS RD(x)
  - ⑦ CONSTRUCT CEMENT CONCRETE SIDEWALK PER DETAIL ON SHEETS RD(x)
  - ⑪ CONSTRUCT DRIVEWAY PER DRIVEWAY PLAN AND PROFILE SHEETS DWY(x). SEE PLAN FOR DRIVEWAY NUMBER
  - ⑬ INSTALL FENCE OF TYPE NOTED PER DETAIL ON SHEETS RD(x)
  - ⑭ INSTALL BEAM GUARDRAIL TYPE 31 PER DETAIL ON SHEETS GD(x)
  - ⑮ INSTALL BEAM GUARDRAIL TYPE 31 NON-FLARED TERMINAL PER DETAIL ON SHEETS GD(x)
  - ⑯ INSTALL BEAM GUARDRAIL TRANSITION SECTION TYPE 21 PER DETAIL ON SHEETS GD(x)
  - ⑰ INSTALL TEMPORARY FENCE, TYPE AND LOCATIONS SHOWN ON THE PLANS, PER DETAIL ON SHEETS RD(x)
  - ⑱ INSTALL BEAM GUARDRAIL ANCHOR TYPE 10 (THREE BEAM), PER DETAIL ON SHEETS GD(x)
  - ⑳ INSTALL MAILBOX ON SUPPORT OF TYPE NOTED PER DETAIL ON SHEETS RD(x)



Sidewalk Staking

PNT	STA/OFF	DESC
S22	218+24.00, 45.50L	BEGIN TAPER, R=15'
S23	218+42.00, 39.50L	END TAPER
S24	220+12.27, 39.50L	BEGIN TAPER, R=15'
S25	220+27.23, 35.50L	END TAPER

Ditch Staking

PNT	STA/OFF	DESC
D2	219+40.00, 55.00L	END DITCH

Fence Staking

PNT	STA/OFF	DESC
F11	218+50.00, 70.00L	ANGLE POINT
F12	219+77.06, 69.73L	END FENCE
F13	222+12.89, 70.00L	BEGIN FENCE

- FULL DEPTH CONSTRUCTION
- CEMENT CONCRETE
- HMA DRIVEWAY

NE 119TH STREET EAST - VOLUME 1 CRP #342422

**ROADWAY PLAN & PROFILES**  
STA 218+00 TO STA 223+00

CALL 48 HOURS BEFORE YOU DIG

1-800-424-5555

"It's the Law"

NORTHWEST UTILITIES NOTIFICATION CENTER

CLARK COUNTY, WASHINGTON

**TRANSPORTATION PROGRAM**

**PUBLIC WORKS**

ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**

MARC E. HARRIS  
STATE OF WASHINGTON  
REGISTERED PROFESSIONAL ENGINEER


DATE 04/12/18

PP6

83 OF 232


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE






**NOTES:**

- SEE RAILROAD SIGNAL PLANS RRS1 THROUGH RRS15 FOR DETAILS ON RAILROAD CROSSING SIGNING.




LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
 SIGNING AND STRIPING INSTALL  
 STA 213+00 TO STA 223+00

DATE 04/12/18  
 SSIN5  
 92 OF 167



SEE SHEET RR3 FOR RAILROAD CROSSING AND SIDEWALK GRADING NORTH SIDE

119290015  
ROOD EUNICE M TRUSTEE

NE 119TH STREET

199658000  
BRODERSON IVARD


199624000  
COLLINS CHRIS

SEE SHEET RR2 FOR RAILROAD CROSSING AND SIDEWALK GRADING SOUTH SIDE

**GENERAL NOTES**

1. SEE RAILROAD CROSSING, RAILROAD SIGNALING, AND INTELLIGENT TRANSPORTATION SYSTEM SHEETS FOR DETAILS.


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 1 CRP #342422  
**RAILROAD CROSSING SHEET LAYOUT**

DATE 04/12/18  
RR1  
96 OF 232





STA 220+20.00, 39.50' RT  
 N=143462.741  
 E=1111420.889  
 EL= 235.74

NE 119TH STREET

STA 220+84.81, 44.67' RT  
 N=143456.411  
 E=1111485.596  
 EL= 235.31

STA 220+90.14, 47.43' RT  
 N=143453.557  
 E=1111490.874  
 EL= 235.31  
 MATCH TRACK PANEL ELEVATION

STA 220+83.51, 44.00' RT  
 N=143457.106  
 E=1111484.311  
 EL= 235.31

STA 220+60.00, 44.00' RT  
 N=143457.526  
 E=1111460.803  
 EL= 235.33

STA 220+60.00, 50.00' RT  
 N=143451.527  
 E=1111460.695  
 EL= 235.42

STA 220+82.05, 50.00' RT  
 N=143451.133  
 E=1111482.743  
 EL= 235.17

STA 220+87.38, 52.76' RT  
 N=143448.279  
 E=1111488.021  
 EL= 235.17  
 MATCH TRACK PANEL ELEVATION

STA 220+99.02, 52.03' RT  
 N=143448.802  
 E=1111499.671  
 EL= 235.31  
 MATCH TRACK PANEL ELEVATION

STA 221+50.00, 45.50' RT  
 N=143454.417  
 E=1111550.761  
 EL= 236.67

STA 221+46.11, 46.01' RT  
 N=143453.974  
 E=1111546.864  
 EL= 236.53

STA 221+04.35, 54.79' RT  
 N=143445.948  
 E=1111504.949  
 EL= 235.31

STA 221+10.82, 55.49' RT  
 N=143445.133  
 E=1111511.407  
 EL= 235.31

STA 221+50.00, 51.50' RT  
 N=143448.418  
 E=1111550.654  
 EL= 236.76


STA 221+47.67, 51.81' RT  
 N=143448.152  
 E=1111548.316  
 EL= 236.67

STA 221+01.59, 60.11' RT  
 N=143440.670  
 E=1111502.096  
 EL= 235.18

STA 220+96.26, 57.36' RT  
 N=143443.524  
 E=1111496.817  
 EL= 235.18  
 MATCH TRACK PANEL ELEVATION

**CONSTRUCTION NOTES**

- ① TRANSITION CURB HEIGHT FROM 6 INCHES TO 0 INCHES IN 6 FEET TO MATCH TRACK PANEL ELEVATION
- ② INSTALL DETECTABLE WARNING SURFACE PER PLAN AND DETAIL ON ROADWAY DETAIL SHEET RD(x)



LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



TRANSPORTATION PROGRAM

**PUBLIC WORKS**  
 ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**





NE 119TH STREET EAST - VOLUME 1 CRP #342422  
**RAILROAD CROSSING SOUTH SIDE**

DATE 04/12/18  
 RR2  
 97 OF 232

**CONSTRUCTION NOTES**

- ① TRANSITION CURB HEIGHT FROM 6 INCHES TO 0 INCHES IN 6 FEET TO MATCH TRACK PANEL ELEVATION
- ② INSTALL DETECTABLE WARNING SURFACE PER PLAN AND DETAIL ON ROADWAY DETAIL SHEET RD(x)




119320000  
THOMAS KENNETH

119290015  
ROOD EUNICE M  
TRUSTEE


NE 119TH STREET

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE




NE 119TH STREET EAST - VOLUME 1 CRP #342422  
**RAILROAD CROSSING  
NORTH SIDE**

DATE 04/12/18  
RR3  
98 OF 232



- NOTES:**
1. ALL POINTS ARE TOP FACE OF CURB (TFC).
  2. SEE TYPICAL SECTION SHEETS FOR MEDIAN SECTIONS.




LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



TRANSPORTATION PROGRAM

**PUBLIC WORKS**  
ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**




NE 119TH STREET EAST - VOLUME 1 CRP #342422  
**MEDIAN CURBING RAILROAD CROSSING**

DATE 04/12/18  
M1  
99 OF 232



**LEGEND**

- PANELS TO BE REMOVED FOR REINSTALLATION
- GAGE PANELS TO REMAIN. PROTECT IN PLACE
- RIGHT-OF-WAY



LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE




**TRANSPORTATION PROGRAM**

**PUBLIC WORKS**  
ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**

NE 119TH STREET EAST - VOLUME 2 CRP #342422  
**EXISTING CONDITIONS - RAIL**  
SHEET 1 OF 1

DATE 02/07/18  
XCR  
119 OF 167




**LEGEND**

- RAIL CROSSING LIGHT ARM
- RAIL CROSSING GATE
- PED SIGNAL
- RIGHT-OF-WAY
- NEW PANEL
- REINSTALLED PANEL
- RAIL ROAD TIE
- EXISTING PANEL TO REMAIN

**NOTES:**

1. FIELD VERIFY LOCATION PRIOR TO PLACEMENT.
2. SEE STORMWATER, WATER, AND LIGHTING PLANS FOR NEW UTILITY CASINGS. NEW CASING SHALL BE INSTALLED IN ACCORDANCE WITH CLARK COUNTY STANDARD SPECIFICATIONS FOR UNDERGROUND CROSSING OF RAILROAD RIGHT OF WAY AND THE PROJECT PLANS AND SPECIFICATIONS.




LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE




NE 119TH STREET EAST - VOLUME 2 CRP #342422  
**RAILROAD CROSSING PLAN**  
 SHEET 1 OF 1

DATE 02/07/18  
 RRCD  
 120 OF 167




TYPICAL CONCRETE CROSSING TRACK SECTION  
NTS

1



DETAIL: BUNGALOW SECTION  
NTS

2



RAIL BUNGALOW PAD  
NTS

3

NOTES:  
1. RE-GRADING PLAN FOR EXISTING GROUND ELEVATION.

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



TRANSPORTATION PROGRAM

PUBLIC WORKS  
ENGINEERING & CONSTRUCTION DIVISION


ENGINEERING AND DESIGN SECTION

NE 119TH STREET EAST - VOLUME 2 CRP #342422  
TYPICAL TRACK DETAILS AND SITE GRADING  
SHEET 1 OF 1

DATE 02/07/18  
RRTD  
121 OF 167



M:\VISIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_001.dwg  
 January 29, 2018 4:20 PM  
 BRAD FEWELL



**CONSTRUCTION NOTES:**

1. APPROACHES TO BE DOUBLE-BONDED. EXISTING BONDS MAY BE REUSED, HOWEVER, THE OWNER SHALL MAKE THE FINAL DETERMINATION OF A BOND'S SUITABILITY FOR USE.
2. RELOCATE EXISTING 4'X6' SIGNAL HOUSE. REUSE EXISTING ELECTRONICS. PROVIDE AND INSTALL NEW U.G. CABLE AND TRACK WIRES. PROVIDE AND INSTALL ALL NEW GATE/CANT. COMBO'S INCLUDING NEW LED LIGHT HEADS, GATE MECH'S AND GATE ARMS.
3. PROVIDE AND INSTALL X-LINK RECORDER IN SIGNAL HOUSE AND INTERFACE TO CLARK COUNTY ITS CABINET.
4. EXISTING INSULATED JOINTS TO BE TESTED. JOINTS PASSING TESTING MAY BE REUSED SUBJECT TO THE APPROVAL OF THE OWNER.
5. REPLACE XB BATTERY WITH 7EA. GNB ABSOLYTE 50G27 680 AH.
6. PROVIDE AND INSTALL LARRY MCGEE DTMF CONTROLLER AND EXTERNAL ANTENNA.
7. STICK TIMES = 15 MINUTES.
8. ALL CROSSING LAMPS, INCLUDING GATE ARM LAMPS, TO BE LED.
9. REFERENCE ITS PLANS FOR INSTALLATION OF X-LINK CAMERAS.
10. DIMENSIONS TO CROSSING SIGNALS FROM CENTERLINE OF TRACK TO CENTER OF MAST, AND FROM EDGE OF PAVEMENT TO CENTER OF MAST.



**LEGEND:**

- = TEST LINK
  - = HEAVY DUTY LIGHTNING ARRESTER
  - = HEAVY DUTY EQUALIZER
  - = TWISTED 2 TURNS PER FOOT.
  - = BELL
  - = INSULATED NUT.
  - = GUARDRAIL
- ALL WIRING #16 AWG UNLESS OTHERWISE NOTED. ALL SHEETS.

**NOT TO SCALE**

APPROACH AND WARNING TIME CALCULATION	TRACK 1
MINIMUM WARNING TIME	25 SEC
PLUS CLEARANCE TIME	3 SEC
PLUS ADDITIONAL GATE DELAY	0 SEC
PLUS BUFFER TIME	5 SEC
<b>TOTAL WARNING TIME</b>	<b>31 SEC</b>
<b>TOTAL APPROACH TIME</b>	<b>31 SEC</b>
MAXIMUM TRAIN SPEED	10 MPH
TIMES RATIO OF FT/SEC TO MPH	1.4667
<b>TOTAL APPROACH DISTANCE</b>	<b>485 FT.</b>

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE




NE 119TH STREET EAST - VOLUME 2 CRP #342422  
**RAILROAD SIGNALING**  
 SHEET 1 OF 15

DATE 06/30/16  
**RRS1**  
 122 OF 167



M:\ISIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_002.dwg  
 BRAD FEWELL  
 January 29, 2018 4:20 PM




NOTES:  
 1. ALL WIRING #16 UNLESS NOTED OTHERWISE.

REV 1  
 ISIS/REB  
 RED=IN/INSTALL  
 YELLOW=OUT/REMOVE



ORIGINALLY PRINTED  
 IN COLOR

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
 RAILROAD SIGNALING  
 SHEET 2 OF 15

DATE 06/30/16  
 RRS2  
 123 OF 167



6 PORT INDUSTRIAL POE UNMANAGED ETHERNET SWITCH

Specifications	
<b>Technology</b>	
<b>Standards</b>	IEEE802.3 10BaseT Ethernet IEEE802.3u 100BaseTX Fast Ethernet IEEE802.3x Flow Control and Back-Pressure IEEE802.3at Power over Ethernet
<b>Processing Type</b>	Store and Forward
<b>Protocol</b>	CSMA/CD
<b>Flow Control</b>	IEEE 802.3x flow control, back pressure flow control
<b>Switch Properties</b>	
<b>Switch Architecture</b>	Back-Plane (Switching Fabric): 1.0Gbps Packet Throughput Ability (Full-Duplex): 1,488Mpps @ 64bytes
<b>Transfer Rate</b>	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port
<b>MAC Table Size</b>	2K
<b>Interface</b>	
<b>RJ45 Ports</b>	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
<b>PoE Pin Out</b>	IEEE802.3u (PoE+) = 1+4D+/00T+ V+, V-, V+, V- for pin 1, 2, 3, 6 (Erdspan, MDI-X Alternative A)
<b>Fiber Port</b>	2*10GFX SFP/SFP+ type connector Multi-mode (2Km) - 50/25um ~ 62.5/125um Single-mode (30km) - 9/125um ~ 13/125um
<b>Wavelength</b>	1310nm (Multi-mode and Single-mode)
<b>Power Requirements</b>	
<b>Input Voltage</b>	48-55VDC Redundant Input
<b>Overload Current Protection</b>	Slow-Blow Fuse
<b>Connection</b>	1 removable 4-contact terminal block
<b>Reverse Polarity Protection</b>	Yes
<b>PoE Power Output</b>	25W @ 48VDC (per PoE port); 30W @ 51-55VDC per PoE port
<b>Power Consumption</b>	110 Watts @ 48VDC; 130 Watts @ 51-55VDC
<b>Mechanical Characteristics</b>	
<b>Housing</b>	Metal IP30 protection
<b>Dimensions</b>	30 x 142 x 99 mm (1.18 x 5.59 x 3.90 in.)
<b>Weight</b>	Unit Weight: 1.1 lbs. Shipping Weight: 1.45 lbs
<b>Mounting</b>	DIN-Rail mounting, wall mounting (optional)
<b>Environmental Limits</b>	
<b>Operating Temperature</b>	STD: -10° to 70° C (14° to 158° F); EOT: 40° to 75° C (-40° to 167° F)
<b>Storage Temperature</b>	-40° C ~ 85° C (-41° F ~ 185° F)
<b>Ambient Relative Humidity</b>	5 to 95%, (non-condensing)
<b>Regulatory Approvals</b>	
<b>EMI</b>	FCC Class A
<b>ERS</b>	EN6100-4-2; EN6100-4-3; EN6101-4-4; EN6100-4-5; EN6100-4-6; EN6101-4-8 EN6100-6-2; EN6100-4-4
<b>Free Fall</b>	IEC60088-2-32
<b>Shock</b>	IEC60088-2-27
<b>Vibration</b>	IEC60088-2-6
<b>Green</b>	RoHS Compliant
<b>Certifications</b>	FCC, CE, UL508
<b>Warranty</b>	5 Years

- NOTES:
- 1) ALL WIRING ON THIS SHEET TO BE #16 AWG UNLESS OTHERWISE NOTED.
  - 2) ITS TO PROVIDE VOLTAGE CONVERTER WITH ISOLATED OUTPUT TO ASSURE THAT X-LINK CAMERAS AND RELATED EQUIPMENT DO NOT PLACE A GROUND ON SIGNAL BATTERIES.

Z:\GIS\CADD\Washington State RR\MP 07-60\_NE\_119th St\0760\_003.dwg  
ERICA ZELLER February 2, 2018 2:09 PM


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
RAILROAD SIGNALING  
SHEET 3 OF 15

DATE 06/30/16  
RRS3  
124 OF 167

TRAIN TENNA VERTICAL  
OUTDOOR BASE ANTENNA  
(MOUNT TO EXTERIOR OF BUNGALOW)



**\*WARNING\***  
PLACING CROSSING OVERRIDE  
SWITCH IN THE OVERRIDE  
POSITION COMPLETELY  
DISABLES THIS HIGHWAY  
CROSSING WARNING  
SYSTEM. PROPER  
AUTHORITIES MUST  
BE NOTIFIED PRIOR  
TO OVERRIDE.

**NOTES:**  
1. ALL WIRING #16 UNLESS NOTED  
OTHERWISE.

REV 1  
ISIS/REB  
RED=IN/INSTALL  
YELLOW=OUT/REMOVE

**ORIGINALLY PRINTED  
IN COLOR**

M:\ISIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_004.dwg  
BRAD FEWELL  
January 29, 2018 4:20 PM


LOCATIONS OF EXISTING UTILITIES ARE  
APPROXIMATE AND MAY BE INCOMPLETE




NE 119TH STREET EAST - VOLUME 2 CRP #342422  
**RAILROAD SIGNALING**  
SHEET 4 OF 15

DATE 06/30/16  
**RRS4**  
125 OF 167


M:\VIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_005.dwg  
BRAD FEWELL  
January 29, 2018 4:20 PM



CONNECTS TO PED #1 SHT. 9  
CONNECTS TO SIGNAL #1 SHT. 8



CONNECTS TO PED #2 SHT. 9  
CONNECTS TO SIGNAL #2 SHT. 8



REV 1  
ISIS/REB  
RED=IN/INSTALL  
YELLOW=OUT/REMOVE

ORIGINALLY PRINTED IN COLOR


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE




NE 119TH STREET EAST - VOLUME 2 CRP #342422  
RAILROAD SIGNALING  
SHEET 5 OF 15

DATE 06/30/16  
RRS5  
126 OF 167


M:\ISS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_006.dwg  
 BRAD FEWELL  
 January 29, 2018 4:21 PM



CONNECTS TO  
 GATE #1  
 SHT. 7



CONNECTS TO  
 GATE #2  
 SHT. 7



X = INTERNAL GATE WIRES THAT SHARE ELECTRICAL CONNECTIONS WITH OTHER WIRES THAT ARE ASSIGNED THE SAME NUMBER.

ORIGINALLY PRINTED  
 IN COLOR

REV 1  
 ISIS/REB  
 RED=IN/INSTALL  
 YELLOW=OUT/REMOVE

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422


RAILROAD SIGNALING  
 SHEET 6 OF 15

DATE 06/30/16

RRS6


127 OF 167

M:\VISIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_007.dwg  
 January 29, 2018 4:21 PM  
 BRAD FEWELL



CONNECTS TO GATE CIRCUITS SHT. 6

CONNECTS TO GATE CIRCUITS SHT. 6



CIRCUIT CONTROLLER ADJUSTMENT		
CONTACT	CLOSED	FUNCTION
1 FRONT	0°-89°	MOTOR UP CONTROL
2		
3	46°-93°	MOTOR DN
4	5°-93°	BELL
5	0°-5°	GATE DN IND.
6	83°-90°	FLASHING LIGHT

NOTES:


- 1.) ALL WIRING TO BE #10 AWG UNLESS OTHERWISE NOTED.
- 2.) TO ENABLE BELL WITH GATE DOWN STRAP BETWEEN BELL AND BELL1 TERMINALS IN CANTILEVER JCT. BOXES.

REV 1  
 ISIS/REB  
 RED=IN/INSTALL  
 YELLOW=OUT/REMOVE

ORIGINALLY PRINTED IN COLOR

NEW SHEET

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422



RAILROAD SIGNALING  
 SHEET 7 OF 15

DATE 06/30/16


RRS7

128 OF 167


M:\VIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_008.dwg  
 January 29, 2018 4:21 PM  
 BRAD FEWELL



SIGNAL #1





SIGNAL #2



**NOTES:**

1. GETS-GS P/N 07G045-300.
2. (M) = LED SIGNAL LAMP WITH 8.5 TO 16 VOLT WORKING VOLTAGE.

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422

RAILROAD SIGNALING  
 SHEET 8 OF 15

DATE 06/30/16



RRS8

129 OF 167

NEW SHEET



M:\VIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_009.dwg  
BRAD FEWELL  
January 29, 2018 4:21 PM



NOTES:  
1. = LED SIGNAL LAMP WITH 8.5 TO 16 VOLT WORKING VOLTAGE.


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
RAILROAD SIGNALING  
SHEET 9 OF 15

NEW SHEET  
DATE 06/30/16  
RRS9  
130 OF 167


M:\VIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_010.dwg  
BRAD FEWELL  
January 29, 2018 4:21 PM




NOTES:

- MINIMUM WIRE SIZE  
15 AMP - NO. 14 AWG THHN OR THWN SOLID  
20 AMP - NO. 12 AWG THHN OR THWN SOLID  
30 AMP - NO. 10 AWG THHN OR THWN SOLID
- GROUND FAULT INTERRUPT (GFCI)  
MUST BE USED ON ALL CIRCUITS SERVING  
CONVENIENCE OUTLETS AND ANY EQUIPMENT  
OUTSIDE THE BUNGALOW. RECEPTACLE MOUNTED  
GFCI MAY BE USED INSTEAD OF BREAKER TYPE.

SIDE B



LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422

RAILROAD SIGNALING  
SHEET 10 OF 15



DATE 06/30/16

RRS10

131 OF 167

M:\ISIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_011.dwg  
 BRAD FEWELL  
 January 29, 2018 4:21 PM

REV 1  
 ISIS/REB  
 RED=IN/INSTALL  
 YELLOW=OUT/REMOVE



ORIGINALLY PRINTED  
 IN COLOR

LOCATIONS OF EXISTING UTILITIES ARE  
 APPROXIMATE AND MAY BE INCOMPLETE



TRANSPORTATION  
 PROGRAM


PUBLIC  
 WORKS  
 ENGINEERING &  
 CONSTRUCTION  
 DIVISION



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
 RAILROAD SIGNALING  
 SHEET 11 OF 15

DATE 06/30/16  
 RRS11  
 132 OF 167

M:\VIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_012.dwg  
 January 29, 2018 4:21 PM  
 BRAD FEWELL



REV 1  
 ISIS/REB  
 RED=IN/INSTALL

**ORIGINALLY PRINTED  
 IN COLOR**

LOCATIONS OF EXISTING UTILITIES ARE  
 APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422


**RAILROAD SIGNALING  
 SHEET 12 OF 15**

DATE 06/30/16

**RRS12**

133 OF 167


M:\ISIS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_013.dwg  
 January 29, 2018 4:21 PM  
 BRAD FEWELL



REV 1  
 ISIS/REB  
 RED=IN/INSTALL  
 YELLOW=OUT/REMOVE

ORIGINALLY PRINTED  
 IN COLOR

LOCATIONS OF EXISTING UTILITIES ARE  
 APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422


RAILROAD SIGNALING  
 SHEET 13 OF 15

DATE 06/30/16

RRS13

134 OF 167

M:\ISS CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_014.dwg  
 January 29, 2018 4:21 PM  
 BRAD FEWELL



LEGEND:  
 - - - - UNDERGROUND CABLE  
 □ - X-LINK CAMERA

REV 1  
 ISIS/REB  
 RED=IN/INSTALL  
 YELLOW=OUT/REMOVE

ORIGINALLY PRINTED  
 IN COLOR

LOCATIONS OF EXISTING UTILITIES ARE  
 APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
 RAILROAD SIGNALING  
 SHEET 14 OF 15

DATE 06/30/16  
 RRS14  
 135 OF 167


**TORQUE VALUES**

TORQUE VALUES FOR 18-8 S/S HARDWARE WITHOUT ANTI-SEIZE COMPOUND.

1. 3/8"-16 BOLTS: 236 IN. LBS.
2. 1/2"-13 BOLTS: 517 IN. LBS.
3. 5/8"-11 BOLTS: 1110 IN. LBS.
4. 1"-8 BOLTS: 3440 IN. LBS.



TORQUE VALUES FOR 18-8 S/S HARDWARE WITH ANTI-SEIZE COMPOUND.

1. 3/8"-16 BOLTS: 201 IN. LBS.
2. 1/2"-13 BOLTS: 439 IN. LBS.
3. 5/8"-11 BOLTS: 944 IN. LBS.
4. 1"-8 BOLTS: 2924 IN. LBS.



**FEATURES :**

- STRUCTURE MEETS AAR, AREMA AND AASHTO RECOMMENDED DESIGN CRITERIA
- ALUMINUM CONSTRUCTION 6061-T6
- 3/4" THK. x 17" WD. SLOTTED WALKWAY BAR GRATING
- HANDRAIL 39" HIGH WITH INTERMEDIATE HANDRAIL AT 18"
- 17'-6" ROAD CLEARANCE
- SIGN MOUNTING BRACKETS WELDED TO THE STRUCTURE
- 12" LED FLASHING LIGHT CAN BE FURNISHED
- REMOVABLE LADDER GUARD
- 12" SINGLE PIPE MAST WILL BE SUPPLIED WITH 10'-0" TO 22'-0" ARM
- 12" PIPE MAST WILL BE SUPPLIED WITH 24'-0" TO 30'-0" ARM



**NEW SHEET**

NE 119TH STREET EAST - VOLUME 2 CRP #342422

**RAILROAD SIGNALING**  
SHEET 15 OF 15

DATE 06/30/16

**RRS15**

136 OF 167

Z:\SIS\_CADD\Washington State RR\MP 07.60\_NE 119th St\0760\_015.dwg  
ERICA ZELLER February 2, 2018 2:11 PM


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE






**CONSTRUCTION NOTES**

- 1 CONSTRUCT FOUNDATION, SUPPLY AND INSTALL TYPE 332D CABINET AND ITS EQUIPMENT WITH INTERIOR BATTERY BACKUP, SEE SHEET ITS1
- 2 FURNISH AND INSTALL PULL BOX PER WSDOT STANDARD PLAN J-90.10-02.
- 3 FURNISH AND INSTALL CONDUIT. SEE WIRING SCHEDULE.
- 4 FURNISH AND INSTALL POE PTZ CAMERA INCLUDING MOUNTING EQUIPMENT.




MATCH LINE STA 218+00 SEE PLAN SHEET INC4

MATCH LINE STA 223+00 SEE PLAN SHEET INC4



CONDUIT & FIBER OPTIC SCHEDULE								
RUN NO	CONDUIT	48 SMFO	CAT5e	CAT6u	PULL LINE	#12 TRACER WIRE	POWER	NOTES
1	3" VIA TRENCHING	1			1	1		
2	3" VIA TRENCHING	1			1	1		
3	3" VIA TRENCHING			1	1			
4	3" VIA TRENCHING		1		1			
5	3" VIA TRENCHING						2 - #6	POWER W/ 1-#6 GRD



**GENERAL NOTES**

1. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH WSDOT AND CLARK COUNTY STANDARD PLANS AND SPECIFICATIONS, OR AS AMENDED BY THE CONTRACT SPECIFICATIONS.
2. PROPOSED CONDUIT LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO ANY ITS WORK. ANY CONFLICTS RESOLUTIONS SHALL BE APPROVED BY COUNTY ENGINEER.
3. COORDINATE WITH THE POWER COMPANY FOR SERVICE HOOK-UP.
4. CONTRACTOR SHALL PROVIDE AND INSTALL FIBER AND ETHERNET SWITCHES IN ITS CABINET.

**LEGEND**

- PROPOSED COBRA HEAD LIGHT POLE NUMBER (N). SEE LIGHTING SCHEDULE
- PROPOSED POE PTZ CAMERA
- ITS CABINET
- SERVICE CABINET
- PULL BOX
- WSDOT TYPE 1 JUNCTION BOX
- WSDOT TYPE 2 JUNCTION BOX
- ILLUMINATION CONDUIT AND CONDUCTOR
- ITS CONDUIT AND CONDUCTOR
- RIGHT OF WAY

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



**TRANSPORTATION PROGRAM**


**PUBLIC WORKS**  
ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**

NE 119TH STREET EAST - VOLUME 2 CRP #342422  
**INTELLIGENT TRANSPORTATION SYSTEM PLAN**  
SHEET 1 OF 1


DATE 02/07/18  
**ITSP1**  
137 OF 167

TYPICAL 332D COMMUNICATIONS/UPS CABINET DETAILS



NOTE: CONTRACTOR SHALL PROVIDE AND INSTALL FIBER SWITCHES


LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



NE 119TH STREET EAST - VOLUME 2 CRP #342422  
 INTELLIGENT TRANSPORTATION SYSTEM  
 SHEET 1 OF 2

DATE 02/07/18  
 ITS1  
 138 OF 167


### ITS-POWER DISTRIBUTION ASSEMBLY - FRONT VIEW



HINGE AT TOP AND BOTTOM. ALL WIRING SHALL HAVE SUFFICIENT SLACK TO ALLOW DOOR TO FULLY OPEN

DEPTH OF ITS-PDA - 10.50-IN MAX  
CIRCUIT BREAKERS PER 2009 CALTRANS TEES SECTION 1.3.9

### ITS-POWER DISTRIBUTION ASSEMBLY - REAR VIEW



HINGE AT BOTTOM, BOTH SIDES. ALL WIRING SHALL HAVE SUFFICIENT SLACK TO ALLOW DOOR TO FULLY OPEN

ALL SCREWS ON TERMINAL STRIPS SHALL BE PAN HEAD STANDARD / PHILLIPS (COMBO) 10-32 MACHINE SCREWS WITH 18-8 STAINLESS STEEL (TYPE 316 STAINLESS STEEL IS ACCEPTABLE AS ALTERNATE)



RECEPTACLE COLOR:

- CB 1 - CPU - BLACK
- CB 2 - DATA COMS - GREY
- CB 3 - VIDEO CAMS - BLUE
- CB 4 - UPS - RED
- GFCI - WHITE


**NOTES:**


7. CIRCUIT BREAKER AUXILIARY SWITCH- WHEN CIRCUIT BREAKER IS PLACED IN THE 'ON' POSITION, THE NORMALLY OPEN (NO) TERMINAL SHALL BE CONNECTED TO THE COMMON TERMINAL. WHEN PLACED IN THE 'OFF' POSITION, THE NORMALLY CLOSED (NC) TERMINAL SHALL BE CONNECTED TO THE COMMON TERMINAL.
8. JP1 -- INSTALL JUMPER WHEN EXTERNAL UPS / BBS IS NOT INSTALLED. REMOVE JUMPER AND CONNECT EXTERNAL UPS / BBS TO T2-10.
9. JP2 -- INSTALL JUMPER WHEN INTERNAL UPS / BBS IS NOT INSTALLED. REMOVE JUMPER AND CONNECT INTERNAL UPS / BBS TO T3-2.

- WIRE NOTES:**
1. ALL WIRING SHALL BE CONSTRUCTED FROM STRANDED SINGLE CONDUCTOR COPPER MATERIAL, INSULATION RATED AT 90 DEGREES CELSIUS AND UL LISTED FOR DAMP AND DRY LOCATIONS.
  2. 120 VAC (AC+) & BATTERY -VOLTS DC SUPPLY LINES SHALL HAVE BLACK INSULATION
  3. 120 NEUTRAL (AC-) WIRING SHALL HAVE WHITE INSULATION
  4. BATTERY +VOLTS DC & +24 VDC POWER SUPPLY WIRES SHALL HAVE RED INSULATION
  5. -24 VDC POWER SUPPLY (LOGIC REF) WIRES SHALL HAVE WHITE INSULATION WITH A RED TRACER STRIPE
  6. GROUNDING WIRES SHALL HAVE GREEN INSULATION



NOTE: CONTRACTOR SHALL PROVIDE AND INSTALL FIBER SWITCHES





**CONSTRUCTION NOTES**

- 1 INSTALL NEW LED COBRA HEAD STYLE STEEL STREET LIGHT POLE ON NEW FOUNDATION
- 2 FURNISH AND INSTALL LIGHTING CONDUIT. SEE LIGHTING WIRING SCHEDULE
- 3 FURNISH AND INSTALL TYPE 1 JUNCTION BOX. SEE WSDOT STD. PLAN J-40.10-04
- 4 FURNISH AND INSTALL 2 -10" STEEL CASINGS BY DIRECTIONAL BORE. SEE ITS PLANS FOR FIBER OPTIC CABLING. SEE GENERAL NOTE 2. VERIFY DEPTH TO BE 6.0 FEET BELOW RR TOP OF TIE (APPROX. ELEV: 236.8)
- 5 CONSTRUCT FOUNDATION, FURNISH AND INSTALL METERED SERVICE PER DETAIL ON SHEET ILLD1 AND ILLD2
- 6 CPU SERVICE POLE, COORDINATE CONNECTION WITH CPU.
- 7 INSTALL SERVICE CONDUIT AND WIRING

**GENERAL NOTES**

1. SEE WSDOT STANDARD PLANS:  
 J-28.10-01 FOR STEEL LIGHT STANDARD.  
 J-28.22-00 FOR STEEL LIGHT STANDARD (SLIP BASE)  
 J-28.24-01 FOR STEEL LIGHT STANDARD (FIXED BASE).  
 J-28.30-03 FOR DESIGN OF TYPE A FOUNDATION  
 J-28.40-02 FOR STEEL LIGHT STANDARD BASE MOUNTING (FIXED BASE).  
 J-28.42-01 FOR STREET LIGHT STANDARD ANCHOR/SLIP PLATE FOR SLIP BASE  
 J-28.50-03 FOR STREET LIGHT STANDARD POLE BASE AND HAND HOLE DETAILS.  
 J-28.70-03 FOR STREET LIGHT STANDARD WIRING DETAILS.
2. STEEL CASING SHALL HAVE A MINIMUM THICKNESS OF 0.188 INCHES AND A MINIMUM YIELD STRENGTH OF 35,000 P.S.I
3. ALL CONDUIT RUNS AND JUNCTION BOX LOCATIONS ARE APPROXIMATE. FINAL LOCATIONS MAY BE ADJUSTED TO AVOID CONFLICTS AND EASE OF CONSTRUCTION, BUT MUST BE APPROVED BY THE ENGINEER PRIOR TO EXCAVATION.

CONDUIT & CONDUCTOR SCHEDULE						
RUN NO. #	CONDUIT	ILLUMINATION WIRES	CIRCUIT	PULL LINE	POWER	NOTES
1	2" VIA TRENCHING	2 - #8 w/ 1 - #8 GRD	1	-		
2	2" VIA TRENCHING	2 - #8 w/ 1 - #8 GRD	1	-		
3	2" VIA TRENCHING	-	-	-	2 - #6 w/ #2 GRD	

NOTE: POWER SERVICE REQUIREMENTS TO BE DETERMINED BY CLARK PUBLIC UTILITY

LIGHTING WIRING SCHEDULE								
LUMINAIRE NUMBER	LOCATION		LUMINAIRE			POLE TYPE	CIRCUIT	NOTES
	STATION	OFFSET	TYPE-DISTRIBUTION-WATTAGE	ARM LENGTH (FT)	MOUNTING HEIGHT (FT)			
1	219+59.2	47.10 Rt	LED - TYPE III - SPEC 9-29.10	15	30	STEEL	1	FIXED BASE
2	220+70.0	43.00 Lt	LED - TYPE III - SPEC 9-29.10	15	30	STEEL	1	SLIP BASE
3	221+68.0	38.50 Rt	LED - TYPE III - SPEC 9-29.10	15	30	STEEL	1	FIXED BASE
4	222+78.2	38.50 Lt	LED - TYPE III - SPEC 9-29.10	15	30	STEEL	1	SLIP BASE



**LEGEND**

- PROPOSED COBRA HEAD LIGHT POLE NUMBER (N). SEE LIGHTING SCHEDULE
- PROPOSED PTZ CAMERA (SEE ITS PLANS)
- WSDOT TYPE 1 JUNCTION BOX
- PROPOSED SERVICE CABINET
- CPU POWER SERVICE PEDESTAL
- CONDUIT AND CONDUCTOR
- RIGHT OF WAY

**CASING CONTENTS**



1. ILLUMINATION CASING:  
SCH. 80 HDPE WITH 3 - #8 COPPER WIRE CARRYING 240V.
2. ITS CASING  
SCH. 80 HDPE WITH 48 STRAND SINGLE MODE FIBER OPTIC CABLE.

LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE




NE 119TH STREET EAST - VOLUME 2 CRP #342422  
**ILLUMINATION PLAN**  
 SHEET 1 OF 1

DATE 02/07/18  
 ILLP1  
 140 OF 167



WIRING SCHEMATIC - ROADWAY LIGHTING

LEGEND



LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



**TRANSPORTATION PROGRAM**

**PUBLIC WORKS**  
ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**

NE 119TH STREET EAST - VOLUME 2 CRP #342422

ILLUMINATION DETAIL  
SHEET 1 OF 2

DATE 02/07/18

ILLD1




141 OF 167

150 AMP TYPE 120/240 1Ø SERVICE CABINET

NOTES:

1. SEE STD. SPECIFICATION 9-29.24, SERVICE CABINETS. THE CONTRACTOR SHALL SUBMIT A REQUEST FOR APPROVAL OF MATERIALS THAT DESCRIBES THE SERVICE CABINET PROPOSED FOR USE.
2. HINGES SHALL HAVE STAINLESS STEEL OR BRASS PINS.
3. CABINETS SHALL BE RATED NEMA 3R AND SHALL INCLUDE TWO RAIN TIGHT VENTS.
4. METERING EQUIPMENT DOOR SHALL BE PAD LOCKABLE. EACH DOOR SHALL BE GASKETED. INSTALL FIGURE 8 CORE LOCK ON BOTTOM DOOR COMPATIBLE WITH COUNTY LOCKS.
5. METERING ARRANGEMENTS VARY WITH DIFFERENT SERVING UTILITIES. THE UTILITY MAY REQUIRE METER BASE MOUNTING IN THE ENCLOSURE, ON THE SIDE OR ON THE BACK OF THE ENCLOSURE. THE UTILITY MAY SPECIFY A MINIMUM DIMENSION BETWEEN THE DOOR AND THE FRONT OF THE SAFETY SOCKET.
6. THE CONTRACTOR SHALL VERIFY THE SERVING UTILITY'S REQUIREMENTS PRIOR TO FABRICATION OF AND INSTALLING THE SERVICE EQUIPMENT.
8. ALL BUSSWORK SHALL BE HIGH GRADE COPPER AND SHALL EQUAL OR EXCEED THE MAIN BREAKER RATING. ALL BREAKERS SHALL BOLT ONTO THE BUSSWORK. JUMPERING OF BREAKERS SHALL NOT BE ALLOWED. BUSSWORK SHALL ACCOMMODATE ALL FUTURE EQUIPMENT AS SHOWN IN THE BREAKER SCHEDULE.
9. ALL INTERNAL WIRE RUNS SHALL BE IDENTIFIED WITH "TO - FROM" CODED TAGS LABELED WITH THE CODE LETTERS AND/OR NUMBERS SHOWN ON THE SCHEDULES. APPROVED PVC OR POLYOLEFIN WIRE MARKING SLEEVES SHALL BE USED.
10. A 1% TOLERANCE IS ALLOWED FOR ALL DIMENSIONS.
12. INSTALL CONDUIT COUPLINGS ON ALL CONDUITS. PLACE COUPLINGS FLUSH WITH TOP OF CONCRETE FOUNDATION.
13. SEAL CABINET TO FOUNDATION WITH A 1/2" BEAD OF SILICONE. APPLY SILICONE TO DRY SURFACE ONLY. INSTALL GASKET (30 LB BUILDING PAPER) AND SEAL WITH A NON-HARDENING WATER-TIGHT SEALANT.
14. THE METER BASE PORTION OF THIS SERVICE SHALL MEET METERING PORTION OF EUSERC DRAWING 309 REQUIREMENTS.
15. UNUSED CIRCUIT BREAKER LOCATIONS SHALL BE COVERED.

- ① METER BASE PER SERVING UTILITY REQUIREMENTS. AS A MINIMUM, THE METER BASE SHALL BE SAFETY SOCKET BOX WITH FACTORY INSTALLED TEST BYPASS FACILITY THAT MEETS THE REQUIREMENTS OF EUSERC DRAWING 304.
- ② 150 AMP MAIN BREAKER
- ③ PHOTOCELL BREAKER (SPST 15 AMP - 120/240 VOLT)
- ④ PHOTOCELL TEST SWITCH (SPDT SNAP ACTION, POSITIVE CLOSE, 15 AMP - 120/277 VOLT "T" RATED)
- ⑤ PHOTOELECTRIC CONTROL, MOUNTED ON LUMINAIRE No. 1
- ⑥ ILLUMINATION CIRCUIT BREAKER (20 AMP)
- ⑦ ITS CABINET CIRCUIT BREAKER (50 AMP)
- ⑧ CONTACTOR
- ⑨ RECEPTACLE BREAKER (SPST 20 AMP - 120/240 VOLT)
- ⑩ RECEPTACLE, GROUNDED (GFCI 20 AMP - 125 VOLT)
- ⑪ NEUTRAL BUSS, 14 LUG COPPER
- ⑫ HINGED FRONT FACING DOOR WITH 4" x 4" MIN. POLISHED WIRE GLASS WINDOW.
- ⑬ HINGED DEAD FRONT WITH 1/4 TURN FASTENERS OR SLIDE LATCH.
- ⑭ CABINET MAIN BONDING JUMPER BUSS SHALL BE 4 LUG TINNED COPPER. SEE CABINET MAIN BONDING JUMPER DETAIL, STANDARD PLAN J-3b.
- ⑯ SPARE BRANCH BREAKER (DPST 20AMP- 120/240 VOLT)
- ⑰ METAL WIRING DIAGRAM HOLDER
- ⑱ REMOVABLE EQUIPMENT MOUNTING PAN
- ⑲ 6" x 6" MIN. UNDERGROUND FEED - UTILITY SERVICE WIREWAY (LEFT REAR CORNER)
- ⑳ SCREENED VENTS, 2 REQUIRED, 1 EACH SIDE, LOUVERED PLATES.
- ㉑ PROVIDE BREAKER FOR SIGNAL CABINET HEATER (SPST 20 AMP - 120/240 VOLT)
- ㉒ NOT USED
- ㉓ NOT USED
- ㉔ 24 CIRCUIT PANEL BOARD - MINIMUM SIZE WITH SEPARATE MAIN BREAKER.
- ㉕ LABEL CABINET WITH BUSSWORK RATING.



LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND MAY BE INCOMPLETE



TRANSPORTATION PROGRAM

**PUBLIC WORKS**  
ENGINEERING & CONSTRUCTION DIVISION

**ENGINEERING AND DESIGN SECTION**

NE 119TH STREET EAST - VOLUME 2 CRP #342422

ILLUMINATION DETAIL  
SHEET 2 OF 2

DATE 02/07/18

ILLD2

142 OF 167