

WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

Petitioner,			DOCKET NO. TR- PETITION FOR EXEMPTION FROM COMMISSION RULES RELATED TO RAILROAD COMPANIES – CLEARANCES (WAC 480-60)		
The Petitioner asks the Washington Utilities and Transportation Commission to grant exemption from rules related to (check one or more):					
Railroad overhead clearance requirements found in WAC 480-60-040					
	Railroad s	side clearance requirements	found in WAC 480-60-050		
	Railroad t	rack clearance requirement	s found in WAC 480-60-060		
WAC 4 WAC 4 WAC 4 WAC 4 WAC 4 WAC 4	/Attachments: .80-60-020 .80-60-030 .80-60-040 .80-60-050 .80-60-060 .80-60-990 .80-60-9901	Exemptions Definitions Overhead clearances Side clearances Track clearances Illustration – Typical clear Illustration – Typical track			
			<u> </u>		
Note: If the restricted clearance is located at a customer facility, the customer is the petitioner. If the restricted clearance is located at a railroad-owned facility, the railroad is the petitioner.					
Petitioner:					
Business Address:					
City, State, and Zip Code:					
Mailing Address, if Different:					
Representative Name and Title:					
Representative Phone Number and Email Address:					
Representative Signature: Kiri Mailsoi					

04-21

Section 2 – Railroad's Information

Note: When a railroad <u>customer</u> is the petitioner in a request for clearance exemption, the railroad must sign the Railroad Support Statement in Section 8. When a railroad requests a clearance exemption for its own facility or location, it is not necessary to complete Sections 2 or 8.			
Railroad:			
Business Address:			
City, State, and Zip:			
Mailing Address, if Different:			
Contact Name and Title:			
Contact Phone Number:			
Email Address:			
Section 3 – Restricted Clearance Location			
Name of Facility or Location:			
DI ' 1 A 11			
Physical Address:			
Physical Address: City and County:			
City and County:			

Section 4 – Restricted Clearance Description

Describe in detail each structure or track which is, or will be, located at less than the required standard clearance from an adjacent track. Where more than one track is involved, identify the track by number or name. The description should include the length of the structure along the track, its distance from the center line of track, and its maximum elevation. For overhead clearance impairments, the description should include the minimum elevation of the structure as measured from the top of the rail. (Attach additional pages if necessary.)
Describe why is it necessary to operate with restricted clearances.
Explain why the facility should not be constructed or altered to conform to required clearances.
Describe what modifications would be necessary to meet required clearances.

Section 5 – Drawings

Attach drawings to show the following:

- The area within a 100-foot radius of each restricted clearance.
- The track layout of the industry or railroad facility involved, including any connecting tracks and switches (provide identifying name or number for each impaired track and each major structure adjacent thereto).
- A profile view of each impairing structure and its relationship with the adjacent trackage, including measurements from the centerline of track (between rails) to all adjacent impairments. Each drawing should be made to scale, and each impairment should be color coded and identified by letter (see sample illustrations).

Section 6 – Trackage			
Describe the trackage involved, including the overall length of each track and the length of track prior to and beyond each impairing structure.			
Wiles around the translation of the second o			
Who owns the trackage involved?			
Who operates on this trackage?			
From which direction(s) can train movements be originated on each impaired track?			
What is the average number of train movements per day?			
What is the speed of train movements?			
What time of day do train movements occur?			
Describe typical railroad activities in the area involved in this request:			

Section 7 – Warning Devices

Note: Retroreflective warning signs should be placed not more than 50 feet in advance of the nearest restricted clearance when entering the impaired track. If operations occur during hours of darkness, warning signs should be illuminated. If such placement and illumination is not feasible, please explain why and specify where each placement will be made.)
What form of warning is proposed for railroad employees at each restricted clearance and where will it be installed? Class 1 railroads have specific standards for signage. Please provide examples of proposed signage, lighting, etc. for this facility.

Section 8 – Railroad Support Statement

Note: If a railroad is requesting the exemption from clearance requirements for its own facility or location, it is not necessary to complete this section.

The undersigned represents the railroad operating at the facility or location with the areas of restricted clearance.

We have investigated the conditions at the location of the restricted clearance. We are satisfied that the conditions are the same as described by the Petitioner. We do not object to the petitioner's request for exemption from Commission clearance rules. We support the proposed warning devices for the areas of restricted clearance. We agree to notify our operating employees of the areas of restricted clearance at this facility upon approval of the request for exemption, as directed by the Commission.

April 2025

Dated at Vancouver

, Washington, on the day of

Kyle Leatham

Printed Name

Kyls Leatham
Signature of Railroad's Representative

Manager Public Projects

Title

206-625-6152

Phone Number

kyle.leatham@BNSF.com

Email

1310 W 11th St, Vancouver, WA 98660

Mailing Address