ATTACHMENT B



WN U-76

Second Revision of Sheet No. 114.4 Canceling First Revision of Sheet No. 114.4

Schedule 114 RESIDENTIAL ENERGY EFFICIENCY RIDER—OPTIONAL FOR QUALIFYING LOW INCOME CUSTOMERS

ENERGY EFFICIENT MEASURES: (continued) Supplemental Measures:

/	(continued)
15)	Replacement windows with a U-value of 0.30 or less.
14)	Ductless heat pumps may be installed to replace permanently installed electric heat, space heaters or any fuel source except natural gas with adequate combustion air as determined by the Agency.
13)	Refrigerators applicable in all homes: Refrigerators with monitored results or listed in the Weatherization Assistance Program Technical Assistance Center database may be replaced with a model with an estimated annual consumption of 600 kWh or less when a SIR of 1.0 or greater is indicated. Replaced refrigerators must be removed and recycled in accordance with EPA guidelines.
12)	Compact fluorescent light and/or light emitting diode (LED) bulbs applicable in all homes. Energy Star certified bulbs placed in fixtures that are on 2 or more hours per day.
11)	Light emitting diode (LED) and/or fluorescent light fixtures applicable in all homes.
10)	Water heaters: Tank replacement of existing electric water heaters. Replacement will be a model with an EF rating as follows: <= 55 gallon capacity = 0.94 or greater, > 55 gallon capacity = 2.2 EF or greater. Heat pump water heaters meeting Northwest Energy Efficiency Alliance Northern Climate Specifications replacing an existing electric water heater.
9)	Water heater blankets: Installed where tank is located in an unconditioned space and in compliance with the Washington Department of Commerce Weatherization Manual.
8)	Energy efficient showerheads, aerators and water pipe wrap where electric water heaters are present. Showerheads with a visible flow rating greater than 2.5 gallons per minute (gpm) will be replaced, and showerheads without a gpm marking may be replaced at the discretion of agency staff.
7)	Smart Thermostats included on the EnergyStar Qualified Products List on centrally controlled, ducted electric heating systems, where replacing a non-communicating thermostat.
6)	Timed thermostats on centrally controlled multi-room heating systems except when used with heat pumps. Heat anticipating type thermostats for zonal electric resistance heating systems. Zonal thermostats must be separate from the heating unit and must be calibrated at the site to within 2°F of actual room temperature in the range of 65°F-75°F.
5)	Dehumidifiers.

Issued By PacifiCorp d/b/a Pacific Power & Light Company

By: _____ Matthew McVee Title: Vice President, Regulation