



**Alliance for Telecommunications
Industry Solutions**

ATIS Standard

ATIS 3GPP SPECIFICATION

ATIS.3GPP.32.304V600-2005

**Technical Specification Group Services and System Aspects;
Telecommunication management;
Configuration Management (CM); Notification Integration Reference
Point (IRP): Common Management Information Protocol
(CMIP) Solution Set (SS)**

**Approved by
WTSC
Wireless Technologies and Systems Committee**



ATIS is a technical planning and standards development organization that is committed to rapidly developing and promoting technical and operations standards for the communications and related information technologies industry worldwide using a pragmatic, flexible and open approach. Over 1,100 participants from more than 350 communications companies are active in ATIS' 21 industry committees, and its Incubator Solutions Program.

< <http://www.atis.org/> >

The text in this ATIS Specification is identical 3GPP TS 32.304 V6.0.0 (2004-March).

Please note that 3GPP TS 32.304 V6.0.0 (2004-March) was developed within the Third Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP™. The contents of 3GPP TS 32.304 V6.0.0 (2004-March) are subject to continuing work within the 3GPP™ and may change following formal 3GPP™ approval. Should the 3GPP™ modify the contents of 3GPP TS 32.304 V6.0.0 (2004-March), it will be re-released by the 3GPP™ with an identifying change of release date and an increase in version number. The user of this Specification is advised to check for the latest version of 3GPP TS 32.304 V6.0.0 (2004-March) at the following address:

<ftp://ftp.3gpp.org/Specs/> (sorted by release date)

The user is further advised to verify the changes over the version listed as the approved basis for this Specification and to utilize discretion after identifying any changes.

3GPP Support Office
650 Route des Lucioles -- Sophia Antipolis
Valbonne - FRANCE
tel: +33 4 92 94 42 00 fax: +33 4 93 65 47 16 web: <http://www.3gpp.org>

"3GPP" is a registered trademark of ETSI in France and other jurisdictions on behalf of the 3rd Generation Partnership Project Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).

ATIS.3GPP.32.304V600-2005

Published by

Alliance for Telecommunications Industry Solutions
1200 G Street, NW, Suite 500
Washington, DC 20005

Copyright © 2005 by Alliance for Telecommunications Industry Solutions
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at +1 202.628.6380. ATIS is online at < <http://www.atis.org/> >.

Printed in the United States of America.

Contents

Foreword.....	4
Introduction.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions.....	6
3.2 Abbreviations.....	6
4 Basic aspects.....	7
4.1 Architectural aspects.....	7
4.1.1 Event report management function in ITU-T.....	7
4.1.1.1 Event report management model.....	7
4.1.1.2 Event forwarding discriminator management.....	7
4.1.1.3 Definition of notifications.....	7
4.1.2 Mediation between the concepts of Notification IRP IS and ITU-T.....	7
4.2 Mapping.....	8
4.2.1 Mapping of Information Object Classes (IOC).....	8
4.2.2 Mapping of operations.....	8
4.2.3 Mapping of operation parameters.....	9
4.2.3.1 Parameter mapping of the operation 'subscribe'.....	9
4.2.3.2 Parameter mapping of the operation 'unsubscribe'.....	9
4.2.3.3 Parameter mapping of the operation 'getSubscriptionIds'.....	10
4.2.3.4 Parameter mapping of the operation 'getSubscriptionStatus'.....	11
4.2.3.5 Parameter mapping of the operation 'changeSubscriptionFilter'.....	11
4.2.3.6 Parameter mapping of the operation 'suspendSubscription'.....	12
4.2.3.7 Parameter mapping of the operation 'resumeSubscription'.....	12
4.2.3.8 Parameter mapping of the operation 'getNotificationCategories'.....	12
4.2.3.9 Parameter mapping of the operation 'getIRPVersion'.....	12
4.2.3.10 Parameter mapping of the Operation 'getOperationProfile'.....	13
4.2.3.11 Parameter mapping of the operation 'getNotificationProfile'.....	13
4.2.4 Mapping of the notification header.....	13
5 GDMO definitions.....	14
5.1 Managed Object Classes.....	14
5.1.1 notificationControl.....	14
5.2 Packages.....	14
5.2.1 notificationControlBasicPackage.....	14
5.2.2 notificationControlInfoPackage.....	14
5.2.3 notificationIRPVersionPackage.....	14
5.2.4 notificationProfilePackage.....	15
5.3 Actions.....	15
5.3.1 Void.....	15
5.3.2 getNotificationCategories (O).....	15
5.3.3 getNotificationIRPVersion (M).....	15
5.3.4 getNotificationProfile (O).....	16
5.3.5 getOperationProfile (O).....	16
5.4 Attributes.....	17
5.4.1 notificationControlId.....	17
5.4.2 supportedNotificationCategories.....	17
5.4.3 supportedNotificationIRPVersions.....	17
6 ASN.1 definitions.....	17
Annex A (informative): Change history.....	20

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part the 32.30x-series covering the 3rd Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management; Configuration Management (CM), as identified below:

- 32.301: "Notification Integration Reference Point (IRP): Requirements";
- 32.302: "Notification Integration Reference Point (IRP): Information Service (IS)";
- 32.303: "Notification Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
- 32.304: "Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)";**

The Itf-N interface for CM is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the Notification Integration Reference Point (IRP): Information Service defined in 3GPP TS 32.302 [3]. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Notification Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.302 V6.0.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.302: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Information Service (IS)".
- [4] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [5] ITU-T Recommendation X.710: "Information technology - Open Systems Interconnection - Common Management Information Service".
- [6] ITU-T Recommendation X.711: "Information technology - Open Systems Interconnection - Common Management Information Protocol: Specification".
- [7] ITU-T Recommendation X.721: "Information technology - Open Systems Interconnection - Structure of management information: Definition of management information".
- [8] ITU-T Recommendation X.731: "Information technology - Open Systems Interconnection - Systems Management: State management function".
- [9] ITU-T Recommendation X.733: "Information technology - Open Systems Interconnection - Systems Management: Alarm reporting function".
- [10] ITU-T Recommendation X.734: "Information technology - Open Systems Interconnection - Systems Management: Event report management function".
- [11] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [12] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions defined in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2] and 3GPP TS 32.302 [3] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASN.1	Abstract Syntax Notation number 1
CM	Configuration Management
CMIP	Common Management Information Protocol
CMIS	Common Management Information Service
CMISE	Common Management Information Service Element
EFD	Event Forwarding Discriminator
EM	Element Manager
ETSI	European Telecommunications Standards Institute
GDMO	Guidelines for the Definition of Managed Objects
IOC	Information Object Class
IRP	Integration Reference Point
ITU-T	International Telecommunication Union - Telecommunications
Itf-N	Interface N (between NM and EM/NE) (3GPP TS 32.102 [2])
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NM	Network Manager
NMC	Network Management Centre
OS	Operations System
TMN	Telecommunications Management Network

4 Basic aspects

The present document provides the GDMO and ASN.1 definitions necessary to implement the Notification IRP for the CMIP interface. The definitions provided in the present document are employed by any other IRP that includes event reporting and/or management of event reporting.

4.1 Architectural aspects

The architecture of the Notification IRP CMIP Solution Set is adapted as much as possible to the event reporting management model as defined in ITU-T Recommendation X.734 [10].

4.1.1 Event report management function in ITU-T

4.1.1.1 Event report management model

According to the event reporting management model specified in ITU-T Recommendation X.734 [10] each managed object may emit notifications (potential event reports). Conceptually, these potential event reports are distributed to all Event Forwarding Discriminators (EFDs) that are instantiated in the IRPAgent. The event forwarding discriminators process the potential event reports to determine which event reports are to be forwarded to a particular destination. The conditions event reports must satisfy in order to be forwarded are specified by the discriminator construct. This is a set of one or more assertions about the presence or value of attributes of the potential event report.

Operational and administrative states are defined for event forwarding discriminators. The operational state has two possible values: enabled and disabled. In the enabled state the discriminator processes the potential event reports. In the disabled state potential event reports are not processed. The administrative states defined are locked and unlocked. When the state is changed from unlocked to locked forwarding of event reports is suspended. When the administrative state is changed from locked to unlocked event forwarding is resumed.

4.1.1.2 Event forwarding discriminator management

The event forwarding discriminator is a managed object. Event reporting is controlled by performing operations on these objects. The required management operations are defined in ITU-T Recommendation X.710 [5].

In order to initiate the transmission of event reports an event forwarding discriminator has to be created in the IRPAgent. For this purpose the CMISE M-CREATE service is used. In order to terminate the transmission the discriminator has to be deleted (M-DELETE). The filtering mechanism may be changed by modifying the discriminator construct attribute. This operation is requested by M-SET. The transmission may be suspended and resumed by changing the administrative state from unlocked to locked and vice versa. Also for modifying the administrative state the M-SET service is used.

4.1.1.3 Definition of notifications

ITU-T Recommendation X.734 [10] does not define any specific notifications. Instead, any object of the IRPAgent that shall have the capability to emit notifications must have the GDMO and the supporting ASN.1 syntax definition of these notifications included in the definition of its managed object class. More specifically, whereas the present document defines the managed objects and operations for the event reporting function the other IRPs must specify the information to be carried in the notifications.

The event reports are sent from the IRPAgent to the IRPManager using the CMISE service M-EVENT-REPORT, defined in ITU-T Recommendation X.710 [5] and ITU-T Recommendation X.711 [6].

4.1.2 Mediation between the concepts of Notification IRP IS and ITU-T

The Notification IRP Information Service defines several operations allowing the IRPManager to control the event reporting: subscribe, unsubscribe, suspend subscription, resume subscription, change filter, get subscription status, get subscription identifiers.

The subscription-related operations of the Notification IRP (subscribe, unsubscribe, suspendSubscription, resumeSubscription, changeSubscriptionFilter, getSubscriptionStatus, getSubscriptionIds) are mapped into CMISE

services. The remaining operations of the Notification IRP (getNotificationCategories, getNotificationIRPVersion, getOperationProfile, getNotificationProfile) allowing the IRPManager to retrieve information pertaining to the Notification IRP are implemented as GDMO actions by a special managed object in the IRPAgent.

The EFDs are hence directly controlled by the IRPManager. On Itf-N are invoked CMISE services when EFDs are managed and GDMO actions when the IRPManager retrieves information about the Notification IRP.

4.2 Mapping

The semantics of the Notification IRP are defined in 3GPP TS 32.302 [3]. The definitions of the management information defined there are independent of any implementation technology and protocol. This clause maps these protocol independent definitions onto the equivalencies of the CMIP Solution Set of the Notification IRP.

4.2.1 Mapping of Information Object Classes (IOC)

Table 1 maps the IOCs defined in the Notification IRP Information Service onto the corresponding Managed Object Classes defined in this CMIP Solution Set. The Managed Object Classes (MOC) are qualified as Mandatory (M) or Optional (O).

Table 1: Mapping of IOC

IOC of the Notification IRP Information Service	MOC or Attributes of the CMIP solution set	Qualifier
NotificationIRP	notificationControl	M
NtfSubscriber	--	
NtfSubscription	--	

4.2.2 Mapping of operations

Table 2 and table 3 map the operations defined in the 3GPP TS 32.302 [3] (Notification IRP: Information Service) and 3GPP TS 32.312 [12] (Generic IRP Management: Information Service) onto corresponding CMISE services and GDMO actions. The operations are qualified as mandatory (M) or optional (O).

The CMISE services are defined in ITU-T Recommendation X.710 [5].

Table 2: Mapping of operations of the Notification IRP IS

Interface	Operation	GDMO Action or CMISE of CMIP SS	Qualifier
NotificationIRPManagement	subscribe	M-CREATE (CMISE) Creation of an EFD	M
	unsubscribe	M-DELETE (CMISE) Deletion of an EFD	M
SubscriptionSuspendOperations	suspendSubscription	M-SET (CMISE) Modification of the administrative state of the EFD to locked	O
	resumeSubscription	M-SET (CMISE) Modification of the administrative state of the EFD to unlocked	O
SubscriptionFilterOperations	changeSubscriptionFilter	M-SET (CMISE) Modification of the discriminator construct in the EFD	O
SubscriptionStatusOperations	getSubscriptionStatus	M-GET (CMISE) Retrieval of EFD attributes	O
SubscriberManagement	getSubscriptionIds	M-GET (CMISE) Retrieval of the object instances of the EFDs having the specified destination attribute	O
IRPManagementOperations	getNotificationCategories	getNotificationCategories	O

Table 3: Mapping of operations of the Generic IRP Management IS

Interface	Operation	GDMO Action of CMIP SS	Qualifier
GenericIRPVersionsOperations	getIRPVersion	getNotificationIRPVersion	M
GenericIRPProfileOperations	getOperationProfile	getOperationProfile	O
	getNotificationProfile	getNotificationProfile	O

4.2.3 Mapping of operation parameters

The tables in the following clauses show the parameters of each operations defined in the Information Service described in 3GPP TS 32.302 [3] and their equivalence in this CMIP solution set.

4.2.3.1 Parameter mapping of the operation 'subscribe'

A manager subscribes to certain notifications by creating an appropriate EFD in the IRPAgent using the CMISE M-CREATE service.

The attribute list parameter of M-CREATE shall contain the values of the EFD attributes for destination and discriminatorConstruct.

The managed object instance of the created EFD is returned to the IRPManager in the M-CREATE success confirmation. According to ITU-T Recommendation X.710 [5] this parameter has to be returned, if it is not supplied in the M-CREATE request.

Table 4a: Parameter mapping of the operation 'subscribe'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
managerReference	IN	M-CREATE request parameter 'Attribute list': attribute identifier and value for the EFD 'destination' attribute	M
timeTick	IN	--	--
notificationCategories	IN	M-CREATE request parameter 'Attribute list': attribute identifier and value for the EFD 'discriminatorConstruct' attribute	O
filter	IN	M-CREATE request parameter 'Attribute list': attribute identifier and value for the EFD 'discriminatorConstruct' attribute	O
subscriptionId	OUT	M-CREATE success confirmation parameter 'Managed object instance'	M
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-CREATE success confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-CREATE failure confirmation.	M

4.2.3.2 Parameter mapping of the operation 'unsubscribe'

The IRPManager can unsubscribe from receiving certain notifications by deleting the associated EFD using the M-DELETE service. The EFD to be deleted is identified by the M-DELETE parameters for the base object class and the base object instance.

The Notification IRP Information Service 3GPP TS 32.302 [3] specifies that a NtfSubscriber (IRPManager) may only delete subscriptions that are involved in a subscription relationship with the NtfSubscriber identified by the ManagerReference input parameter. This behaviour is mapped to a filtering mechanism in CMIP. The filter must specify an assertion on the EFD attribute 'destination' so that only EFDs whose destination attribute value specifies the IRPManager invoking this operation are selected for deletion.

In 3GPP TS 32.302 [3] it is also specified that all subscriptions made by the IRPManager specified in the managerReference input parameter shall be deleted when no subscriptionId is provided. This feature is mapped to a scoping and filtering mechanism. Scoped are all EFDs, selected by the filter are only those whose destination attribute specifies the invoking IRPManager.

Table 4b: Parameter mapping of the operation 'unsubscribe'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
managerReference	IN	M-DELETE request parameters 'Scope' and 'Filter' Note: The filter parameter must specify an assertion selecting only EFDs whose destination attribute value specifies the IRPManager identified by managerReference.	M
subscriptionId	IN	M-DELETE request parameters 'Base object class' and 'Base object instance'	M
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-DELETE success confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-DELETE failure confirmation.	M

4.2.3.3 Parameter mapping of the operation 'getSubscriptionIds'

The IRPManager may retrieve a list of its subscriptions using the M-GET service. For this purpose the M-GET parameter 'Filter' must specify an assertion selecting only EFDs whose destination attribute value specifies the IRPManager identified by managerReference. The object identifiers of the selected EFDs are returned in the M-GET response parameter 'Managed object instance'. The attributes selected in the M-GET request parameter 'Attribute identifier list' and the values returned in the parameter 'Attribute list' are of no interest.

Table 5: Parameter mapping of the operation 'getSubscriptionIds'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
managerReference	IN	M-GET request parameters 'Base object class', 'Base object instance', 'Scope' and 'Filter' Note: The filter parameter must specify an assertion selecting only EFDs whose destination attribute value specifies the IRPManager identified by managerReference.	M
subscriptionIdSet	OUT	M-GET response parameter 'Managed object instance'	M
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-GET success confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-GET failure confirmation.	M

4.2.3.4 Parameter mapping of the operation 'getSubscriptionStatus'

The status of an EFD may be retrieved by the IRPManager by reading the attribute values of the EFD. For this purpose the CMIS service M-GET is used.

The emission of certain notifications is suspended when the administrative state of the corresponding EFD is locked. In the unlocked state notifications are forwarded to the IRPManager.

Table 6: Parameter mapping of the operation 'getSubscriptionStatus'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
subscriptionId	IN	M-GET request parameters 'Base object class' and 'Base object instance'	M
notificationCategoryList	OUT	--	--
filterInEffect	OUT	M-GET response parameter 'Attribute list': attribute identifier and value for the EFD 'discriminatorConstruct' attribute	M
subscriptionStatus	OUT	M-GET response parameter 'Attribute list': attribute identifier and value for the EFD 'administrativeState' attribute administrativeState locked = suspended unlocked = not suspended/resumed	O
timeTick	OUT	--	--
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-GETsuccess confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-GET failure confirmation.	M

4.2.3.5 Parameter mapping of the operation 'changeSubscriptionFilter'

The IRPManager may change the conditions to be satisfied by a potential event report before being forwarded by modifying the discriminator construct. The EFD is identified by the M-SET request parameters for the base object class and the base object instance. The new discriminator construct is specified in the M-SET request parameter 'Modification list'.

Table 7: Parameter mapping of the operation 'changeSubscriptionFilter'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
subscriptionId	IN	M-SET request parameters 'Base object class' and 'Base object instance'	M
filter	IN	M-SET request parameter 'Modification list': attribute identifier and value for the EFD 'discriminatorConstruct' attribute	M
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-SET success confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-SET failure confirmation.	M

4.2.3.6 Parameter mapping of the operation 'suspendSubscription'

The IRPManager may suspend the transmission of certain notifications by changing the administrative state of the corresponding EFD to locked. The M-SET service is used to request the change of the administrative state. The EFD is identified by the M-SET parameters for the base object class and the base object instance. The attribute to be modified and the new attribute value is specified in the M-SET request parameter 'Modification list'.

Table 8: Parameter mapping of the operation 'suspendSubscription'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
subscriptionId	IN	M-SET request parameters 'Base object class' and 'Base object instance'	M
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-SET success confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-SET failure confirmation.	M

4.2.3.7 Parameter mapping of the operation 'resumeSubscription'

The IRPManager may resume the emission of certain notifications by changing the administrative state of the corresponding EFD to unlocked. The M-SET service is used to request the change of the administrative state. The EFD is identified by the M-SET request parameters for the base object class and the base object instance. The attribute to be modified and the new attribute value is specified in the M-SET request parameter 'Modification list'.

Table 9: Parameter mapping of the operation 'resumeSubscription'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
subscriptionId	IN	M-SET request parameters 'Base object class' and 'Base object instance'	M
status	OUT	status = OperationSucceeded The semantics of this status are conveyed by the emission of a M-SET success confirmation. status = OperationFailed The semantics of this status are conveyed by the emission of a M-SET failure confirmation.	M

4.2.3.8 Parameter mapping of the operation 'getNotificationCategories'

Table 10: Parameter mapping of the operation 'getNotificationCategories'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
notificationCategoryList	OUT	notificationCategoryList	M
status	OUT	status	M

4.2.3.9 Parameter mapping of the operation 'getIRPVersion'

Table 11: Parameter mapping of the operationParameters of 'getIRPVersion'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
versionNumberSet	OUT	versionNumberList	M
status	OUT	status	M

4.2.3.10 Parameter mapping of the Operation 'getOperationProfile'

Table 12: Parameter mapping of the operation 'getOperationProfile'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
irpVersion	IN	irpVersionNumber	M
operationNameProfile	OUT	operationNameProfile	M
operationParameterProfile	OUT	operationParameterProfile	M
status	OUT	status	M

4.2.3.11 Parameter mapping of the operation 'getNotificationProfile'

Table 13: Parameter mapping of the operation 'getNotificationProfile'

IS Parameter Name	IN/OUT	CMIP SS Equivalent	Qualifier
irpVersion	IN	irpVersionNumber	M
notificationNameProfile	OUT	notificationNameProfile	M
notificationParameterProfile	OUT	notificationParameterProfile	M
status	OUT	status	M

4.2.4 Mapping of the notification header

The following table gives the mapping between the parameters of the notification header specified in 3GPP TS 32.302 [3] onto the M-EVENT-REPORT request parameters. The notification header contains those parameters that shall be present in every notification.

Table 15: Mapping of common notification parameters

IS Parameters of the Notification Header	M-EVENT-REPORT Request Parameters	Qualifier
(see note 1)	Invoke identifier	M
objectClass	Managed object class	M
objectInstance	Managed object instance	M
notificationId	(see note 2)	O
eventTime	Event time	M
systemDN	(see note 3)	--
notificationType	Event type	M
NOTE 1: There is no common parameter in IRP Notification that corresponds to Invoke Identifier defined in ITU-T Recommendation X.710 [5].		
NOTE 2: The common parameter NotificationId is mapped onto notificationIdentifier (ITU-T Recommendation X.721 [7] and X.733 [9]) which is no explicit M-EVENT-REPORT parameter. Instead, it is included in the M-EVENT-REPORT request parameter 'Event information'.		
NOTE 3: The common parameter SystemDN is conditional in 3GPP TS 32.302 [3] and is not used on the CMIP interfaces.		

5 GDMO definitions

5.1 Managed Object Classes

5.1.1 notificationControl

```
notificationControl MANAGED OBJECT CLASS
  DERIVED FROM
    "Rec. X.721 | ISO/IEC 10165-2 : 1992":top;
  CHARACTERIZED BY
    notificationControlBasicPackage,
    notificationIRPVersionPackage;
  CONDITIONAL PACKAGES
    notificationControlInfoPackage PRESENT IF "an instance supports it",
    notificationProfilePackage PRESENT IF "an instance supports it";

REGISTERED AS { ts32-304NotificationsObjectClass 1};
```

5.2 Packages

5.2.1 notificationControlBasicPackage

```
notificationControlBasicPackage PACKAGE
  BEHAVIOUR
    notificationControlBasicPackageBehaviour;
  ATTRIBUTES
    notificationControlId;
  REGISTERED AS {ts32-324Package 1};

notificationControlBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "An instance of the MOC notificationControl is identified by the value of the attribute notificationControlId.";
```

5.2.2 notificationControlInfoPackage

```
notificationControlInfoPackage PACKAGE
  BEHAVIOUR
    notificationControlInfoPackageBehaviour;
  ATTRIBUTES
    supportedNotificationCategories GET;
  ACTIONS
    getNotificationCategories;

REGISTERED AS { ts32-304NotificationsPackage 1};

notificationControlInfoPackageBehaviour BEHAVIOUR
DEFINED AS
  " The attribute supportedNotificationCategories indicates the categories of notifications supported by the current IRPAgent. The action getNotificationCategories provides the IRPManager with the capability to query the supported categories of notifications.";
```

5.2.3 notificationIRPVersionPackage

```
notificationIRPVersionPackage PACKAGE
  BEHAVIOUR
    notificationIRPVersionPackageBehaviour;
  ATTRIBUTES
    supportedNotificationIRPVersions GET;
  ACTIONS
    getNotificationIRPVersion;

REGISTERED AS { ts32-304NotificationsPackage 3};

notificationIRPVersionPackageBehaviour BEHAVIOUR
DEFINED AS
```

"This package has been defined to allow the IRPManager to get information about the Notification IRP versions supported by the IRPAgent.
The attribute *supportedNotificationIRPVersions* indicates all versions of the NotificationIRP currently supported by the IRPAgent.
The action *getNotificationIRPVersion* is invoked by the IRPManager to get information about the NotificationIRP versions supported by the IRPAgent.";

5.2.4 notificationProfilePackage

notificationProfilePackage **PACKAGE**

BEHAVIOUR

notificationProfilePackageBehaviour;

ACTIONS

getOperationProfile,
getNotificationProfile;

REGISTERED AS { ts32-304NotificationsPackage 4};

notificationProfilePackageBehaviour **BEHAVIOUR**

DEFINED AS

"This package has been defined to allow the IRPManager to get detailed information about the profile of Notification IRP.

The action *getOperationProfile* is invoked by the IRPManager to get detailed information about the operations supported by Notification IRP.

The action *getNotificationProfile* is invoked by the IRPManager to get detailed information about the notifications supported by Notification IRP.";

5.3 Actions

5.3.1 Void

5.3.2 getNotificationCategories (O)

getNotificationCategories **ACTION**

BEHAVIOUR

getNotificationCategoriesBehaviour;

MODE

CONFIRMED;

WITH REPLY SYNTAX

TS32-304TypeModule.GetNotificationCategoriesReply;

REGISTERED AS { ts32-304NotificationsAction 2};

getNotificationCategoriesBehaviour **BEHAVIOUR**

DEFINED AS

An IRPManager may invoke this action to query the categories of notifications supported by a concerned IRPAgent. This action is irrelevant to any subscriptions. An IRPManager may invoke this action before or after a subscription.

The 'Action response' is composed of the following data:

- notificationCategoryList

This parameter identifies a list of categories of notifications supported by the concerned IRPAgent. A list containing no element, i.e. a NULL list means that the IRPAgent does not support any category of notification.

- status
It contains the results of this action. Possible values: noError (0), error (the value indicates the reason of the error).";

5.3.3 getNotificationIRPVersion (M)

getNotificationIRPVersion **ACTION**

BEHAVIOUR

getNotificationIRPVersionBehaviour;

MODE

CONFIRMED;

WITH REPLY SYNTAX

TS32-304TypeModule.GetNotificationIRPVersionReply;

REGISTERED AS { ts32-304NotificationsAction 3};

getNotificationIRPVersionBehaviour **BEHAVIOUR**

DEFINED AS

"An IRPManager invokes this action to enquiry about the version of the Notification IRP the concerned IRPAgent supports.

The 'Action information' field contains no data:

The 'Action response' is composed of the following data:

- versionNumbersList
It contains a list of versions supported by the concerned IRPAgent which are backwards compatible. A list containing no element, i.e. a NULL list means that the concerned IRPAgent doesn't support any version of the Notification IRP.
- status
It contains the results of this action. Possible values: noError (0), error (the value indicates the reason of the error).";

5.3.4 getNotificationProfile (O)

getNotificationProfile **ACTION**

BEHAVIOUR

getNotificationProfileBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-304TypeModule.IRPVersionNumber;

WITH REPLY SYNTAX

TS32-304TypeModule.GetNotificationProfileReply;

REGISTERED AS { ts32-304NotificationsAction 4};

getNotificationProfileBehaviour **BEHAVIOUR**

DEFINED AS

"An IRPManager invokes this action to enquiry about the notification profile (supported notifications and supported parameters) for this specific Notification IRP version.

The 'Action information' contains the following data:

- irpVersionNumber
This mandatory parameter identifies a Notification IRP version.

The 'Action response' is composed of the following data:

- notificationNameProfile
It contains a list of notification names, i.e. a NULL list means that the Notification IRP doesn't support any notification.
- notificationParameterProfile.
It contains a set of elements, each element corresponds to a notification name and is composed by a set of parameter names.
- status
It contains the results of this action. Possible values: noError (0), error (the value indicates the reason of the error).";

5.3.5 getOperationProfile (O)

getOperationProfile **ACTION**

BEHAVIOUR

getOperationProfileBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-304TypeModule.IRPVersionNumber;

WITH REPLY SYNTAX

TS32-304TypeModule.GetOperationProfileReply;

REGISTERED AS { ts32-304NotificationsAction 5};

getOperationProfileBehaviour **BEHAVIOUR**

DEFINED AS

"An IRPManager invokes this action to enquiry about the operation profile (supported operations and supported parameters) for this specific Notification IRP version.

The 'Action information' contains the following data:

- irpVersionNumber
This mandatory parameter identifies a Notification IRP version.

The 'Action response' is composed of the following data:

- operationNameProfile
It contains a list of operation names.
- operationParameterProfile.

It contains a set of elements, each element corresponds to an operation name and is composed by a set of parameter names.

- **status**
It contains the results of this action. Possible values: noError (0), error (the value indicates the reason of the error).";

5.4 Attributes

5.4.1 notificationControlId

```
notificationControlId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-304TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    notificationControlIdBehaviour;

REGISTERED AS { ts32-304NotificationsAttribute 1};

notificationControlIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute names an instance of a notificationControl object class.";
```

5.4.2 supportedNotificationCategories

```
supportedNotificationCategories ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-304TypeModule.NotificationCategoryList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    supportedNotificationCategoriesBehaviour;

REGISTERED AS { ts32-304NotificationsAttribute 2};

supportedNotificationCategoriesBehaviour BEHAVIOUR
DEFINED AS
  "This attribute provides the information concerning the categories of notifications currently supported by the IRPAgent.";
```

5.4.3 supportedNotificationIRPVersions

```
supportedNotificationIRPVersions ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-304TypeModule.SupportedNotificationIRPVersions;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    supportedNotificationIRPVersionsBehaviour;

REGISTERED AS { ts32-304NotificationsAttribute 3};

supportedNotificationIRPVersionsBehaviour BEHAVIOUR
DEFINED AS
  "This attribute provides the information concerning the NotificationIRP versions currently supported by the IRPAgent.";
```

6 ASN.1 definitions

```
TS32-304TypeModule {itu-t(0) identified-organization(4) etsi(0) mobileDomain(0) umts-Operation-
Maintenance(3)
  ts-32-304(304) informationModel(0) asn1Module(2) version1(1)}
```

```
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
```

```
--EXPORTS everything
```

```

IMPORTS
Destination, DiscriminatorConstruct
FROM Attribute-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asnlModule(2) 1}
CMISFilter
FROM CMIP-1 {joint-iso-ccitt ms(9) cmip(1) modules(0) protocol(3)};

baseNodeUMTS                OBJECT IDENTIFIER ::= { itu-t (0) identified-organization (4)
                           etsi (0) mobileDomain (0) umts-Operation-Maintenance (3) }
ts32-304Prefix              OBJECT IDENTIFIER ::= { baseNodeUMTS ts-32-304(304)}
ts32-304InfoModel           OBJECT IDENTIFIER ::= { ts32-304Prefix informationModel(0)}

ts32-304NotificationsObjectClass OBJECT IDENTIFIER ::= { ts32-304InfoModel managedObjectClass(3)}
ts32-304NotificationsPackage OBJECT IDENTIFIER ::= { ts32-304InfoModel package(4)}
ts32-304NotificationsAttribute OBJECT IDENTIFIER ::= { ts32-304InfoModel attribute(7)}
ts32-304NotificationsAction  OBJECT IDENTIFIER ::= { ts32-304InfoModel action(9)}

-- Start of 3GPP SA5 own definitions

ErrorCauses ::= ENUMERATED
{
  noError (0), -- operation / notification successfully performed
  notificationIRPVersionNotSupported (3), -- Notification IRP version requested by NM not
  supported by IRPagent
  wrongFilter (4), -- the value of the filter parameter is not valid
  wrongDestination (5), -- the value of the destination parameter is not valid
  unspecifiedErrorReason (255) -- operation failed, specific error unknown
}

GeneralObjectId ::= INTEGER

GetNotificationCategoriesReply ::= SEQUENCE
{
  notificationCategoryList NotificationCategoryList,
  status ErrorCauses
}

GetNotificationIRPVersionReply ::= SEQUENCE
{
  versionNumbersList SupportedNotificationIRPVersions,
  status ErrorCauses
}

GetNotificationProfileReply ::= SEQUENCE
{
  notificationNameProfile NotificationList,
  notificationParameterProfile ParameterListOfList,
  status ErrorCauses
}

GetOperationProfileReply ::= SEQUENCE
{
  operationNameProfile OperationList,
  operationParameterProfileParameterListOfList,
  status ErrorCauses
}

IRPVersionNumber ::= GraphicString

NotificationCategory ::= ENUMERATED
{
  alarm (1), --the notification category defined in the alarm IRP
  basicCM (2), --the notification category defined in the basic CM IRP
  bulkCM (3), --the notification category defined in the bulk CM IRP
}

NotificationCategoryList ::= SET OF NotificationCategory

NotificationList ::= SET OF NotificationName

NotificationName ::= GraphicString

OperationList ::= SET OF OperationName

OperationName ::= GraphicString

ParameterList ::= SET OF ParameterName

```

```
ParameterListOfList ::= SET OF ParameterList
ParameterName ::= GraphicString
SupportedNotificationIRPVersions ::= SET OF IRPVersionNumber
END -- of TS32-304TypeModule
```

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010471	001	--	SupportedNotificationCategory syntax	4.0.0	4.1.0
Sep 2001	S_13	SP-010471	002	--	Introduction of conditional packages	4.0.0	4.1.0
Sep 2001	S_13	SP-010471	003	--	OID modified according to TS 32.304 new number	4.0.0	4.1.0
Dec 2001	S_14	SP-010653	004	--	Maximize the reuse of ITU-T CMIP event report management functions	4.1.0	5.0.0
Mar 2002	S_15	SP-020031	006	--	Correction of errors in the GDMO and ASN.1 definitions	5.0.0	5.1.0
Jun 2002	S_16	SP-020290	007	--	Correction of erroneous notification header mapping table	5.1.0	5.2.0
Jun 2002	S_16	SP-020290	008	--	Introduction of SS (32.304) to IS (32.302) relation and correction of Foreword	5.1.0	5.2.0
Dec 2002	--	--	--	--	Cosmetics	5.2.0	5.2.1
Mar 2004	S_23	SP-040105	--	--	Automatic upgrade to Rel-6 (no CR)	5.2.1	6.0.0