

BEFORE THE WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

No. TR-041112

RECEIVED
RECORDS MANAGEMENT

PETITION JUL -9 AM 9:10

Tacoma Rail

Petitioner

Road Name Main Street

vs.

W.U.T.C. Crossing No. 20J 18.60

City of Chehalis

Respondent

D.O.T. Crossing No. 396783S

Application is hereby made to the Washington Utilities and Transportation Commission for an order (check one or more of the following)

directing the _____ of a grade crossing;
(construction-reconstruction-relocation)

directing installation of automatic grade crossing signal or other warning device (other than crossbucks) at a new crossing;

directing Upgrades of warning devices at an existing crossings;
(replacement-change-upgrade)

allocating funds from the "grade crossing protective fund" for _____ of active warning devices;
_____ (installation and/or maintenance)

authorizing the construction of the project, funding to be pursuant to the Intermodal Surface Transportation Efficiency Act (ISTEA) in cooperation with the Washington State Department of Transportation Local Programs Division;

at the railroad grade crossing identified above and described in this petition. This application seeks the relief specified above by (check one of the following)

hearing and order

order without hearing

[] Has application for funding, pursuant to Intermodal Surface Transportation Efficiency Act been made to the Local Programs Division for this project?
Yes No

[] If the answer is yes to the question above, has the funding requested under the Intermodal Surface Transportation Efficiency Act been denied?
Yes No

I certify under penalty of perjury that the information provided in and with this petition is true and correct.

Chris Storey
Petitioner
Chris Storey Project Manager
Print Name Title
747 Market Street
Street Address
Tacoma, WA 98402-3769
City-State-Zip Code

INTERROGATORIES

Use additional paper as needed

[1]

State name of highway and railway at crossing intersection:

Existing or proposed highway N/A mile post N/A

Existing or proposed railway TRMW mile post 18.60

Located in ___ 1/4 of the NW 1/4 of Sec. 38 Twp. 14N Range 02W W.M.

WUTC crossing number 20J 18.60 DOT crossing number 396783S

Street Main Street City Chehalis County Lewis
(if applicable) (if applicable)

[2]

Character of crossing (indicate with X or numbers where applicable):

(a) Common Carrier Logging or Industrial

(b) Main Line Branch Line Siding or Spur

(c) Total number of tracks at crossing 1 (one)
(Note: A track separated 100 feet or more from another track constitutes a separate crossing.)

(d) Operating maximum train speed: Legal maximum train speed:
Passenger 20 MPH Passenger 20 MPH
Freight 20 MPH Freight 20 MPH

(e) Actual or estimated train traffic in 24 hours:
Passenger Trains 1 Freight Trains 1
(Note: Round trip counted as two trains. Include switch movements.)

[3]

Character of Roadway:

(a) State Highway - Classification _____

(b) County Highway - Classification _____

(c) City Street - Classification _____

(d) Number of traffic lanes existing in each direction: _____
Number of additional traffic lanes proposed: _____

(e) Posted vehicle speed limit: Automobiles _____ MPH Trucks _____ MPH

(f) Estimated vehicle traffic in 24 hours: Current total _____, including _____ trucks
and _____ school bus trips. Projected traffic in _____ years: total _____,
including _____ trucks and _____ school bus trips.

[4]

- (a) If temporary, state for what purpose crossing is to be used and for how long.

- (b) If temporary grade crossing, will you remove the crossing at completion of the activity requiring the temporary crossing?

[5]

- (a) State whether or not a safer location for a grade crossing exists within a reasonable distance in either direction from the proposed point of crossing, and if so, what reason, if any, why this safer location should not be adopted, even though in doing so, it may be necessary to relocate a portion of the highway or railway.

- (b) Are there any hillsides, earth, or other embankments, buildings, trees, orchards, side tracks (on which cars might be spotted), loading platforms, etc., in the vicinity not feasible to move, which may obstruct the view and which can be avoided by relocating the proposed crossing. Would it be practical to do so? Please describe.

[6]

- (a) Is it feasible to construct and use an over or under crossing at the intersection of said railway and highway? If not, state why.

- (b) Does the railway line at any point in the vicinity of the proposed crossing pass over a fill or trestle or through a cut where it is feasible to construct an under or over crossing, even though it may be necessary to relocate a portion of the highway to reach that point?

- (c) If a suitable place for an under - or over - crossing exists in the vicinity of the proposed crossing, state the distance and direction from the proposed crossing; the approximate cost of construction; and what, if any, reason exists why it should not be constructed.

[7]

- (a) State approximate distance to nearest public or private crossing in each direction of railroad involved herein.
- (b) If there is an existing crossing in near vicinity, or if more than one crossing is proposed, is it feasible to divert highways served and to be served by existing and proposed crossings, thus eliminating the need for more than once crossing?
- (c) If so, state approximate cost of highway relocation to effect such changes.
- (d) Will the proposed crossing eliminate the need for one or more existing crossings in the vicinity? If so, state direction and approximate distance to the crossing or crossings.
- (e) If this crossing is authorized, do you propose to close any existing crossing or crossings?

[8]

State the lengths of views which are now available along the line of railway to travelers on the highway when approaching the crossing from either side of the railway and when at points on the highway as follows:

Approaching crossing from.....(direction) an unobstructed view to

- right when on highway 300 feet from crossing of _____ feet
- right when on highway 200 feet from crossing of _____ feet
- right when on highway 100 feet from crossing of _____ feet
- right when on highway 50 feet from crossing of _____ feet
- right when on highway 25 feet from crossing of _____ feet
- left when on highway 300 feet from crossing of _____ feet
- left when on highway 200 feet from crossing of _____ feet
- left when on highway 100 feet from crossing of _____ feet
- left when on highway 50 feet from crossing of _____ feet
- left when on highway 25 feet from crossing of _____ feet

Approaching crossing from..... (opposite direction) an obstructed view to

- right when on highway 300 feet from crossing of _____ feet
- right when on highway 200 feet from crossing of _____ feet
- right when on highway 100 feet from crossing of _____ feet
- right when on highway 50 feet from crossing of _____ feet
- right when on highway 25 feet from crossing of _____ feet
- left when on highway 300 feet from crossing of _____ feet
- left when on highway 200 feet from crossing of _____ feet
- left when on highway 100 feet from crossing of _____ feet
- left when on highway 50 feet from crossing of _____ feet
- left when on highway 25 feet from crossing of _____ feet

[9]

Attach one or more prints showing a vicinity map and a layout of railway and highway, as well as profiles of each, also showing percent of grade, 500 feet of highway and railway when approaching crossing from all four directions. On the prints, spot and identify obstructions of view located in all four quadrants. Provide a traffic control layout showing the location of the existing and proposed signing of the intersection.

See attached map.

[10]

- (a) Is it feasible to provide a 25 foot level grade crossing on both sides from center line of railway at point of crossing?
- (b) If not, state in feet the length of level grade it is feasible to obtain.
- (c) Is it feasible to obtain an approach grade, prior to the level grade of five percent or less? If not, state why, and state the percent approach grade possible.

[11]

Do you know of any reason not appearing in any of the answers to these interrogatories why the proposed crossing should not be made at grade or at the point proposed by you? If so, please state same fully.

Interrogatories 12 and 13 are to be completed only if this petition involves installation, replacement or changing of automatic grade signal or other warning device, other than sawbucks.

[12]

- (a) State in detail, the number and type of automatic signals or other warning devices (other than sawbucks) proposed to be installed. (This portion should be filled in only after conference between the railroad and the petitioning local governmental agency.)
- (b) State an estimate of the cost for installing the signals or other devices proposed, as obtained from the respondent railroad company. . . **\$ 59,325.00**
- (c) State a cost estimate for maintaining the signals or devices for 12 months, as obtained from the respondent railroad company . . . **\$ 2,100.00**
- (d) If this is an existing crossing, what will the proposed warning devices replace in the way of existing devices? **Replace existing cantilever-mounted signals and bungalow with: new cantilever-mounted signals with 12" LED-type lights, signal bungalow, and insulated joints.**
- (e) As the petitioner, are you prepared to pay or will you promise to pay to the respondent railroad company, your share of the cost of installing the warning devices proposed as provided by law?

Yes No

[13]

Furnish a brief statement of why the public safety requires the installation of the automatic signals or the devices as proposed. **Tacoma Rail strongly recommends upgrading this intersection along the Mountain Division Rail Line, in Lewis County. This intersection has equipment that is out of date, which slows freight traffic and puts the general public at risk. Upgrades to this intersection will both increase train speeds and public safety**