BEFORE THE

WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION

WASHINGTON UTILITIES AND TRANSPORTATION COMMISSION,))) DOCKET NOS. UE-140188 and
Complainant,) UG-140189 (Consolidated)
)
v.)
)
AVISTA CORPORATION, DBA)
AVISTA UTILITIES,)
)
Respondent.)
-)

RESPONSE TESTIMONY OF ROBERT R. STEPHENS

ON BEHALF OF

THE INDUSTRIAL CUSTOMERS OF NORTHWEST UTILITIES

July 22, 2014

TABLE OF CONTENTS

Page

UMMARY
LECTRIC COST OF SERVICE STUDY
Overview3Review of Avista's Cost of Service Study6Allocation of Production-Related Costs7Allocation of Transmission Costs18Overall Cost of Service Results22
LECTRIC REVENUE ALLOCATION ("RATE SPREAD")
LECTRIC RATE DESIGN
xhibit No. (RRS-2): Qualifications of Robert R. Stephens
xhibit No(RRS-3): Monthly Peak Demands as a Percent of the Annual System Peak
xhibit No(RRS-4): Allocation of System Peak Day Capacity
xhibit No(RRS-5): Production-Related Costs Allocated Using a 4 CP Method
xhibit No(RRS-6): Production-Related Costs Allocated Using a 4 CP Method (Peak Credit)
xhibit No(RRS-7): Section 34 of Avista's Open Access Transmission Tariff
xhibit No(RRS-8): Modifications for Production-Related Cost Allocation & Transmission Cost Allocation

1 Q. PLEASE STATE YOUR NAME AND BUSINESS ADDRESS.

- 2 A. Robert R. Stephens. My business address is 16690 Swingley Ridge Road, Suite 140,
- 3 Chesterfield, MO 63017.

4 Q. WHAT IS YOUR OCCUPATION?

- 5 A. I am a consultant in the field of public utility regulation and a Principal of Brubaker &
- 6 Associates, Inc., energy, economic and regulatory consultants.

7 Q. PLEASE DESCRIBE YOUR EDUCATIONAL BACKGROUND AND 8 EXPERIENCE.

9 A. These are set forth in Exhibit No. (RRS-2).

10 Q. ON WHOSE BEHALF ARE YOU APPEARING IN THIS PROCEEDING?

- 11 A. I am appearing on behalf of the Industrial Customers of Northwest Utilities ("ICNU"),
- 12 an association of large industrial businesses, some of whom are customers of Avista
- 13 Corporation ("Avista" or the "Company").

14 Q. WHAT IS THE PURPOSE OF YOUR RESPONSE TESTIMONY?

- A. I will address Avista's electric cost of service study, revenue allocation ("rate spread"), and rate design issues. More specifically, with respect to cost of service, I
 will address alternatives to Avista's allocators for production-related costs and for transmission costs. I will also address Avista's rate spread proposal for a uniform percentage increase to the rate schedules, and its proposals for rate design, including Avista's decoupling proposal.
- The fact that I do not address any particular issue should not be interpreted as
 tacit approval of any position taken by Avista.

1		I. SUMMARY
2	Q.	PLEASE SUMMARIZE YOUR RECOMMENDATIONS.
3	A.	My response testimony can be summarized as follows:
4 5 6 7 8 9		1. The Company's electric cost of service study filed in this case is, in many respects, consistent with studies filed by Avista in the past. However, I have identified two significant changes that should be made in order for the cost of service study to more accurately measure the cost causation incurred by the various customer rate schedules. These relate to the classification and allocation of production costs and the allocation of transmission costs.
10 11 12 13 14 15 16		2. With respect to the classification and allocation of production plant costs, I discuss the significant shortcomings of the "Peak Credit" classification and recommend that it be discontinued. My recommendation is for production fixed costs to be allocated in a more traditional demand approach. If the Washington Utilities and Transportation Commission (the "Commission") decides to retain the Peak Credit classification approach, I strongly recommend that the demand allocator be modified to more accurately address capacity cost causation.
17 18 19 20 21 22		3. Whether or not the Peak Credit is retained, I recommend use of the 4 Coincident Peaks ("CP") as a better measure of the demand component for allocating production costs than Avista's proposed 12 CP measure, since Avista's load exhibits significant peaks. This allocator is also more strongly supported in the National Association of Regulatory Utility Commissioners ("NARUC") Electric Utility Cost Allocation Manual ("NARUC Manual").
23 24 25		4. With respect to transmission system costs, I recommend use of the 12 CP demand allocation method rather than the Peak Credit method. 12 CP is a better measure of cost causation and is more consistent with industry norms.
26 27 28		5. Adjustment on these two allocation issues reveals significant class cost differences from the results of the Avista cost study. The differences are summarized and shown for each class rate schedule herein.
29 30 31 32 33		6. Regarding rate spread, I support Avista's proposed uniform percentage increase, if Avista's full revenue requirement is approved. If Avista does not receive its requested revenue requirement, then the reduction should flow to the rate schedules other than Schedule 1, since it is currently paying revenues well below its cost of service.
34 35 36 37		7. I do not support Avista's proposal for revenue decoupling for Schedule 25. Nevertheless, if the Commission adopts some form of adjustment, a better approach to provide revenue stabilization would be through increasing the demand charges, offset by decreased energy charges.

1

II. ELECTRIC COST OF SERVICE STUDY

2 Overview

Q. PLEASE EXPLAIN THE BASIC STEPS FOR ESTABLISHMENT OF FAIR AND REASONABLE RATES?

5 The ratemaking process has three steps. First, we must determine the utility's total A. 6 revenue requirement and whether an increase or decrease in revenues is necessary. 7 Second, we must determine how the revenues are to be distributed among the various 8 customer classes or schedules. A determination of how many dollars of revenue 9 should be produced by each class is essential to obtaining the appropriate level of 10 rates. This is called "revenue allocation" or "rate spread." Finally, individual tariffs 11 must be designed to produce the required amount of revenues from each class of 12 service and to send efficient price signals to customers.

13 The guiding principle at each step should be cost of service. In the first step – 14 determining revenue requirements – it is widely agreed that the utility is entitled to a 15 revenue increase only to the extent that its actual overall cost of service has increased. 16 If current rate levels exceed the revenue requirement, a rate reduction is required. In 17 short, rate revenues should equal a utility's actual cost of service. The same principle 18 should apply in the last two steps. Each customer class should, to the extent 19 practicable, produce revenues equal to the cost of serving that particular class. On 20 some occasions, this may require a rate increase for some customer classes and a rate 21 decrease for others. The standard tool for determining whether a class requires a rate 22 increase or decrease is an embedded class cost of service ("ECOS") study, which 23 shows the rate of return for each class of service. Ideally, rate levels should be 24 modified so that each customer class provides approximately the same rate of return.

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

Finally, in designing individual tariffs, the goal is to base the rate design on the cost of service, so that each customer's rate tracks, to the extent practicable, the utility's cost of providing that service to the customers on the tariff.

4 5 **O**.

HOW ARE LARGE INDUSTRIAL CUSTOMERS AFFECTED BY THE PRICE OF ENERGY?

A. For many industrial customers, energy is a primary component of their costs. For
some, it may be the most critical component. As such, rate stability and overall cost of
electricity prices are vital to the economic health of large commercial and industrial
customers in Washington – and to the economic health of Washington itself, as
Washington industries compete in national and world markets. Furthermore, any cost
of service study or rate design that misallocates costs to large customers will also
result in unjust and unreasonable rates.

13 Q. WHAT IS THE BASIC PURPOSE OF AN ECOS STUDY?

A. The basic purpose of an ECOS study is an empirical determination of the cost of
serving classes of customers.

16 After determining the overall cost of service or revenue requirement, an ECOS 17 study is used to ascertain the cost of service among customer classes (i.e., a cost of 18 service study shows how each customer class contributes to the total system cost). For 19 example, when a class produces the same rate of return as the total system, it is 20 returning to the utility revenues sufficient to cover the costs incurred in serving it 21 (including a reasonable authorized return on investment). If a class produces a below-22 average rate of return, it may be concluded that the revenues are insufficient to cover 23 all relevant costs. On the other hand, if a class produces a rate of return above the 24 average, it is paying revenues sufficient to cover the cost attributable to it and, in

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

addition, is paying part of the cost attributable to other classes who produce a below
 average rate of return. The ECOS study is important because it shows the class
 revenue requirement as well as the rate of return under current and any proposed rates.

As a measurement or estimation tool, the ECOS study is not the step in which other factors, such as rate moderation or continuity, should be considered or allowed to influence the results. Those types of considerations are taken up in the revenue allocation and rate design steps.

8 Q. PLEASE COMMENT ON THE PROPER FUNDAMENTALS OF AN ECOS 9 STUDY.

10 Α. In all ECOS studies, certain fundamental concepts should be recognized. Of primary 11 importance among these concepts is the functionalization of costs, as well as the 12 classification of the nature of these costs as to whether they vary with the quantity of 13 energy consumed, the demand placed upon the system, or the number of customers 14 Stated another way, functionalization is the classification and being served. 15 arrangement of costs according to major functions, such as production, transmission, and distribution. 16

17 Fixed costs are those costs which tend to remain constant over the short run 18 irrespective of changes in output and are generally considered to be demand-related. 19 Fixed costs include those costs which are a function of the size of the investment in 20 utility facilities, and those costs necessary to keep the facilities "on-line." Variable 21 costs, on the other hand, are those costs which tend to vary with output and are 22 generally considered to be commodity-related. Customer-related costs are those 23 which are closely related to the number of customers served, rather than the quantity 24 of energy consumed or the peak demands placed upon the system. An understanding

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

of these concepts is essential to development of ECOS studies, as well as appropriate
 rate design.

3 Review of Avista's Cost of Service Study

4 Q. HAVE YOU REVIEWED THE COMPANY'S ECOS STUDY?

5 A. Yes. I have reviewed the Company's ECOS study that was submitted as part of 6 Avista witness Tara Knox's direct testimony in this case.^{1/}

Q. IS THE COMPANY'S ECOS STUDY REASONABLE TO USE AS A BASIS FOR REVENUE ALLOCATION AND RATE DESIGN IN THIS CASE?

A. Not entirely. The ECOS study filed in this case is, in many respects, consistent with
studies filed by Avista in the past and is reasonable in certain ways. However, I have
serious concerns with two aspects of its study. First, the study classifies production
plant investment to the customer classes using a method that is based only in small
part (31%) on the customers' contribution to peak demand for each month of the year
and in much larger part (69%) on the basis of energy.^{2/}

15 This method is improper because the allocated plant investments include the 16 cost of all production resources, and are dependent on the maximum capacities of 17 those resources. Instead, production costs should be allocated to the customer classes 18 according to each class's demand during the peak months, when all of Avista's 19 production resources are in use, and when those resources are most likely to be 20 operating at their maximum capacities. It is Avista's system peak demands, which 21 occur during winter and summer months, that drive the need for additional capacity. 22 Demands during moderate-load times, whether time of day or month of year, do not

^{2/} <u>Id.</u> at 15.

 $[\]frac{1}{2}$ Exh. No. ___(TLK-1T).

cause new generating capacity to be built. Energy allocators should be used only on
 variable costs, i.e., those which vary with the level of output of the units, such as fuel.
 Second, in addition to its misallocation of production costs, the Company's

4 ECOS study also improperly allocates the costs of transmission.

5 Alloca

Allocation of Production-Related Costs

6 Q. HOW HAS THE COMPANY ALLOCATED PRODUCTION-RELATED 7 COSTS?

8 A. The Company's process is described at pages 12-15 of Avista witness Knox's direct
9 testimony, and in additional detail at pages 3-4 of Exhibit No. (TLK-3).

10 As described, Avista proposes to use the "Peak Credit" ratio to classify 11 production and transmission resources. According to Ms. Knox, Avista proposes a 12 modification to a prior application of the Peak Credit measure, used prior to 2010, to 13 one which utilizes the system load factor to determine the proportion of the production 14 function that is demand-related. This modification yields a 31.27% proportion to be 15 allocated on the basis of demand, with the remaining 68.73% to be allocated based on 16 energy delivered. Avista performs this classification for both production fixed and 17 variable costs and, as described below, to transmission plant. For the approximately 18 31% of costs that are classified as demand-related, Avista proposes to allocate on the 19 basis of 12 CP, based on the average class contributions to the 12 monthly peaks for 20 the year ended June 30, 2013.

Q. SETTING ASIDE THE VALIDITY OF THE PEAK CREDIT FOR THE MOMENT, WHY HAS AVISTA USED THE 12 CP METHOD TO ALLOCATE THE PRODUCTION COSTS IN ITS ECOS STUDY?

24 A. Avista witness Knox states as follows:

1Although the Company is usually a winter peaking utility, it2experiences high summer peaks and careful management of capacity3requirements is required throughout the year. The use of the average of4twelve monthly peaks recognizes that customer capacity needs are not5limited to the heating season. $\frac{3}{4}$

6

Q. DO YOU FIND THIS EXPLANATION COMPELLING?

7 A. No, I do not. As I will explain further, Avista demonstrates significant peaks, 8 especially in the winter; although in 2012, Avista experienced two high demand 9 months in the summer (which are included in the test year). A 12 CP method is more 10 typically used when demands are relatively steady over the course of a year and do not 11 exhibit significant peaks, which drive the need for new capacity. In addition, when 12 12 CP is used, it is typically when all production plant costs are allocated on the basis of 13 demand, rather than when only a relatively small proportion (31%) is allocated on 14 demand.

15Q.IS AVISTA'S USE OF 12 CP IN THIS MANNER WELL SUPPORTED IN16INDUSTRY LITERATURE, SUCH AS THE NARUC MANUAL?

A. No. Although I have not conducted an exhaustive search for corroboration of Avista's method in industry literature, thus far, I have seen no specific support for the method.
Rather, I find greater support for a more direct measure of system peak in the NARUC Manual, which lists the 12 CP method as one of the options for production allocation, but not in conjunction with a Peak Credit classification approach.
However, the same passage of the NARUC Manual that addresses the 12 CP

- 23 method casts doubt on its use for Avista, when it states of the 12 CP method: "This
- 24 method is usually used when the monthly peaks lie within a narrow range; i.e., when

^{3/} Exh. No. ___(TLK-3T) at 3.

the annual load shape is not spiky."^{4/} While the NARUC Manual does not define the
word "spiky," it is clear that in cases where the need for production capacity (i.e.,
system demand) is substantially different across the months of the year, a 12 CP
allocator is not appropriate.

Additional guidance is provided in the NARUC Manual where it describes
conditions wherein multiple coincident peak demands may be warranted. In
describing one of those conditions, the NARUC Manual states: "Criteria for
determining which hours to use include: (1) all hours of the year with demands within
<u>5 percent or 10 percent</u> of the system's peak demand."^{5/}

10 By considering only the hourly demands that are reasonably close to the annual 11 system peak, the cost analyst recognizes that it is only during the highest system load 12 hours that production capacity is most likely to be fully utilized. Consequently, a 13 demand allocation method that is based on each class's contribution during these high 14 demand periods will fairly and reasonably recognize the classes' proportionate 15 responsibility in causing the utility to incur those production investments. Therefore, in cases where the monthly peak loads fluctuate significantly (e.g., like the nearly 38% 16 fluctuation in peak load in Avista's case), $\frac{6}{2}$ a method that considers only the annual 17 18 system peak, or the average of monthly peaks that are near the system peak, is more 19 appropriate.

20

21

Another instructive allocation method from the NARUC Manual is the "summer and winter peak method" which is used to "reflect the effect of two distinct

 $[\]frac{4}{2}$ NARUC Manual at 46.

 $[\]frac{5}{6}$ <u>Id.</u> (emphasis added).

² The highest peak month, July, is nearly 38% higher than the lowest peak month, September.

seasonal peaks on customer cost assignment."¹/₂ The NARUC Manual states: "If the
 summer and winter peaks are close in value, and if both significantly affect the
 utility's generation expansion planning, this approach may be appropriate."⁸/

As I will demonstrate below, during the test year, Avista exhibited the summer
and winter peak conditions described above. Under the summer and winter peak
method, either the single highest summer and single highest winter peaks are used
(i.e., 2 CP) or a small number of summer and winter peak hours are used (i.e., 4 CP).

8 To summarize, when monthly peak demands are quite similar during the entire 9 year, a 12 CP method may be supported by industry literature. But when, as here, a 10 substantial variation in peak demands is seen throughout the year, there is more 11 support for production plant allocation based only on those peaks within a narrow 12 range of the highest peak, or on the summer and winter peaks only.

Q. WHY ARE THE CUSTOMER LOADS DURING THE HIGHEST MONTHLY PEAK DEMANDS RELEVANT TO THE ALLOCATION OF PRODUCTION INVESTMENT?

16 A. The key factors that link customer loads at the time of the highest monthly peak

- 17 demand to the allocation of production investments are the following:
- Utilities typically bring all of their generating resources into operation in the hours leading up to their highest monthly peaks. This includes the base load, intermediate load and peaking plants, as well as the short-term and long-term power purchasing contracts. For many utilities in the United States, these peaks occur during the summer season. Avista exhibits peaks in both summer and winter.
- 24
 2. The production costs that are allocated include the cost of base load, intermediate
 load and peaking plants, as well as the costs of short-term and long-term power
 purchase contracts.

 $[\]frac{1}{2}$ NARUC Manual at 45.

<u>8/</u> <u>Id.</u>

13. The portion of the utility's highest monthly demand that is contributed by a2customer class will provide a fair representation of the portion of production cost3that the utility incurred to serve the class. For example, if a class constitutes 10%4of the load at the times of system peak, it essentially represents 10% of the need5for generation capacity and, thus, should be allocated 10% of production capacity6costs.

7Q.HAVE YOU HAD AN OPPORTUNITY TO REVIEW AVISTA'S8HISTORICAL SYSTEM PEAK LOAD DATA?

9	А.	Yes. These load data are available in Avista's annual Federal Energy Regulatory
10		Commission ("FERC") Form 1 filings. Charts of the historical load data for the last
11		six calendar years are shown on Exhibit(RRS-3). These charts clearly indicate a
12		dominant winter peak and, in 2012 (only), two high summer peak months. In 2013,
13		only the monthly peak demands during January and July were within 10% of the
14		December peak. ^{9/}

Table 1, below, summarizes the number of months in each of the last six
calendar years that were within 5% and 10% of the system peak.

 $^{^{9/}}$ In Exh. No.___(RRS-3), months within 5% of the peak (inclusive) are shown in red and months between 5% and 10% lower than the peak are shown in gray.

TABLE 1				
Number of Months In Which Peak Demands Were Near Annual Peak Demands				
Year	Within 5% of Peak	Within 10% of Peak		
2008	0	1		
2009	1	2		
2010	0	3		
2011	1	3		
2012	2	5		
2013	0	2		
Test Year	2	4		

1 As can be seen from Table 1, Avista has peak demands that are within 10% of 2 the system peak in relatively few months each year, and even fewer are within 5% of 3 the peak.


4 Based on the excerpt from the NARUC Manual regarding the selection of 5 multiple coincident peaks, applied to the test year peak data, a 3 CP allocation method would reflect the number of monthly peaks within 5% of the annual peak (inclusive). 6 7 A 5 CP allocation method would reflect the number of monthly peaks within 10% of 8 the annual peak (inclusive). However, 2013 is somewhat anomalous as it actually had 9 no months within 5% of the peak and only two months within 10%. A 4 CP allocator, 10 which is often supported for allocating fixed production costs, would be reasonable (if 11 not conservative) in this case. A 4 CP allocator would include July, August, December and January and, thus, would also match and equally represent the summer 12 13 and winter peaks exhibited by Avista's customers. This allocation method finds 14 greater support in the NARUC Manual than does the 12 CP methodology used by 15 Avista, as discussed previously.

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

1 The Company's peak demands during the other months are forecast to be 2 significantly lower than those that occur during the summer and winter peak months. 3 Therefore, in my opinion and based on the criteria stated in the NARUC Manual, the 4 12 CP method simply is <u>not</u> justified as the best demand allocator for the Avista 5 system, and a 4 CP method should be used.

6 Q. CAN YOU ILLUSTRATE THE DIFFERING CUSTOMER PROPORTIONS 7 OF SYSTEM LOAD DURING PEAK MONTHS, AS OPPOSED TO 8 NON-PEAK MONTHS?

9 A. Yes. Figure 1 below shows the major Avista customer schedules' contribution to peak
10 load during the Company's extreme (i.e., highest and lowest), demand months of July
11 and September, when its test year system loads are at the maximum and minimum,
12 respectively.





13

14

As can be seen from Figure 1, peak loads of Schedule 1 and Schedule 11/12 customer classes are much higher in July than in September, undoubtedly due

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

primarily to air conditioning, while Schedules 21/22 and 25 are relatively
 unchanged/flat, in July and September. It is these additional loads of the Schedule 1
 and Schedule 11/12 customers that drive the peak loads of Avista and the need for
 generating capacity.

5Q.PLEASECOMMENTONTHEPEAKCREDITMETHODOF6CLASSIFICATION OF PRODUCTION COSTS.

7 I do not agree with the Peak Credit method used to classify production costs between Α. 8 demand and energy components, as proposed by Avista. This approach is more 9 commonly referred to as the "peak and average demand" method and is given little 10 discussion in the NARUC Manual. While I do not have the complete history of its use 11 in Avista cases, typically the use of this type of method for classification or allocation 12 of production costs is based on a perceived trade-off between capacity investment and 13 fuel savings. In my opinion, this classification inappropriately assigns far too much 14 weight to energy usage as a basis for assigning production costs.

15 In considering how Avista classifies and allocates production plant, and 16 considering the peak demands of the various rate schedules, it is clear that not enough 17 production capacity is assigned to some of the rate schedules and too much is allocated to others. This is illustrated in Exhibit No. ____(RRS-4) which shows the 18 equivalent amount of capacity allocated to customer rate schedules, as compared to 19 their peak demands.^{10/} As shown in this exhibit, Schedule 25 is allocated considerably 20 21 more capacity than its peak demand warrants, while Schedule 1, for example, is not 22 assigned enough capacity to meet its capacity needs. Figure 1 below graphically

 $[\]frac{10}{10}$ For peak demands, I have utilized the average of the 4 CP, as discussed above. Had I used the actual peak or the single CP, the results shown would have been even more dramatic.

depicts the results of Exhibit No. ___(RRS-4). This highlights a major weakness of 1

2 the Peak Credit method.




Figure 2

WHAT CLASSIFICATION OR ALLOCATION METHODOLOGY DO YOU 4 Q. 5 **RECOMMEND FOR PRODUCTION INVESTMENT IN THIS CASE?**

6 A. Because production investment is primarily due to the need for and the size of the 7 peak demands of customers, it should be assigned to customer classes exclusively, or 8 at least primarily, on those classes' contribution to utility system peaks. Allocation by 9 this method has widespread support in the industry and is, in my view, a better 10 reflection of cost causation than allocation methods that utilize energy usage to any 11 significant degree. Furthermore, even when energy usage (as measured by average

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

3

demand) is utilized, a far more appropriate and typical approach is the "average and
 excess demand" method.^{11/}

However, I am advised that the Peak Credit method has been used for Avista for some time. Assuming the Commission is not constrained to utilize the peak credit method due to its prior use, I recommend it not be used in this case. On the other hand, if the Commission is constrained to utilize the peak credit method, I recommend that it be refined in its application.

8 Q. IF THE PEAK CREDIT CLASSIFICATION IS ADOPTED, HOW WOULD 9 YOU RECOMMEND THAT THE APPROACH BE REFINED?

10 A. In that case, the heavy reliance on energy usage in assigning costs (69%) highlights 11 the critical need to refine the demand allocator used for capacity costs. As mentioned, 12 the Avista electric system exhibits a predominant winter peak and, recently, summer 13 peak. Therefore, any method of cost allocation that considers loads in hours that do not contribute to the need for new generation, or any energy-based method, $\frac{12}{}$ does not 14 15 adequately account for the dominant system peaks, fails to reflect the actual load 16 characteristics of the Avista system, and fails to properly reflect class responsibility 17 for production investment. Thus, for Avista, a 4 CP is a more appropriate allocation 18 method for demand-related production costs. This is true in the context of a full 19 allocation of production investment or as used in conjunction with the Peak Credit 20 classification approach.

^{11/} <u>See NARUC Manual at 49-52.</u>

¹²Similarly, allocating costs on average demand is mathematically equivalent to a kWh allocation and ignores the distinctions between peak period usage and off-peak period usage.

1Q.HAVE YOU CALCULATED THE 4 CP ALLOCATION FACTORS2NECESSARY TO APPROPRIATELY ALLOCATE DEMAND-RELATED3PRODUCTION COSTS IN AVISTA'S ECOS STUDY?

4 A. Yes. These allocation factors, along with Avista's proposed 12 CP allocation factors,

5 are shown in Table 2, for each of the Avista rate schedules in the ECOS study, and

6 allow for ready comparison across the allocation methods.

TABLE 2				
Production Allocation Comparison				
<u>Class</u>	<u>4 CP</u>	<u>12 CP</u>		
Sch 1	51.99%	48.71%		
Sch 11/12	8.83%	8.38%		
Sch 21/22	22.65%	24.40%		
Sch 25	14.50%	16.27%		
Sch 31/32	1.69%	1.97%		
Sch 41/49	0.33%	0.27%		
Total	100.00%	100.00%		

7 Q. HAVE YOU MODIFIED THE AVISTA ECOS STUDY SO THAT 8 PRODUCTION-RELATED COSTS ARE USING YOUR ALLOCATED 9 **RECOMMENDED 4 CP RATHER THAN THE 12 CP METHOD?**

10 A. Yes. I have calculated the ECOS study for the recommended 4 CP demand allocation 11 method under both a 100% demand allocation of production capacity costs, and in the 12 context of Avista's Peak Credit classification (31% demand, 69% energy). For the 13 100% demand 4 CP allocation, I calculate the ECOS results if the peak credit method 14 for classification is not used at all and, instead, production fixed costs are allocated on 15 the basis of 4 CP demand alone. Disuse of the peak credit method altogether will 16 require some modifications to the allocation of production variable costs and 17 transmission costs. For simplicity, I have used a 100% energy allocator for variable

Response Testimony Robert R. Stephens

Docket Nos. UE-140188 and UG-140189 (Consolidated)

production costs, and a 100% 12 CP allocator for transmission costs. This treatment of transmission costs will be discussed further in the next section. The results of this allocation method are shown in Exhibit No. ____(RRS-5). As shown, for some rate schedules, the change in production cost allocator makes a significant difference in the cost of service.

6 I have also modified the Avista ECOS study to adopt a 4 CP demand measure 7 in the context of the Peak Credit classification approach, should the Commission 8 utilize that method. For this version of the ECOS study no other changes were made 9 as compared to Avista's proposed study. The results of this modification are shown in 10 Exhibit No. __(RRS-6). As with my primary recalculation shown in Exhibit No. 11 __(RRS-5), the change in the demand measure makes a significant difference in the 12 schedules' overall cost of service.

13 Q. ARE THERE OTHER METHODOLOGIES TO CONSIDER HERE?

A. Potentially, other parties may recommend a new look at the methodologies used in
 allocating costs among customer classes. I will review those and comment in the
 cross-answering testimony.

17Q.SHOULD THE COMMISSION RETAIN PRODUCTION COSTS, IS EXHIBIT18_____(RRS-6) YOUR RECOMMENDED ECOS STUDY RESULT?

A. No, not quite. I do not recommend that transmission costs be classified according to
 the peak credit method under any circumstance, as I will discuss below.

21 Allocation of Transmission Costs

22 Q. HOW DOES AVISTA ALLOCATE TRANSMISSION COSTS IN ITS ECOS 23 STUDY?

24 A. It uses the same peak credit methodology as is used for classifying production costs.

Response Testimony Robert R. StephensExhibit No.__(RRS-1T)Docket Nos. UE-140188 and UG-140189 (Consolidated)Page 18

1Q.WHAT IS THE COMPANY'S RATIONALE FOR ALLOCATING2TRANSMISSION COSTS IN THIS MANNER?

3	А.	My review of Company witness Knox's direct testimony in this case reveals very little
4		support for this method. First, Ms. Knox states: "In Washington, transmission costs
5		have traditionally been treated as an extension of the generation system, therefore, the
6		revised peak credit ratio has also been applied to transmission costs in this study." ^{13/}
7		Ms. Knox also states:
8		The Peak Credit method acknowledges that all energy production costs
9		contain both capacity and energy components as they provide energy
10		throughout the year as well as capacity during system peaks. Likewise,
11		the transmission system is built not only for peak use, but also for
12		everyday delivery of energy. ^{14/}

13Q.HOW DO YOU RESPOND TO MS. KNOX'S STATED RATIONALE IN THIS14REGARD?

15 A. I do not believe it is sufficient to justify this unusual allocation of transmission costs.

16 Q. WHY DO YOU BELIEVE THIS ALLOCATION METHOD IS UNUSUAL?

- 17 A. I am not aware of any case outside of Washington where a utility has classified or
- 18 allocated transmission costs on the basis of energy to <u>any</u> degree. I see no justification
- 19 for allocating transmission costs in this manner.

20Q.WHY DO YOU BELIEVE THERE IS NO JUSTIFICATION FOR UTILIZING21AN ENERGY COMPONENT IN CLASSIFYING OR ALLOCATING22TRANSMISSION COSTS?

- 23 A. Unlike production, where parties sometimes claim there is a trade-off between fixed
- 24 and variable costs that justify an energy component in the allocation to reflect
- 25 cost-causation, there is not even an arguable trade-off for transmission facilities.

^{13/} Exh. No. ___(TLK-1T) at 14.

^{14/} Exh. No. ___(TLK-3) at 3.

1 I can illustrate this through a simple hypothetical. If a utility were to build a 2 1,000 MW generating unit in an area that is not adjacent to transmission facilities, 3 additional transmission facilities would need to be constructed to connect the 4 generating unit to the electrical grid. The capacity of the new transmission facilities 5 would need to be designed to carry the maximum output of the generating unit. The 6 capacity of those new transmission facilities is not dependent on the fuel type or 7 economics of the generating unit being constructed or how often it is run. Said 8 another way, essentially the same transmission facilities would need to be built 9 whether the 1,000 MW unit is a nuclear power plant, with a very high capacity factor 10 producing 7.9 million MWh/year, or a natural gas-fired peaking plant with a much lower capacity factor producing 4.4 million MWh/year. The transmission facilities 11 12 would be designed and constructed to meet the maximum capacity (1,000 MW) 13 required over the lines.

14 Similarly, increased or decreased utilization of the transmission system, once it 15 is built, does not impact the costs of the transmission assets. For example, higher 16 cumulative energy flow without an increase in demand does not impact transmission 17 costs. In addition, the vast majority of transmission costs are fixed, not variable. For 18 these reasons, an energy allocation of transmission costs is not justified.

19 20

Q. HAS THE COMPANY CONFIRMED THAT ITS TRANSMISSION SYSTEM IS CONSTRUCTED TO MEET THE PEAK DEMAND OF ITS CUSTOMERS?

21 A. Yes. Company witness Patrick Ehrbar states exactly that.^{15/} He makes no mention of 22 energy usage as a causal component in this regard. Further, my review of Avista's

^{15/} Exh. No. ___(PDE-1T) at 14.

Transmission Planning Standards, Policies and Procedures reveals no reliance on
 energy flow as a planning criterion.

Q. ARE THERE OTHER REASONS FOR NOT UTILIZING THE PEAK CREDIT METHOD FOR ALLOCATING TRANSMISSION COSTS?

A. Yes, there are. In providing guidance to utilities in billing for network transmission
service, FERC utilizes 12 CP, without regard to the amount of energy flowed across
the lines over time.^{16/} Further, in billing for transmission service, Avista itself utilizes
a 12 CP billing method for network transmission service as specified in Sections 34.1
and 34.2 of Avista's Open Access Transmission Tariff. A copy of Section 34 of that
tariff is attached as Exhibit No. (RRS-7).

Q. BESIDES 12 CP, ARE THERE ANY OTHER REASONABLE OPTIONS FOR ALLOCATION OF TRANSMISSION COSTS?

13 Yes, considering that the transmission system is built to meet the peak demands on the Α. 14 system (as opposed to times of relatively low demands), it would not be unreasonable 15 to use a 1 CP or 4 CP measure given Avista's annual load shape showing some 16 monthly peak demands to be far (38%) below the annual peak. Indeed, some Regional 17 Transmission Organizations effectively use a 1 CP or 5 CP for billing for transmission 18 service. However, although 12 CP may not be the truest measure of cost-causation, as 19 it overemphasizes demands in non-peak seasons, given its widespread use by other 20 utilities around the country and by FERC, it is reasonable (though conservative) for 21 use in this case.

 $[\]frac{16}{2}$ Generally, FERC Orders 888 and 889 dealt with these matters.

1 Q. WHAT IS YOUR RECOMMENDATION?

- 2 A. I recommend that transmission system costs not utilize the peak credit method at all.
- 3 Rather, the 12 CP demand measure should be used for 100% allocation of
- 4 transmission costs.

3.

5 Q. CAN YOU PROVIDE A COMPARISON OF THE TRANSMISSION 6 ALLOCATION FACTORS THAT YOU RECOMMEND TO THOSE USED BY 7 AVISTA?

- 8 A. Yes, I can. The resulting effective transmission allocation factors are shown in Table
- 9

TABLE 3				
Comparison of <u>Transmission Allocation Factors</u>				
Rate <u>Schedule</u>	Avista <u>Allocation</u>	ICNU <u>Allocation</u>		
Sch 1	44.45%	48.71%		
Sch 11/12	9.54%	8.38%		
Sch 21/22	25.28%	24.40%		
Sch 25	18.08%	16.27%		
Sch 31/32	2.25%	1.97%		
Sch 41/49	0.40%	0.27%		
Total	100.00%	100.00%		

10

Q. CAN YOU PROVIDE THE RESULTS OF APPLYING THE 12 CP ALLOCATION OF TRANSMISSION COSTS TO THE MODIFIED PEAK CREDIT ALLOCATION OF PRODUCTION COSTS?

14 A. Yes. This information is provided in Exhibit ____(RRS-8). This exhibit differs from

- 15 Exhibit No. ____(RRS-6) in that transmission costs are 100% allocated on 12 CP. If
- 16 the Peak Credit is retained at all, it should only be retained for production costs.

1 Overall Cost of Service Results

Q. CAN YOU PLEASE PROVIDE A SUMMARY OF THE RESULTS OF THE ECOS STUDIES MODIFIED FOR BOTH OF YOUR RECOMMENDATIONS FOR PRODUCTION COST ALLOCATION AS WELL AS TRANSMISSION COST ALLOCATION?

- 6 A. Yes. This information is provided in Table 4, below, which provides the rate schedule
- 7 returns under Avista's ECOS study, my preferred ECOS study, Exhibit No.
- 8 ____(RRS-5) and the modified Peak Credit (production-only) ECOS study, Exhibit
- 9 No. ___(RRS-8).

		TABL	E 4			
<u>Summa</u>	ry Compariso	on of Cost	of Service	Study Re	<u>sults</u>	
					Exhibit (F	RRS-8)
			Exhibit (F	RS-5)	Modi	fied
	Avis	ta	Recomm	ended	Peak C	redit
	ECOS	Study	ECOS S	Study	ECOS S	Study
	Rate of		Rate of		Rate of	
Schedule	Return	Index	Return	Index	Return	Index
Sch 1	4.50%	0.65	3.92%	0.57	4.09%	0.59
Sch 11/12	13.19%	1.92	13.77%	2.00	13.38%	1.94
Sch 21/22	9.41%	1.37	10.14%	1.47	9.83%	1.43
Sch 25	5.86%	0.85	7.57%	1.10	6.85%	0.99
Sch 31/32	6.28%	0.91	7.56%	1.10	7.02%	1.02
Sch 41/49	6.36%	0.92	6.50%	0.95	6.40%	0.93
Total	6.88%	1.00	6.88%	1.00	6.88%	1.00
Notes:						
Production (fixed)	12 CP Pea	k Credit	4 CP 1	00%	4 CP Peal	c Credit
Production (variable)	12 CP Pea	k Credit	Generation	n 100%	4 CP Peal	c Credit
Transmission	12 CP Pea	k Credit	12 CP 1	.00%	12 CP 1	00%

11

10

As Table 4 shows, the cost returns vary significantly from Avista's calculation.

12

For example, rather than a rate of return index of 0.85 for Schedule 25, under my

Response Testimony Robert R. Stephens Docket Nos. UE-140188 and UG-140189 (Consolidated)

adjusted measure of cost of service, the rate of return index is 1.10, meaning that
 Schedule 25 customers actually are providing revenues to produce a return higher than
 the system average, i.e., indicating that Schedule 25 is currently providing revenues
 above cost of service.

5

III. ELECTRIC REVENUE ALLOCATION ("RATE SPREAD")

Q. PLEASE DISTINGUISH THE REVENUE ALLOCATION STEP IN THE 7 PROCESS FROM THE COST OF SERVICE ANALYSIS.

8 A. As previously mentioned, the cost of service analysis is an empirical analysis of the 9 costs caused by the various customer schedules. In itself, it does nothing to change 10 customers' rates. Rather, determining how much of the revenue requirement should 11 be borne by each rate schedule is the step known as revenue allocation or rate spread.

12 The rate spread should be based on the results of the cost of service study, 13 since cost-based rates tend to be the most economically efficient. However, the rate 14 spread can be influenced by other principles, such as rate continuity, rate moderation 15 and avoidance of rate shock.

16 Q. WHAT IS AVISTA'S PROPOSAL REGARDING RATE SPREAD?

- A. As explained by Company witness Patrick Ehrbar, Avista proposes to spread its
 increase on a uniform percentage basis to all classes.^{17/} Mr. Ehrbar's rationale for this
 rate spread approach is primarily found in his consideration of the cost of service
 study from the 2012 general rate case, where he concludes:
- Those study results along with the cost of service study results in this case demonstrate that all rate schedules, with the exception of the Street and Area Lights rate schedules, have had steady movement closer to the overall rate of return (unity). Therefore, the Company chose to

^{17/} Exh. No. ___(PDE-1T) at 5.

1 2 spread the proposed rate increase on a uniform percentage basis which continues the progress towards unity.^{18/}

3

Q. IS AVISTA'S PROPOSAL REASONABLE?

A. It is clear from his statement that Mr. Ehrbar's proposal is based on the results of
Avista's cost of service study showing that certain classes to varying degrees are
currently over-paying or under-paying, as evidenced by the present relative rate of
return, as shown on Table 6 of Mr. Ehrbar's direct testimony.^{19/} I can accept Mr.
Ehrbar's proposal at Avista's proposed revenue requirement.

9 However, even Mr. Ehrbar's proposal provides very little movement toward 10 cost of service for Schedule 1, which is far below cost of service under any of the 11 ECOS study results shown in Table 4 above. This is indicated by the rate of return 12 indices which range from 0.57 to 0.65. Greater movement toward cost of service for 13 this class is justified from a cost of service view. Mr. Ehrbar's proposed 3.8% 14 increase does little to bring Schedule 1 closer to cost. Even with a 3.8% increase, 15 Schedule 1 would provide rate of return indices of only 0.60 under my recommended ECOS study and 0.68 under Avista's ECOS study. $\frac{20}{}$ 16

17 Q. WHAT DO YOU RECOMMEND FOR RATE SPREAD?

A. Although a greater than 3.8% increase is justified from a cost of service basis, it is
 acceptable in this case. However, the increase for Schedule 1 should not be reduced if
 Avista's approved revenue requirement is lower than proposed by Avista. Rather,
 those savings should accrue to the other classes, all of which are providing revenues
 near or above cost of service presently.

<u>18/</u> <u>Id.</u> at 10.

 $[\]underline{19}$ Id. at 11.

 $[\]underline{20}'$ Based on my recommended ECOS study.

1

IV. ELECTRIC RATE DESIGN

2 Q. WHAT IS AVISTA'S OVERALL PROPOSAL AS IT RELATES TO RATE 3 DESIGN?

A. According to Company witness Ehrbar, the Company is not proposing any changes to
 the existing rate structures within its rate schedules except for changes in rate
 components.^{21/}

7 For Extra Large General Service Schedule 25, the current rate consists of a 8 two-tiered demand charge: (1) \$15,000 for the first 3,000 kVA or less; and (2) an 9 additional demand charge of \$5.25 per kVA for monthly demand in excess of 3,000 10 kVA. Energy charges are broken into three blocks: the first 500,000 kWh, 500,00 11 through 6,000,000 kWh, and all over 6,000,000 kWh. The rates per kWh are \$0.05750, \$0.05177, and \$0.04433, respectively. Avista proposes to change the 12 13 demand charges to \$16,500 for the first 3,000 kVA and \$5.75 per kVA for demand above 3,000 kVA.^{$\frac{22}{}$} The energy charges for the same blocking structure are proposed 14 15 to be \$0.05853, \$0.05266, and \$0.04503, respectively. In addition to these demand 16 and energy charges, there are service voltage discounts, which Avista does not propose to change. 17

18 Q. DO YOU HAVE ANY RECOMMENDATIONS AS REGARDS SCHEDULE 25 19 RATE DESIGN?

A. Yes, I do. As indicated in Mr. Ehrbar's direct testimony, the Company is concerned
 about revenue stabilization, and Mr. Ehrbar goes so far as to propose a revenue
 decoupling mechanism, which I will discuss further below. Although I believe the
 decoupling proposal is unwarranted for Schedule 25 customers, in the case of the

<u>21/</u> <u>Id.</u> at 12.

^{22/} Exh. No. ___(PDE-4) at 3.

Commission choosing to adopt some form of adjustment that works to stabilize revenue, I believe it would be appropriate to increase the Schedule 25 demand charges which, as previously mentioned, are generally used to recover fixed costs. This increase in demand charges would necessitate a reduction in energy charges in order to maintain the overall revenues to be collected from this rate schedule. I will further discuss how this adjustment would help to stabilize revenue.

7 Q. WHAT IS AVISTA'S PROPOSAL REGARDING REVENUE DECOUPLING?

8

- A. Avista is requesting an electric and natural gas decoupling mechanism in this case. I
- 9
- will focus on the electric decoupling mechanism, as described by Mr. Ehrbar:
- 10 The traditional problem is that rates are established in a general rate case to provide revenue to recover the fixed costs to provide service to 11 12 customers. However, the majority of that revenue is received on a volumetric basis, i.e., based on the volume of kWh and therm sales. ... 13 14 [I]f the ratemaking process does not account for the known reduction in 15 kWh sales related to energy efficiency, rates set based on historical test period loads are actually designed to not provide recovery of the 16 Company's costs under normal operating conditions. $\frac{23}{}$ 17
- 18 Avista explains that it seeks a rate mechanism that will provide for greater revenue 19 stability and, at the same time, not discourage energy efficiency efforts by customers.
- 20 Mr. Ehrbar states: "The primary reason Avista is considering decoupling in the first
- 21 place is there is recognition that energy efficiency kWh savings eliminates revenue
- from the utility intended to cover utility costs." $\frac{24}{}$
- 23 Mr. Ehrbar goes on to outline the elements of the electric decoupling 24 mechanism as consisting of four steps.^{25/} Essentially, his proposed method is to 25 determine and fix the allowed non-power supply revenue on a per customer basis.

^{23/} Exh. No. (PDE-1T) at 49-50.

<u>24/</u> <u>Id.</u> at 23.

<u>25/</u> <u>Id.</u> at 54-59.

1		Under this design, as long as the number of customers in each rate schedule stays
2		relatively constant, Avista's revenues that are derived from items that are not power
3		supply related remain relatively constant. Power supply related costs are variable and
4		generally would rise and fall with power supply revenues.
5 6	Q.	DO YOU HAVE AN OPINION AS TO WHETHER AVISTA'S PROPOSED ELECTRIC DECOUPLING MECHANISM SHOULD BE APPROVED?
7	А.	As a general matter, I recommend against decoupling mechanisms as unnecessary
8		because they reduce the utility's incentive to minimize costs. Alternatively, sound
9		utility rate designs, <i>i.e.</i> , efficient price signals, can often provide the results that the
10		utility seeks.
11		I especially find Avista's decoupling proposal inappropriate in its application
12		to Schedule 25 customers, as being both ill-conceived and unnecessary. This issue is
13		addressed in greater detail by ICNU witness Bradley G. Mullins.
14 15 16	Q.	WHY IS THE COMPANY'S PROPOSED ELECTRIC DECOUPLING MECHANISM PARTICULARLY INAPPROPRIATE AS IT PERTAINS TO SCHEDULE 25 CUSTOMERS?
17	А.	First, for Schedule 25, the relatively small number of customers causes the non-power
18		supply revenue per customer to be very large and potentially volatile. This could
19		thwart Avista's goal of stabilizing revenue. Should a Schedule 25 customer shut down
20		(even a small one) it could have a significant impact on the Company's non-power
21		supply revenues. This is not true for other customer classes with much lower per
22		customer revenue levels. An industrial plant closure is a real possibility given the
23		economic climate in eastern Washington and global competition. Customers should
24		not pay increased revenues when energy savings have nothing to do with customers.

1		Second, as I alluded to previously, a much simpler change in the rate design
2		could accomplish much of the revenue stability the Company seeks. By this, I am
3		referring to the shift of some of the cost recovery from the per kWh energy sales to the
4		demand component.
5	Q.	WHY WOULD THIS PROVIDE GREATER REVENUE STABILITY?
6	А.	To begin, demand charges are generally established to recover fixed costs of the utility
7		system, such as fixed production, transmission and distribution costs (i.e., those costs
8		that do not vary with the level of energy sales). Thus, as more of the cost recovery is
9		assigned to the demand charges, more revenue is derived to cover these fixed costs.
10		In addition, to the extent customers would implement significant energy
11		efficiency measures, a smaller impact on Avista would be observed because the
12		energy charges are lower.
13 14	Q.	WHAT IS YOUR SPECIFIC RECOMMENDATION WITH REGARD TO AVISTA'S PROPOSED ELECTRIC DECOUPLING MECHANISM?
15	А.	Whether or not a decoupling mechanism is approved for any other rate schedule, I
16		recommend that it not be approved for Schedule 25. I believe it would be reasonable
17		to increase the demand charge in the first block from the current \$15,000 to as much
18		as \$25,000 and to increase the per-unit charge for demand over 3,000 kVA from \$5.25
19		per kVA to as much as \$6.25 per kVA. Such a change would provide significant
20		improved revenue stability for Avista, if the Commission finds it necessary to adjust
21		rates in order to increase revenue stability.
22 23	Q.	WHAT WOULD THE RESULTING ENERGY CHARGES BECOME UNDER YOUR ALTERNATE PROPOSAL?

A. The energy charges would depend on the overall revenue requirement assigned to therate class. If the maximum increases to demand charges outlined above were adopted,

Response Testimony Robert R. StephensExhibit No. (RRS-1T)Docket Nos. UE-140188 and UG-140189 (Consolidated)Page 29

1at Avista's proposed increase to the rate class, the blocked energy charges would2become \$0.05556, \$0.04999, and \$0.04274 per kWh, respectively, for the blocks3defined by Avista. These figures would change, of course, with any change to the4Schedule 25 revenue allocation.

5 These changes should provide greater revenue stability to Avista and would 6 reduce any disincentives it has related to energy efficiency programs for these 7 customers.

8 Q. DOES THIS CONCLUDE YOUR RESPONSE TESTIMONY?

9 A. Yes, it does.