


# **EXHIBIT A**

# Council Conservation Resource Potential Assessment and Cost-Effectiveness Methodology

Tom Eckman  
Manager, Conservation Resources

Washington Utilities and Transportation  
Commission I-937 Workshop  
September 3, 2009



**How Do We Know How Much is Left To Do?**



[Web](#)

[Images](#)

[Groups](#)

[Directory](#)

[News](#)

## PNW Efficiency Potential

[I'm Feeling Lucky](#)

[Google Search](#)

- [Advanced Search](#)
- [Preferences](#)
- [Language Tools](#)

©2003 Google

# It's Only a Six Step Process

- Step 1 - Estimate *Technical Potential on a per application basis*
- Step 2 – Estimate *Economic Potential on a per application basis*
- Step 3 - Estimate number of applicable units
- Step 4 – Estimate *Technical Potential for all applicable units*
- Step 5 – Estimate *Realizable Potential for all realistically achievable units*
- Step 6 - Estimate *Economic Potential for all applicable units*

# Before You Start – Decide On A Cost-Effectiveness Metric

- Participant Cost Test (PTC)
  - Costs and benefits to the program participant
- Total Resource Cost (TRC)
  - All Quantifiable costs & benefits regardless of who accrues them. Includes participant and others' costs
- Utility Cost Test (UTC)
  - Quantifiable costs & benefits that accrue only to the utility system. Specifically excludes participant costs
- Rate Impact Measure (RIM)
  - Net change in electricity utility revenue requirements.
    - » Attempts to measure rate impact on all utility customers especially those that do not directly participate in the conservation program
    - » Treats “lost revenues” (lower participant bills) as a cost

# Overview of Methodology

- Resource Potentials Assessment
  - Determines technical availability, achievable potential & cost
- IRP Analysis
  - Determines cost-effectiveness level and “targets”
  - Compares all resources
  - Develops low-cost resources first
  - Results in resource acquisition plans
    - » Targets & budgets & programs for conservation

# Source for Methodology

- Regional Act
  - and Council interpretation of the Act
- Bottom line
  - Develop cost-effective resources first
- Defines cost-effective conservation
  - “...estimated incremental system cost no greater than that of the least-cost similarly reliable and available alternative measure or resource...”



# The Basic Formula

***Achievable Potential*** =

Number Units \* Cost-Effective kWh per Unit \* Market Penetration

Number Homes,  
Floor Area of Retail  
Number of TVs,  
Acres Irrigated,  
Pounds Steel


(kWh/Unit at Current Efficiency – kWh/Unit at  
Cost-Effectiveness Limit of Efficiency)

Current Efficiency is adjusted for adopted codes &  
standards and stock turnover (Frozen Efficiency)

Cost-Effective Limit of Efficiency is estimated from  
Portfolio Model Results. It is based on the cost of  
the next lowest cost resource available to meet  
load.

Fraction realistically  
achievable over time

# Generic Methodology for Estimating Conservation Resource Potential & Targets



# Inputs to Resource Potentials Assessment Methodology

## ■ Availability


- Scope of measures
  - » Technologies
  - » Practices
- Applicability territory
  - » Number of units
  - » Units savings
- Achievable over time
  - » Retrofit
  - » Lost-Opportunity

## ■ Costs


- Materials & labor
- Annual O&M
- Periodic Replacement
- Program Admin
- Financing costs
- Externalities
- Other non-electric

# Results of Resource Potential Assessment Methodology


- Summarize availability & cost
  - Supply Curves
  - TRC levelized costs
    - » All Costs (net of benefits) per kWh
  - Lost-Opportunity Supply Curve
  - Retrofit Supply Curve (Non-Lost-Op)
  - Availability timeline
- Apples to apples comparison




# 5<sup>th</sup> Plan's Non Lost-Opportunity Supply Curve



# 5<sup>th</sup> Plan's Lost-Opportunity Supply Curves



# 5<sup>th</sup> Plan's Achievable Potential




# Annual Conservation Acquisitions in 5<sup>th</sup> Plan





# Pace of Conservation Deployment Matters



# Developing 6<sup>th</sup> Plan Achievable Penetration Rates

## Two Approaches

- Historic Perspective
  - Recent Regional Performance
- Forward-Looking
  - Build from Bottom Up
  - Measure-by-Measure Penetration Rates

# Near-Term Achievability




## Historic Perspective

- Program Performance
- Pace of Codes & Standards
- Periodic Survey of Current Stock

## Forward Looking

- Considers Character of Measures
- Implementation Strategies
- Size & Cost
- Physical Availability of Equipment
- Training & Education Requirements

# Historic Perspective



## BPA, Utility & NEEA Programs

- Averaged 150 MWa per year since 2001
- Over 200 MWa in 2007
- Probably >200 MWa in 2008
- At \$40-50 /MWh Avoided Costs

## Codes & Standards

- One third of Savings since 1991
- Large Long-Term Potential
- Near-Term Impact Limited by New Stock Additions & Turnover Rates

# Forward-Looking

## Use a Bottom-Up Approach to Estimate Penetration Rates

- Estimate Annual Penetration Rates by Measure Bundle
- Distinguish Features that Impact Penetration Rate
  - Complexity of Measures
  - Delivery Mechanisms & Decision Makers
  - Current Market Saturation
  - Equipment & Infrastructure Availability
  - Subject to Code or Standard
  - Size & Cost
- $(\text{Annual Penetration Rate}) \times (\text{Annual Units}) \times (\text{Unit Savings})$
- Then Sum of All Measure-Level Supply Curves by Year & Levelized Cost bin

# Penetration Rate "Families"




## ■ Lost-Opportunity

- Emerging Technology
- LO Slow
- LO Medium
- LO Fast


## ■ Retrofit

- New Measure
- In 20 Years
- In 10 Years
- In 5 Years

# Family of Lost-Opportunity Penetration Rates



# Family of Retrofit Penetration Rates





# Residential Lost-Opportunity Achievable Penetration Rate Themes



## LO Slow

- Refrigerators
- Freezers
- Cooking
- Heat Pump Upgrades
- Elec Furnace to HP Conversions

About 540 MWa by 2029

## LO Medium

- Clothes Washer
- Dishwasher
- Clothes Dryer
- Shell & Window Measures
- Window AC Units

About 340 MWa by 2029

## LO Emerging Technology

- Heat Pump Water Heater
- Gravity Film Heat Exchanger

About 600 MWa by 2029

# Residential Retrofit

## Achievable Penetration Rate Themes



### Retro in 5 Years

- Showerheads
- Lighting

About 240 MWa by 2029

### Retro in 15 Years

- Weatherization
- HVAC Conversions

About 750 MWa by 2029

### New Measure Ramp-Up

- Solar DHW
- Solar PV

About 610 MWa by 2029

# Commercial Lost-Opportunity

## Achievable Penetration Rate Themes



### LO Fast

- Lighting Power Density
- Lighting Controls
- Premium HVAC Equipment
- Variable-Speed Chillers
- Glass – New & Replacement
- Simple HVAC Measures – New
- Package Refrigeration Equip
- Exterior Building Lighting
- Street & Roadway Lighting - New

About 740 MWa by 2029

### LO Medium

- Integrated Building Design
- Daylighting
- Complex HVAC Measures
- Street & Roadway Lighting - Repl
- Parking Lighting
- Signage

About 180 MWa by 2029

# Commercial Retrofit

## Achievable Penetration Rate Themes



### Retro in 10 Years

- Lighting Power Density
- Lighting Controls
- Glass – Retrofit
- Simple HVAC Measures
- Insulation
- DCV Restaurant Hoods
- Computer Servers & IT

About 180 MWa by 2029

### Retro in 20 Years

- Controls Commissioning Complex
- Complex HVAC Measures
- Grocery Refrigeration
- Network PC Controls
- Sewage Treatment
- Water Supply

About 350 MWa by 2029

# Industrial Lost-Opportunity

## Achievable Penetration Rate Themes



### LO Fast

- Lighting Power Density
- Lighting Controls

About 70 MWa by 2029

### LO Medium

- Material Handling
- Motor Rewind

About 60 MWa by 2029

# Industrial Retrofit

## Achievable Penetration Rate Themes



### Retro in 10 Years

- Compressed Air Measures
- Centrifugal Fans
- Belts
- Transformers
- Refrigeration & Food Storage
- Chip Fab Measures

About 250 MWa by 2029

### Retro in 20 Years

- Fan & Pump Optimization
- Premium Fan & Pump Equip
- Pulp & Paper Equipment

About 170 MWa by 2029

### New Measure Ramp-Up (?)

- Plant Energy Management
- Energy Project Management
- Integrated Plant Energy Management

About 250 MWa by 2029

# Agriculture Retrofit

## Achievable Penetration Rate

### Retro in 10 Years

- Scientific Irrigation Systems
- Irrigation Hardware
- Dairy



About 110 MWa

# Distribution System Retrofit


## Achievable Penetration Rate



### New Measure Ramp-Up Medium

- Line Drop Compensation
- VAR Management, Phase Load Balancing, & Feeder Load Balancing
- Substation Voltage Regulators & Select Re-Conductoring
- End-of Line Voltage Control Regulators


About 420 MWa by 2029






# Initial Results

## Bottom Up Lost-Opportunity Supply Curve 2010-2019



# Initial Results: Bottom Up Retrofit Supply Curve 2010-2019



# IRP Methodology





- Supply Curves delivered to Portfolio Model
- Portfolio Model finds least cost & risk Plans
  - Plan is resource acquisition & option schedule
  - Includes both conservation & generation
  - Amounts & timing of acquisitions & options
- For conservation this includes
  - » Lost-Opportunity schedule
  - » Non-Lost-Opportunity schedule
  - » A Cost-effectiveness threshold







# IRP Methodology

- Test thousands of potential “planned portfolios”
- Against 750 futures
- Found Plans with low cost & risk
- Tested Alternative Conservation Deployment Schedules
- Regional Conservation Targets
  - Derived from Plans on low-cost low-risk front

# Portfolio Analysis Determines How Much Energy Efficiency to Develop in the Face of Uncertainty




**Portfolio Analysis Model**




slide 36

Efficient Frontier

# Portfolio Model Calculates Risk and Expected Cost Associated With Each Plan Across 750 "Futures"



# Plans Along the Efficient Frontier Permit Trade-Offs of Costs Against Risk



Or . . .

# Utilities Can Just Use the Utility Target Calculator


[http://www.nwccouncil.org/energy/UtilityTargetCalc\\_v1\\_7.xls](http://www.nwccouncil.org/energy/UtilityTargetCalc_v1_7.xls)



# Background Slides

# Regional Act Cost-Effectiveness

# Conservation Measure Cost-Effectiveness "Inputs and Outputs"



# What's A kWh Saved Worth?

- Value of a kWh of savings depends
  - Cost of power in the wholesale market during the time of day, day of week, month of the year and the year it is saved
  - How many years it lasts

Plus ...

## Other Values of Conservation

- Quantifiable Non-Energy Benefits
  - Water savings, maintenance labor
- Distribution system expansion deferral
  - Poles, wires, transformers, substations
- Transmission system expansion deferral
  - Bigger poles & wires
- Externalities: Like CO<sub>2</sub> production
- Regional Act Credit of 10% to conservation

# Why Value Conservation at Wholesale Market Prices?

- Price paid to buy or sell the marginal kWh, or “run” the marginal resource
- At any given time, the marginal resource may or may not be a new power plant
- Conservation often displaces older generation out of the region
- Conservation defers new coal, wind, solar and gas generation

# Timing-Based Value



Shape of Savings



Value of Wholesale Power




Value of kWh Saved



\$




# Council 5<sup>th</sup> Plan Forecast of Future Average Monthly Market Prices (Mid C-Trading Hub)







# Typical "On-Peak" Load Profiles




# Forecast On-Peak Market Power Prices by Month and Year



# Typical Off-Peak Load Profiles



# Forecast Off-Peak Market Power Prices by Month and Year




The Council's Conservation's Cost-Effectiveness Analysis Compares Savings with Forecast Market Prices at the time the savings occur

- *Four “Load Segments” are used to compute the value of savings:*
  - *Weekday “Peak” Load Hours*
  - *Weekday “Ramp Up/Ramp Down” hours and “Weekend Peak” Load Hours*
  - *Weekday and “Weekend Off-Peak” hours*
  - *Weekend and Holiday “Very-Low”*

## Definition of Load Segment Hours

Hour	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Sunday	Holiday
1	3	3	3	3	3	4	4	4
2	3	3	3	3	3	4	4	4
3	3	3	3	3	3	4	4	4
4	3	3	3	3	3	4	4	4
5	2	2	2	2	2	2	2	4
6	2	2	2	2	2	2	2	3
7	2	2	2	2	2	2	2	3
8	2	2	2	2	2	2	2	3
9	1	1	1	1	1	2	2	2
10	1	1	1	1	1	2	2	2
11	1	1	1	1	1	2	2	2
12	1	1	1	1	1	2	2	2
13	1	1	1	1	1	2	2	2
14	1	1	1	1	1	2	2	2
15	1	1	1	1	1	2	2	2
16	1	1	1	1	1	2	2	2
17	1	1	1	1	1	2	2	2
18	1	1	1	1	1	2	2	2
19	2	2	2	2	2	2	2	3
20	2	2	2	2	2	2	2	3
21	2	2	2	2	2	2	2	3
22	2	2	2	2	2	2	2	4
23	3	3	3	3	3	4	4	4
24	3	3	3	3	3	4	4	4

# Each Conservation Measure Has a Different "Cost-Effectiveness" Limit Based on When It's Savings Occur




# Value Depends on Shape of Savings

## Present Value of One kWh Energy Saved

### Assuming a 20-Year Measure Life

Present Value of Measure Benefits  
Assume 20-year Measure Life - Energy Value Only






# But ...

## Longer-Lived Measures Have More Value


Present Value of One kWh Saved  
For Life of Measure - Energy Value Only

Present Value of Measure Energy Benefits  
PV One kWh of Energy For Measure Life



# Present Value of One KWh Saved Considering All Benefits

Present Value of Measure Benefits for Measure Life



# Benefit/Cost Ratio

$$\text{B/C Ratio} = \frac{\text{Present Value All Benefits}}{\text{Present Value All Costs}}$$

- Incorporates all benefits
  - Shape of saved kWh, life of savings, transmission & distribution deferrals, non-energy benefits, quantifiable externalities
- Incorporates all costs
  - Capital & labor, O&M, periodic replacement, program admin & non-energy costs
  - Regardless of who pays
- Incorporates time value of money for both
- Good when greater than 1.0

# Why We Use Benefit/Cost Ratio to Measure Conservation Cost-Effectiveness

- B/C ratio because timing of savings matters
- There is no single cost against which resources are measured\*\*
- All resources must now “compete” for development against the West Coast wholesale market price
- That price varies dramatically by time of day and season of the year
  
- \*\*\*Levelized cost was useful when we estimated the avoided cost as a single generating plant

# Why Cost-Effectiveness?

- Conservation reduces system costs when it is less expensive than alternative supplies
  - The bigger the difference the greater the value
  - No economic benefit to conservation that costs the same as alternative supplies
- Conservation reduces risk relative to some alternatives
  - It carries no risk of fuel or climate change cost
  - Reduces variability of loads
  - Has value even when market prices are low

## The Act defines regional cost-effectiveness as follows:

- "Cost-effective", when applied to any measure or resource referred to in this chapter, means that such measure or resource must be forecast to be reliable and available within the time it is needed, and to meet or reduce the electric power demand, as determined by the Council or the Administrator, as appropriate, of the consumers of the customers at an estimated incremental system cost no greater than that of the least-cost similarly reliable and available alternative measure or resource, or any combination thereof." (Emphasis added).

# Under the Act the term "system cost" means:

- “An estimate of all direct costs of a measure or resource over its effective life, including, if applicable, the cost of distribution and transmission to the consumer, waste disposal costs, end-of-cycle costs, and fuel costs (including projected increases), and such quantifiable environmental costs and benefits as are directly attributable to such measure or resource”

# Act Interpretation

- The Council has interpreted the Act's provisions to mean that in order for a conservation measure to be cost-effective the discounted present value of all of the measure's benefits should be compared to the discounted present value of all of its costs.
- This interpretation was adopted in the Council's 1983 Plan and *has not been modified*



# Why Limit Utility Investments to Cost-effective Measures?

- *It's Immoral* – Unless payments are limited by Rate Impact Measure/Test non-participant's rates go up to subsidize others for savings that aren't cost-effective
- *It's Uneconomic* – Both the utility system and society could serve the same needs at a lower cost and money spent on non-cost effective measure reduces the amount available to secure these energy services from lower cost options
- *It's Illegal* – Bonneville is restricted by the Act and both BPA and the region's utilities are constrained by the Council's model conservation standards for BPA and utility programs

# Comparing Costs of Conservation & Alternatives

- Levelized Cost
  - Compare alternatives with different lifetimes & cash flow streams
- Benefit/Cost Ratio
  - Compare stream of benefits & costs
  - Use NPV to capture time value of costs & benefits
- Perspectives
  - Total Resource Cost Perspective (TRC)
  - Utility Perspective (UPC)
  - Bonneville Perspective
  - Customer Perspective

# Resource Assessment Methods (Availability & Cost)

- Scope of measures
  - Review known measures & practices
  - Over 130 measures & practices 5<sup>th</sup> Plan
  - New measures (technology)
  - Old measures die (codes supplant some)
- Technical potential is
  - Number of applicable units \* Incremental savings per unit

# Determine Measure Applicability

## Account for territory-specific factors

- Fuel saturations (electric vs gas water heat)
- Building characteristics (size, vintage, insulation)
- Building use (retail, office, school ... single-family, multi-family, mobile home)
- System saturations (heat pump, zonal or gas heat)
- Equipment saturations (36 lamps per house)
- Current measure saturations (4 cfls/house)
- Measure life (stock turnover cycle)
- Measure substitution or overlap (either seal ducts on FAF OR convert FAF to HP and seal ducts)

# Determine “Incremental” Savings per Applicable Unit

- Estimated kW & kWh savings
  - By time-of-day, day of week & month of year
- Savings over baseline efficiency
  - Baseline set by codes/standards or current practices
- Climate-sensitive
  - Heating & cooling degree days & solar
- Measure interactions estimated
  - Lighting & HVAC
  - Order of measures applied

# Developing Costs

## ■ Costs

- Materials & labor
- Financing costs
- Annual O&M
- Periodic Replacement
- Program Admin
- Externalities
- Other non-electric

From programs, bids, published sources

If financed use sponsor's cost

Lamp & ballast replacement costs

Marketing, staff,

# The Basic Formula

g1

***Achievable Potential*** = Number of Applicable Units X  
(Energy Use @ Frozen Efficiency - Energy Use @ Cost  
Effectiveness Limit) X Expected Market Penetration

Where :

***Frozen Efficiency Use*** = Current efficiency adjusted for stock  
turnover and adopted changes in codes and standards.

***Cost Effectiveness Limit*** = Cost of next similarly available  
and reliable resource (represented by future wholesale market  
prices) adjusted for T&D cost deferrals, environmental costs &  
risks (fuel price, carbon control, etc.) – *Estimated from  
Portfolio Model Results*

Slide 70


---

g1


Too complicated for P4. See if my version on the next slide is simpler.  
grist, 5/28/2008




# Retail Cost and Efficiency Trade-off Curve Electric Water Heating




# Residential Hot Water Heating Dwelling Unit Supply Curve




# Annual Deployment Rates for Non-Lost Opportunity Resources




# Annual Deployment Rate for Lost Opportunity Resources




# Annual Deployment Rates for All Conservation Resources



# Cumulative Deployment Rate for Non-Lost Opportunity Resources



# Cumulative Deployment Rate for Lost Opportunity Resources



# Cumulative Deployment Rate for All Resources

