

OPTIONAL FIELD DATA COLLECTION FORM FOR INTRASTATE INSPECTORS

NOTES-FIELD INSPECTION

Company: Puget Sound Energy Date(s): July 1, 2, 8, 2008

Unit: Pierce County (Includes Vashon Island)

Field Readings									
Line & Location	Line Size	In.	CP Volts(volts)		Rectifier		Pressures(psig)		Remarks
			P/S	Casing	Volts	Amps	Set	Actual	
767 38 th St Tacoma WA			-1.573						John Batinovich CP Tech
803 S 38 th St Tacoma			Inlet -1.605 Outlet -1.183						
775 S 38 th St Tacoma			-0.337						
2607 6 th Ave 707413			Riser -1.200 Outlet of Union* -0.119						The remaining have been mitigated. *Shorted to Meter Stub.
PS-0244 IC-03047			On -2.305 OFF* -0.975		35.5	1.8			New anode bed installed for this Power Source (for CP protection. Tap Setting 45 * 2 nd meter reading is taken as the impressed current is turned OFF
PS-0273 IC-037079			ON -1.432 OFF -0.975		13.5	39 mA?			

OPTIONAL FIELD DATA COLLECTION FORM FOR INTRASTATE INSPECTORS

Field Readings

Line & Location	Line Size	In.	CP Volts(volts)		Rectifier		Pressures(psig)		Remarks
			P/S	Casing	Volts	Amps	Set	Actual	
Direct Current Voltage Gradient(DCVG) 3014 N 19 th Tacoma			ON* -1.900 OFF* -1.498						Larry O'Neal CP Technician DCVG 4515.1720 Increased Current* and Used two half cells to measure ground current over a section of pipe. Interval approx 2.5 ft. Looking for 10% off the baseline for anomalies that should be checked.
15716 E Main St Puyallup			-0.862						Jim Oliver CP Technician
Meter # 240862			-1.064						
Meter # 241715									
End 7/1/08									
Start 7/2/08									
RS-1349									Procedure for Regulators PSE 4700.1000 DennisDoyle Paul Bench Bill Molden Peak Shaving with 17 tanks of propane. Some questions about PSE storing propane here for another company. New Odorizer and New Pipe supports for the station. Scott did CP around shed. Need to get sketch from

OPTIONAL FIELD DATA COLLECTION FORM FOR INTRASTATE INSPECTORS

Field Readings									
Line & Location	Line Size	In.	CP Volts(volts)		Rectifier		Pressures(psig)		Remarks
			P/S	Casing	Volts	Amps	Set	Actual	
Lock up 6 inch axial flow							247.4		Darryl Gauge 0-300 psi S/N 1035724 Moulden
RS-2562 2101 West Valley Hwy, Sumner									
RS-0174 E River Rd, Tacoma			Outlet pipe -1.042					Inlet 233.6 Outlet 142.4	Station to be retired sometime around September. 6 inch axial flow regulators
Relief set for 152 lbs. Lock up should be 2 pounds under MAOP Relief should be 2- 3 pounds over MAOP.									PSE 4700.1620 Inspecting and Adjusting Relief Valves Cap Relief Flag is Painted to the top of cap.
RS-0699			-2.090 Recorder sensing line - -1.900				Relief 102#	Relief 102#	Pressure Gauge -- Bill 0-300# Calibration Due 08/07/08
RS-2661			-1.336 On outlet of 1 st stage.					Inlet 234 Inter 141 Outlet 21.4	

OPTIONAL FIELD DATA COLLECTION FORM FOR INTRASTATE INSPECTORS

Field Readings													
Line & Location	Line	Size	In.	CP Volts (volts)	P/S	Casing	Rectifier	Volts	Amps	Pressure (psig)	Set	Actual	Remarks
RS-2661													Gauge 0-30, Bill Expires 08/07/08
END 7/2/08													
Start 7/8/08													
OT-0044													Odorator #2732 Expires 4/25/09 S/N 293378 (4-14 range of flammability) Max Allowed 0.8
Bethel High School													0.20 Read - 0.17% Actual from chart.
ES Valves													
Darrell Hahito													Valve Exercised
VA-05359													Valve Exercised
VA-06771													Valve Exercised
ES Valves													
Ralph Yerbury													
VA-05347													Valve Exercised
VA-07152													Valve Exercised
VA-05290													Valve Exercised
END 7/8/08													